

June 2020
EM2020-0094

Surface Water Data at Los Alamos National Laboratory, Water Year 2017

Newport News Nuclear BWXT-Los Alamos, LLC (N3B), under the U.S. Department of Energy Office of Environmental Management Contract No. 89303318CEM000007 (the Los Alamos Legacy Cleanup Contract), has prepared this document. The public may copy and use this document without charge, provided that this notice and any statement of authorship are reproduced on all copies.

CONTENTS

INTRODUCTION.....	1
Qualifiers	1
STREAM DISCHARGE GAGE STATIONS	5
Station Identification Numbers	5
Data Collection and Computation.....	5
Accuracy of Records	6
Data Presentation.....	6
Los Alamos/Pueblo Watershed.....	9
E026 Los Alamos Canyon below Ice Rink.....	11
E030 Los Alamos Canyon above DP Canyon.....	14
E038 DP Canyon above TA-21	17
E039.1 DP Canyon below Grade Control Structure	19
E040 DP Canyon above Los Alamos Canyon.....	23
E042.1 Los Alamos above Low Head Weir	26
E050.1 Los Alamos Canyon below Low Head Weir.....	29
E055 Pueblo Canyon above Acid Canyon	32
E055.5 South Fork of Acid Canyon	35
E056 Acid Canyon above Pueblo Canyon	38
E059.5 Pueblo Canyon below Los Alamos County WWTF.....	41
E059.8 Pueblo Canyon below Wetlands	44
E060.1 Pueblo Canyon below Grade Control Structure.....	47
Sandia Watershed	50
E121 Sandia Canyon Right Fork at Power Plant	51
E122 Sandia Canyon near Roads and Grounds at TA-03	54
E123 Sandia Canyon below Wetlands	57
E124 Sandia above Firing Range.....	60
E125 Sandia Canyon above SR 4.....	63
Mortandad Watershed.....	66
E201 Mortandad Canyon above Ten Site Canyon.....	67
E201.5 Ten Site Canyon above Mortandad Canyon.....	70
E204 Mortandad Canyon at LANL Boundary	73
E229.3 Cañada del Buey at SR 4.....	76
Pajarito Watershed.....	79
E240 Pajarito Canyon below SR 501	80
E243 Pajarito Canyon above Two Mile Canyon.....	83
E244 Two Mile Canyon above Pajarito Canyon.....	86
E245.5 Pajarito Canyon above Three Mile Canyon	89
E246 Three Mile Canyon above Pajarito Canyon	92
E250 Pajarito Canyon above SR 4.....	95
Water/Cañon de Valle Watershed.....	98
E252 Water Canyon above SR 501	100
E253 Cañon de Valle above SR 501.....	103
E256 Cañon de Valle below MDA P.....	106
E265 Water Canyon below SR 4.....	109
E267 Potrillo Canyon above SR 4	112
Ancho/Chaquhui Watershed	115
E275 Ancho Canyon below SR 4	116

E338 Chaquehui at TA-33	119
E340 Chaquehui Tributary at TA-33.....	122
PRECIPITATION GAGE STATIONS	125
Data Collection and Computation.....	125
Accuracy of Records	125
Data Presentation.....	125
Extended Precipitation Network	126
E038 DP Canyon above TA-21	128
E042.1 Los Alamos above Low Head Weir	130
R055.5 South Fork of Acid Canyon.....	132
E121.9 Sandia Canyon East of Power Plant.....	134
E200.5 Mortandad Canyon Tributary Batch Plant.....	136
E203 Mortandad Canyon below Sediment Traps.....	138
E240 Pajarito Canyon below SR 501	140
E245.5 Pajarito Canyon above Three Mile Canyon	142
E253 Cañon de Valle above SR 501.....	144
E257 Cañon de Valle Tributary at TA-16 Burn Grounds.....	146
E262.4 PHERMEX.....	148
E265 Water Canyon below SR 4.....	150
E267.4 TA-36 Minie Site.....	152
E340 Chaquehui Tributary at TA-33.....	154
Meteorological Tower Data	156
TA-06 Meteorological Tower	157
TA-49 Meteorological Tower	159
TA-53 Meteorological Tower	161
TA-54 White Rock Meteorological Tower	163
North Community Meteorological Tower	165
REFERENCES.....	167
ABBREVIATIONS, ACRONYMS, AND GLOSSARY	167

Figures

Figure 1	Location of watersheds, canyons, streams, stream gages, and rain gages on LANL property	3
Figure 2	The total monthly volume (acre-ft) for WY 2017 for Los Alamos Canyon and DP Canyon.....	10
Figure 3	The total monthly volume (acre-ft) for WY 2017 for Acid Canyon and Pueblo Canyon ...	10
Figure 4	The total monthly volume (acre-ft) for WY 2017 for Sandia Canyon	50
Figure 5	Total monthly volume (acre-ft) for WY 2017 in Mortandad Canyon and Cañada del Buey	66
Figure 6	Total monthly volume (acre-ft) for WY 2017 for Pajarito Canyon	79
Figure 7	Total monthly volume (acre-ft) for WY 2017 in Water Canyon, Cañon de Valle, and Fence Canyon.....	99
Figure 8	Total monthly volume (acre-ft) for WY 2017 in Ancho Canyon and Chaquehui Canyon.....	115

Figure 9 Total monthly precipitation for the extended precipitation network gages for WY 2017, excluding December 2016 to March 2017, when the gages were shut down for winter 127

Figure 10 The total monthly precipitation for the meteorological towers for WY 2017. 156

INTRODUCTION

The annual water data report from Los Alamos National Laboratory (LANL) contains flow data from 35 stream gage stations and precipitation data from the extended network and meteorological observation stations that cover most of LANL's property (Figure 1) and is for water year (WY) 2017 from October 1, 2016 to September 30, 2017. Data are collected from LANL's upper boundary, approximated by NM 501, to the lower boundary, approximated by NM 4. Gage station data are used to support the monitoring of Los Alamos/Pueblo Canyons under the March 2005 and June 2016 Compliance Orders on Consent (Consent Order), the Buckman Direct Diversion Emergency Notification System, monitoring of Sandia Canyon for wetland stabilization, LANL's Environmental Surveillance Program, and activities directed by the "Investigation Report for Water Canyon/Cañon de Valle" (LANL 2011). Precipitation gage station data support all the programs that the stream discharge gage stations support as well as the Multi-Sector General Permit.

Los Alamos, New Mexico, has a semiarid climate with an average rainfall of about 19 in. per year. Over 30% of the area is dominated by ponderosa pine stands at higher elevations that transition to piñon-juniper woodlands as elevation decreases. The Pajarito Plateau is separated into fingerlike mesas by west-to-east-oriented canyons. The majority of the stream discharge gage stations are located within ephemeral streams. These streams flow briefly in response to precipitation that occurs in the surrounding area or snowmelt runoff from higher elevations. The remainder of the year, the streams are dry with no flow. Perennial springs are present on the flanks of the Jemez Mountains and supply base flow to the upper reaches of some canyons, but the volume of flow is insufficient to maintain surface flows across the facility mostly because of losses in stream channel transmission. The remainder of the stream gage stations are located in either intermittent or perennial streams.

Qualifiers

Raw data are qualified using a standard set of numbers to better determine the quality of the data. Qualifiers are noted within the daily peak discharge tables with a letter or letters. Unless otherwise noted, the data are qualified as good continuous records. Some of the data were reliably estimated. Data are reliably estimated during short periods of time using precipitation data to verify no precipitation and/or, when applicable, upstream or downstream stream-gage data.

Qualifier Description	Qualifier	Comments
Missing data	M	Data were missing for an unknown or inexplicable reason.
Ice	I	Ice or snow was present in the channel.
Testing	T	Field crews were present on-site and tested the equipment.
Equipment malfunction	E	Equipment failure occurred or equipment was rendered inoperable by high-flow event.
Silting and scouring	SS	A datum shift was applied because of silting or scouring.
Datum shift	DS	A datum shift was applied to the data.
Inactive	IA	The gage was inactive because of an event that damaged the station beyond immediate repair.
Snow	S	Precipitation as snow.




Figure 1 Location of watersheds, canyons, streams, stream gages, and rain gages on LANL property

STREAM DISCHARGE GAGE STATIONS

Station Identification Numbers

The U.S. Geological Survey (USGS), Water Resources Division, assigns a unique identification number to each stream gage station it establishes. All sites numbered since 1950 are part of the downstream order system. In this report, the station numbers increase from upstream to downstream.

This report adheres to the USGS convention of downstream order system. Because of the proximity of stations in this network, the first five digits of all station numbers are 08313. This five-digit number string is replaced with the letter E in the station number as an abbreviation.

Data Collection and Computation

A complete record at a gage station includes stage and discharge measurements from a stream or channel, directly observed factors that affect the stage/discharge relationship, and weather records. Integrated 5-min records of stage were provided from a data logger or direct readings were collected and verified on-site. Discharge is measured using meters and methods adopted by the USGS. The methods can be found in the USGS Technique of Water Resources Investigations, Book 3 (Carter and Davidian 1968), Chapter A6; and the USGS Water Supply Paper 2175 (Rantz 1982).

Rating curves were developed using the stage-discharge relationship curve determined from measured stage and the corresponding discharge. When it is necessary to define the discharge extremes outside the range for current meter measurements, the curve is extended using logarithmic plotting; velocity area studies; results of indirect measurements of peak discharge, such as slope area or contracted opening measurements, and computations of flow over dams or weirs; or step-backwater techniques.

Daily peak discharge is computed by applying daily peak gage height (stage) to the stage discharge curves or tables. If the stage-discharge relationship is subject to change because of frequent or continual change in the physical features that form the control, the daily peak discharge is computed by the shifting-control method. In the shifting-control method, correction factors based on individual discharge measurements and notes by personnel taking the measurements are applied to the gage heights before discharges are determined from the curves or tables. Occasionally, during high-magnitude events, the gage equipment will not capture the peak gage height. In such cases, when a visual high-water mark has been observed, the peak gage height is estimated.

The shifting-control method is also used if the stage-discharge relationship for a station is temporarily changed by natural vegetation, aggradation and degradation or debris, and sediment accumulation on the control. At some canyon bottom, northern, and perennial stream gage stations, the stage-discharge relationship is affected by ice in the winter and it is not possible to compute discharge. Temperature data, precipitation data, and discharge records from nearby stations are used to estimate discharge during these periods.

For some gage stations, periods occur when no gage height record is obtained or the recorded gage height is so faulty that it cannot be used to compute daily discharge or contents. This occurs when the data logger stops recording or otherwise fails to operate properly. For such periods, the daily discharge is estimated on the basis of recorded range-in-stage, previous and subsequent records, discharge measurements, weather records, and record comparisons made against other stations in the same or nearby basins.

Accuracy of Records

The following two factors determine the accuracy of stream discharge records:

- Stability of the stage-discharge relationship or, if the control is unstable, the frequency of discharge measurements
- Accuracy of measurements of stage, accuracy of discharge measurements, and interpretations of records

The number of significant figures used to report daily peak discharge is based solely on the magnitude of the discharge value. The same method is applied to the monthly summary table in acre-ft per year:

If the value (ft ³ /s) is	Then it is reported as
less than 1 ft ³ /s	nearest hundredth
1–10 ft ³ /s	nearest tenth
10–1000 ft ³ /s	whole number
above 1000 ft ³ /s	three significant figures

Data Presentation

The records published in this report consist of three parts for each stream discharge gage station:

- Station analysis summary
- Station manuscript description with photo
- Data table for WY 2017 (October 1, 2016, to September 30, 2017)

The station analysis supplements each daily values table and includes a description of monitoring equipment, problems associated with data collection during the water year, and other information used to compute stream flow discharge.

Equipment: A description of the monitoring equipment is provided.

Datum Correction: Datum corrections for the period of record are listed.

Gage-Height Record: Information is provided regarding the stage record itself, including accuracy and periods of inoperability.

The station manuscript provides data under various headings: station location, drainage area, revised records, period of record, gage, average volume, and other points pertinent to station operation and regulation. Each continuous record of discharge includes the following categories of descriptions.

Rating: A description of the rating used to calculate discharge at the stream gage site.

Location: The most accurate and available maps, coupled with the light detection and ranging digital elevation model (LIDAR DEM) using North American Datum of 1983 (NAD 83), provide location information.

Drainage Area: The most accurate and available maps provide drainage area measurements. The accuracy of drainage area measurements varies, depending on the type of map available for this purpose.

Revised Records: Because of new information, published records occasionally are found to be incorrect, and revisions are printed in later reports. If the record has been revised, the report in which the most recently revised figure was first published is given.

Period of Record: The period of record is the time during which published records exist for a station or its equivalent station. An equivalent station is one that was in operation when the present station was not in operation and was located so that its records can reasonably be considered equivalent to records from the present station.

Gage: This section describes the type of gage in current use. Under this heading, the datum of the current gage referred to in the National Geodetic Vertical Datum of 1929 (NGVD 29) (see Abbreviations, Acronyms, and Glossary) is a condensed history of the types, locations, and data of previous gages.

Average Volume: The average volume is the average of the annual discharged volume beginning in WY 2012.

Maximum Discharge for Period of Record: The record includes the maximum stage and discharge. Unless otherwise qualified, the maximum discharge or content is the instantaneous maximum corresponding to the highest stage that occurred. The highest stage may have been obtained from a graphic or digital recorder, a crest-stage gage, by direct observation of a non-recording gage or high-water-mark surveys. The minimum stage and discharge are included for perennial streams.

If the maximum stage did not occur on the same day as the maximum discharge or content, it is given separately. Maximum discharge before WY 2010 should be considered estimated because of differences in the current validation and verification methodology.

Maximum Discharge for Current Water Year: Maximums given are similar to those for the period of record. The time for occurrence of peaks is expressed in 24-hr local standard time. For example, 12:30 A.M. is 0030 and 1:30 P.M. is 1330. The minimums for perennial streams are recorded in a similar manner as the maximums.

The daily table of discharge records for stream discharge gage stations gives the daily peak discharge for each day of the water year. In the monthly summary for the table, the row titled "Total Volume (acre-ft)" contains the sum of the daily figures of volume for each month in acre-feet, the row titled "Max Daily Peak (acre-ft)" contains the maximum daily volume for the month in acre-feet, the row titled "Min Daily Peak (acre-ft)" contains the minimum daily volume for the month in acre-feet, and the row titled "Missing Days" contains the number of days missing for each month.

Summary of Discharges from Stream Monitoring Stations for WY 2017

Canyon Sites	Estimated Days with Flow	Total Volume (acre-ft)	Instantaneous Maximum Discharge (ft ³ /s)
E026 Los Alamos Canyon below Ice Rink	258	175	4.7
E030 Los Alamos Canyon above DP Canyon	70	205	12
E038 DP Canyon above TA-21 ^a	52	37	205
E039.1 DP Canyon below Grade Control Structure	113	78	150
E040 DP Canyon above Los Alamos Canyon	90	32	101
E042.1 Los Alamos above Low Head Weir	40	105	51
E050.1 Los Alamos Canyon below Low Head Weir	31	41	56
E055 Pueblo Canyon above Acid Canyon	36	62	33
E055.5 South Fork of Acid Canyon	151	n/a ^b	n/a
E056 Acid Canyon above Pueblo Canyon	328	44	24
E059.5 Pueblo Canyon below WWTF ^c	308	102	61
E059.8 Pueblo Canyon below Wetlands	200	27	1.9
E060.1 Pueblo Canyon below Grade Control Structure	19	0.36	0.58
E121 Sandia Canyon Right Fork at Power Plant	365	514	87
E122 Sandia Canyon Left Fork at Asphalt Plant	362	67	9.1
E123 Sandia Canyon below Wetlands	359	685	78
E124 Sandia above Firing Range	11	25	34
E125 Sandia Canyon above SR 4	1	<0.01	1.1
E201 Mortandad Canyon above Ten Site Canyon	7	0.68	2.9
E201.5 Ten Site Canyon above Mortandad Canyon	1	0.45	31
E204 Mortandad Canyon at LANL Boundary	7	0.26	3.1
E229.3 Cañada del Buey at SR 4	12	0.32	1.5
E240 Pajarito Canyon below SR 501	5	0.03	0.14
E243 Pajarito Canyon above Two Mile Canyon	8	0.01	0.14
E244 Two Mile Canyon above Pajarito Canyon	104	4.0	31
E245.5 Pajarito Canyon above Three Mile Canyon	232	91	43
E246 Three Mile Canyon above Pajarito Canyon	2	0.03	0.11
E250 Pajarito Canyon above SR 4	0	0	0
E252 Water Canyon above SR 501	336	24	0.21
E253 Cañon de Valle above SR 501	0	0	0
E256 Cañon de Valle below MDA ^d P	244	62	1.9
E265 Water Canyon below SR 4	144	3.8	0.34
E267 Potrillo Canyon above SR 4	0	0	0
E275 Ancho Canyon below SR 4	5	17	252
E338 Chaquehui at TA-33	12	4.0	3.0
E340 Chaquehui Tributary at TA-33	0	0	0

^a TA = Technical Area.^b n/a = Not applicable.^c WWTF = Los Alamos County Wastewater Treatment Facility.^d MDA = Material Disposal Area.

Los Alamos/Pueblo Watershed

The Los Alamos Canyon/Pueblo Canyon watershed is located at the northern end of Los Alamos County and LANL. The watershed heads on U.S. Forest Service land in the Sierra de los Valles to the west and northwest of LANL. The highest point in the watershed is at the summit of Pajarito Mountain at an elevation of 3182 m (10,441 ft). The watershed extends eastward from the headwaters across the Pajarito Plateau for about 30.4 km (18.9 mi) to its confluence with the Rio Grande at an elevation of 1678 m (5504 ft). The Los Alamos/Pueblo watershed encompasses approximately 57 mi². The watershed includes Los Alamos, Pueblo, and DP Canyons. Bayo, Guaje, Rendija, and Barrancas Canyons are tributary canyons in the watershed. The watershed contains numerous springs, perennial and ephemeral stream segments, and alluvial groundwater. Portions of Santa Fe National Forest, U.S. Department of Energy– (DOE-) managed property, Los Alamos County (including the Los Alamos townsite), Santa Fe County, and Pueblo de San Ildefonso tribal lands are located within the Los Alamos/Pueblo watershed.

Pueblo Canyon is located on the north side of the Los Alamos townsite and extends from the Jemez Mountains to its confluence with Los Alamos Canyon, approximately 4.5 mi east of the Los Alamos townsite at the intersection of NM 502 and NM 4. Los Alamos Canyon is the southernmost canyon in the watershed. The Los Alamos/Pueblo watershed contains, or may influence, five wetland areas totaling approximately 12.16 acres.

Figure 2 shows the total volume of discharge per month from the upper boundary station in Los Alamos Canyon to the lower boundary stations. As the discharge travels downstream, a considerable amount of transmission loss typically occurs from station to station. During the monsoon season, discharge will not always begin at the upper boundary stations (upper boundary is E026, lower boundary is E050.1) and is highly dependent on the storm track.

Figure 3 shows the total volume of discharge per month from the stream gage discharge stations within Acid and Pueblo Canyons, located within the Los Alamos/Pueblo watershed. Station E055 is the highest station within Acid Canyon and receives the most discharge within this particular section of the watershed. As discharge travels downstream, it is lost via channel transmission. The remainder of the sites within Acid Canyon did not have any discharge. Gage E060.1 is located downstream of the Los Alamos County Waste Water Treatment Facility (WWTF) and the Pueblo Canyon grade-control structure. The treatment facility releases effluent daily. Most of the year, this discharge does not reach E060.1, located 1.71 mi downstream of the WWTF.




Figure 2 The total monthly volume (acre-ft) for WY 2017 for Los Alamos Canyon and DP Canyon




Figure 3 The total monthly volume (acre-ft) for WY 2017 for Acid Canyon and Pueblo Canyon

E026 Los Alamos Canyon below Ice Rink

Location. Lat 35° 52' 49", long -106° 19' 30", NE ¼, Sec. 17, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 7.07 mi².

Period of Record. February 26, 2001, to September 30, 2017.

Revised Record. Drainage area (2006); Section (2007).

Gage. Data logger with radio telemetry. Elevation of gage is 7177 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 207 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 850 ft³/s, September 13, 2013, maximum gage height exceeded.

Maximum Discharge for Current Water Year. Maximum discharge, 4.7 ft³/s, March 23, 2017, gage height 1.82 ft.



E026 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Milltronics sonic probe. The system is powered by a solar-panel battery system housed in a National Electrical Manufacturers Association (NEMA) shelter on top of a 24-in. corrugated metal pipe (CMP) well. The station is equipped with two ISCO samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples. The ISCO samplers are housed in a separate 3- x 4-ft metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurement above the wading stage. All high-flow measurements will be by slope-area or critical-depth computation methods.

Datum Correction. Levels run on November 21, 2001, found the gage to be within limits.

Gage-Height Record. The data logger referenced to the inside staff gage gave a complete and satisfactory record, except for December 13 to December 19, 2016, when the data were missing and December 21, 2016, to February 2, 2017, when the gage sensor was affected by snow and ice in the channel.

Rating. The channel at the gage is about 20 ft wide and straight for 20 ft upstream where it bends to the left and then runs straight for about 150 ft downstream. The streambed through this reach is primarily gravel with cobbles. The low-flow control is a rock-and-gravel riffle located 15 ft downstream from the gage. The channel is the control for medium and high stages. The buildup and scour of this control lead to shift changes during the water year.

Rating No. 3 was developed based on measurements made during the period of record.

Flow is partially regulated by the Los Alamos Reservoir about 1.5 mi upstream of the gage and the draining of this reservoir. The gage of reference at this station is the inside reference point (the reference point measure). At low and medium flows, the staff plate stage reading will be lower than the stilling well stage reading.

One discharge measurement was made during the year.

Discharge. Discharges were computed from Rating No. 3.

E026 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.04	0.22	0	I ^a	I	0.06	3.5	0.60	0.52	0.36	0.04	0.04
2	0.04	1.1	0.07	I	I	0.11	2.6	0.72	0.29	0.18	0.05	0.02
3	0.02	0.60	0.36	I	1.0	0.05	2.6	1.2	2.4	0.22	0.04	0.09
4	0.29	0	0	I	1.0	0.00	3.2	1.3	0.36	0.52	0.04	0.05
5	0	0	0.18	I	0.70	0.07	2.5	2.1	0.14	0.11	0.04	0.09
6	0.02	0	0.04	I	1.0	0	2.5	1.5	0.44	0.04	0.04	0.04
7	0.02	0	0	I	0.29	0	2.7	1.0	1.3	0.18	0.04	0.04
8	0	0	0	I	1.0	0	3.0	1.1	0.18	0.14	0.07	0.04
9	0.02	0	0	I	1.1	0	3.2	1.8	0.14	0.05	0.04	0.02
10	0	0	0.04	I	2.0	0	3.5	1.1	0.22	0.07	0.04	0.04
11	0.02	0	0.05	I	2.8	0	3.5	1.3	0.44	0.07	0.04	0.04
12	0	0	0	I	2.7	0.07	3.4	1.1	0.44	0.07	0.04	0.02
13	0.02	0	M ^b	I	1.9	0.44	3.4	1.3	0.18	0.11	0.04	0.04
14	0.05	0	M	I	1.8	1.0	4.0	0.70	0.22	0.11	0.02	0.04
15	0.07	0	M	I	1.4	1.3	3.7	0.70	0.29	0.36	0.04	0.05
16	0.02	0	M	I	1.5	2.2	3.2	0.52	0.90	0.09	0.04	0.14
17	0.02	0	M	I	1.4	2.4	3.0	0.90	0.22	0.36	0.04	0.04
18	0	0	M	I	1.0	2.9	2.7	0.60	0.36	0.18	0.04	0.14
19	0	0	M	I	0.75	4.0	2.7	1.1	2.0	0.07	0.04	0.09
20	0	0.02	0	I	0.89	4.0	2.2	0.60	0.36	0.05	0.04	0.04
21	0	0	I	I	1.0	4.0	1.6	0.36	0.22	0.04	0.05	0.05
22	0	0	I	I	0.74	4.3	1.4	0.90	0.22	0.04	0.02	0.04
23	0	0	I	I	0.97	4.7	1.8	0.52	0.44	0.04	0.07	0.02
24	0	0	I	I	1.1	4.2	1.1	0.36	0.05	0.04	0.04	0.04
25	0	0.14	I	I	0.30	4.2	2.5	0.22	0.14	0.04	0.04	0.07
26	0	0.07	I	I	0.32	4.0	1.0	0.14	0.90	0.29	0.05	0.04
27	0	0	I	I	0.20	3.7	1.1	0.14	1.9	0.07	0.05	0.44
28	0	0	I	I	0.20	3.7	0.70	0.18	0.80	0.07	0.04	1.9
29	0	0	I	I		3.9	0.70	0.44	1.6	0.09	0.04	1.5
30	0	0	I	I		3.9	0.80	0.52	0.29	0.11	0.04	1.0
31	0		I	I		4.5		0.29		0.04	0.05	

^a I = Ice or snow present in channel.^b M = Data were missing for an unknown or inexplicable reason.

E026 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0.01	I*	I	21	62	72	13	3.0	1.3	1.1	1.6	175
Max Daily Peak (ft³/s)	0.29	1.1	0.36	I	2.8	4.7	4.0	2.1	2.4	0.52	0.07	1.9	4.7
Min Daily Peak (ft³/s)	0	0	0	I	0	0	0	0	0	0	0	0	0
Missing Days	0	0	17	31	2	0	0	0	0	0	0	0	50

* I = Ice or snow present in channel.

E030 Los Alamos Canyon above DP Canyon

Location. Lat 35° 52' 21", long -106° 15' 36", SW ¼, Sec. 13, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 8.57 mi².

Period of Record. July 1994 to September 30, 2017.

Revised Record. Drainage area (2006); Township (2007).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6619 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 101 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 970 ft³/s, September 13, 2013, gage height 4.04 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 12 ft³/s, September 29, 2017, gage height 1.60 ft.



E030 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on an 18-in. CMP well on the left bank. The station is equipped with an ISCO pump sampler (12-count 1-L glass or polyethylene bottles) to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stages.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the entire year.

Rating. The streambed is sand and gravel and subject to slight movement during flow events. The channel is straight for 300 ft above the gage and 50 ft below. Vegetation on the bank is sparse grass.

Rating No. 3 was used for the entire water year.

No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 3.

E030 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0.26	3.9	0.72	0	0	0	0
2	0	0	0	0	0	0.18	2.9	0.64	0	0	0	0
3	0	0	0	0	0	0.01	2.3	0.64	0	0	0	0
4	0	0	0	0	0	0	3.3	0	0	0	0	0
5	0	0	0	0	0	0	2.4	0	0	0	0	0
6	0	0	0	0	0	0	2.1	0	0	0	0	0
7	0	0	0	0	0	0	2.0	0	0	0	0	0
8	0	0	0	0	0	0	2.2	0	0	0	0	0
9	0	0	0	0	0	0	2.4	0.49	0	0	0	0
10	0	0	0	0	0	0	2.6	0.30	0	0	0	0
11	0	0	0	0	0	0	2.5	0.07	0	0	0	0
12	0	0	0	0	0	0	2.4	0	0	0	0	0
13	0	0	0	0	0	0.69	2.4	0	0	0	0	0
14	0	0	0	0	0	0.85	2.5	0	0	0	0	0
15	0	0	0	0	0	1.3	2.7	0	0	0	0	0
16	0	0	0	0	0	1.6	2.5	0	0	0	0	0
17	0	0	0	0	0	1.7	2.2	0	0	0	0	0
18	0	0	0	0	0	2.1	2.0	0	0	0	0	0
19	0	0	0	0	0	2.8	1.8	0	0	0	0	0
20	0	0	0	0	0	3.1	1.7	0	0	0	0	0
21	0	0	0	0	0	3.1	1.6	0	0	0	0	0
22	0	0	0	0	0.14	3.5	1.4	0	0	0	0	0
23	0	0	0	0	0.24	4.0	1.1	0	0	0	0	0
24	0	0	0	0	0.53	4.0	1.0	0	0	0	0	0
25	0	0	0	0	0.56	3.3	0.90	0	0	0	0	0
26	0	0	0	0	0.76	2.8	0.90	0	0	6.5	0	0
27	0	0	0	0	0.22	2.5	0.81	0	0	0.02	0	8.5
28	0	0	0	0	0.35	3.2	1.1	0	0	0	0	5.3
29	0	0	0	0		3.9	1.1	0	0	0	0	12
30	0	0	0	0		3.1	0.85	0	0	0	0	0
31	0		0	0		3.1		0		0	0	

E030 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	2.6	90	103	3.4	0	0.80	0	5.5	205
Max Daily Peak (ft³/s)	0	0	0	0	0.76	4.0	3.9	0.72	0	6.5	0	12	12
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0.68	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E038 DP Canyon above TA-21

Location. Lat 35° 52' 49", long -106° 16' 58", SW ¼, sec. 14, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.22 mi².

Period of Record. April 26, 2000, to September 30, 2017.

Revised Record. Drainage area (2006); Section (2007).

Gage. Data logger with radio telemetry. Elevation of gage is 7087 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 37 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 310 ft³/s, July 12, 2013, and September 13, 2013, gage height 4.5 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 205 ft³/s, July 26, 2017, gage height 3.95 ft.



E038 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble self-contained bubbler system. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with two ISCO pump samplers (one 12-count 1-L glass or polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples. The ISCO samplers are housed in a separate shelter, a 3- x 4-ft metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage. All high-flow measurement will be by slope-area or peak-flow computation methods.

The station is also equipped with a tipping bucket rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. Levels run in July 2005 show the gage to be within limits.

Gage-Height Record. The data logger referenced to the outside gage gave a complete and satisfactory record for the year, except for November 18–20 and 25–26, and December 4–6, 10–13, 17–26 and 29–30, 2016; January 4–19, 21–25, and 28–31, 2017; February 1–2, 4–5, 13–16, 23–26, and 28, 2017; and March 2–3 and 7, 2017, because of ice and snow in the channel.

Rating. The channel is about 10 ft wide and straight for about 30 ft upstream and downstream. The streambed through this reach is primarily sand, gravel, and larger boulders. The low-flow control is a rock outcrop downstream from the gage about 5 ft away. The channel is the control for medium and high stages.

Rating No. 3 was developed using past discharge measurements and verified with current measurements.

No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 3.

E038 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	I*	0	1.8	0	2.2	0	0	1.5
2	0	0	0.03	0	I	I	0.46	0	0	0	0	0
3	0.12	0	0	0	0	I	0	0	0	0	0.67	0
4	0	13	I	I	I	0	0.67	0	0	0	0	0
5	0	15	I	I	I	0	0	0	0	0	0	0
6	0	0.52	I	I	0	0	0	0.21	2.1	0	0	0
7	0	0	0	I	0	I	0	0	11	0	76	0
8	0.52	0	0	I	0	0	0	0	0	111	0	0.82
9	0	0	0	I	0	0	0	7.2	0	0	0	0
10	0	0	I	I	0	0	0	1.1	0	0	0	0
11	0	0	I	I	0	0	0	0	0	0	20	0
12	0	0	I	I	0	0	0	0	0	0	0.03	16
13	0	0	I	I	I	0	0	0	0	0	0	0
14	0	0	0	I	I	0	0	0	0	0	0	0
15	0	0	0	I	I	0	0	0	0	0	0	0
16	0	0	0.73	I	I	0	0	0	0	0	0	0
17	0	0	I	I	0	0	0	0	0	0	0	0
18	0	I	I	I	0	0	0	0	0	0	0	0
19	0	I	I	I	0	0	0	0.73	0	0	2.5	0
20	0	I	I	0	0	0	0	0	0	0	0	0
21	0	2.3	I	I	0	0	0	0	0	0	11	0
22	0	0	I	I	0	0	0	0	0	0	0	0
23	0	0	I	I	I	0	0	0	0	0	21	1.9
24	0	0	I	I	I	0	0	0	0	0	0	0
25	0	I	I	I	I	0	0	0	3.4	0	0	0
26	0	I	I	0	I	0	0	0	0.94	205	0	24
27	0	0.39	0	0	0.09	0	0	0	0	2.1	0.64	36
28	0	0	0	I	I	0.09	0.39	0	0	0.18	0	109
29	0	0	I	I		0.64	1.1	0	0	45	7.5	24
30	0	0	I	I		0	0.52	0	0	0.06	0	10
31	0		0	I		0		0		1.1	0	

* I = Ice or snow present in channel.

E038 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0.06	0	I*	I	I		0.56	0.36	0.62	9.1	5.8	20	37
Max Daily Peak (ft³/s)	0.52	15	I	I	I	0.64	1.8	7.2	11	205	76	109	205
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	5	19	25	13	3	0	0	0	0	0	0	65

* I = Ice or snow present in channel.

E039.1 DP Canyon below Grade Control Structure

Location. Lat 35° 52' 40", long -106° 16' 17", SE ¼, Sec. 14, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.40 mi².

Period of Record. April 4, 2010, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 7016 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 90 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 400 ft³/s, September 13, 2013, gage height 4.0 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 150 ft³/s, July 26, 2017, gage height 2.4 ft.



E039.1 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, a shaft encoder float system, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. A trapezoidal supercritical flume with a 1-ft-wide throat controls flow through the gage reach. No provision has been made for direct discharge measurements above the wading stage. An outside staff gage is available for reference. The station is equipped with two ISCO pump samplers (one 12-count 1-L glass or polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples. The ISCOs are housed in a 3- x 4-ft steel storage box, separate from the other instrumentation. The samplers are triggered by stage through the data logger. All high-flow measurements will be by slope-area or peak-flow computation methods.

Datum Correction. None

Gage-Height Record. The data logger referenced to the outside gage gave a complete and satisfactory record for the year, except for February 21, 2017 because of ice in the channel, and September 28-30, 2017, because of equipment failure.

Rating. Rating No. 1 is based on precalibrated data for a trapezoidal supercritical flume with a 1-ft-wide throat (Kilpatrick and Schneider 1983) and was used throughout the period.

No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 1.

E039.1 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.45	0.64	0.14	0	0	0	0	0.21	0	0	0	0
2	0.45	0.64	0.14	0	0	0	0	0.18	0	0	0	0
3	0.32	0.64	0	0	0	0	0	0.14	0	0	0	0
4	0.25	2.8	0	0	0	0	0	0.14	0	0	0	0
5	0.28	40	0	0	0	0	0.18	0.14	0	0	0	0
6	0.28	11	0	0	0	0	0.18	0.14	0.11	0	0	0
7	0.32	0.45	0	0	0	0	0.14	0.14	4.5	0	18	0
8	0.35	0.21	0	0	0	0	0.14	0.14	0	61	0	0
9	0.35	0.21	0	0	0	0	0.14	5.4	0	0	0	0
10	0.32	0.21	0	0	0	0	0.14	0.64	0	0	0	0
11	0.35	0.21	0	0	0	0	0.14	0	0	0	5.7	0
12	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
13	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
14	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
15	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
16	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
17	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
18	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
19	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
20	0.45	0.18	0	0	0	0	0.14	0	0	0	0	0
21	0.45	4.9	0	0	I ^a	0	0.14	0	0	0	0.45	0
22	0.45	0.45	0	0	0	0	0.11	0	0	0	0	0
23	0.45	0.21	0	0	0	0	0.14	0	0	0	4.9	0
24	0.45	0.21	0	0	0	0	0.14	0	0	0	0	0
25	0.45	0.18	0	0	0	0	0.14	0	0	0	0	0
26	0.45	0.18	0	0	0	0	0.14	0	0	150	0	15
27	0.45	0.21	0	0	0	0	0.14	0	0	0.93	0	35
28	0.83	0.18	0	0	0	0	0.14	0	0	0.07	0	E ^b
29	0.54	0.18	0	0		0	1.1	0	0	45	0	E
30	0.64	0.14	0	0		0	1.6	0	0	0.04	0	E
31	0.64		0	0		0		0		0	0	

^a I = Ice or snow present in channel.^b E = Equipment failure.**E039.1 Monthly Summary Table**

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	24	24	0.36	0	0	0	6.6	3.1	0.26	7.4	2.0	10	78
Max Daily Peak (ft³/s)	0.83	40	0.14	0	0	0	1.6	5.4	4.5	150	18	35	150
Min Daily Peak (ft³/s)	0	0.14	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	1	0	0	0	0	0	0	3	4

E040 DP Canyon above Los Alamos Canyon

Location. Lat 35° 52' 24", long -106° 15' 34", SW ¼, Sec. 13, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.60 mi².

Period of Record. May 1999 to September 30, 2017.

Revised Record. Drainage area (2006); Section (2007).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6621 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 30 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 550 ft³/s, September 13, 2013, gage height 6.12 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 101 ft³/s, July 26, 2017, gage height 3.78 ft.



E040 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Milltronics sonic probe. The system is powered by a solar-panel battery system. All equipment is housed in a NEMA shelter. The station is equipped with an ISCO pump sampler (12-count 1-L glass or polyethylene bottles) to collect water-quality samples. The sampler is housed in a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. High-flow measurements can be made from the bridge upstream of the gage.

Datum Correction. None from levels.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year, except January 5-9, 15, and 20-23, 2017, February 12-13, 2017, and April 29, 2017 because of ice and snow in the channel.

Rating. The channel is about 15 ft wide and bends to the right above the gage and straight for about 100 ft downstream. The streambed through this reach is primarily sand with large boulders. The control at this site is concrete with a v-notch in the middle for low flow. The channel becomes the control for medium to high flows. No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 3.

E040 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0.01	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0.12	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0.01	0	0
5	0	10	0	I*	0	0	0	0	0.01	0	0	0
6	0	6.1	0	I	0	0	0	0	0.01	0.01	0	0
7	0	0	0	I	0	0.03	0	0	0	0.01	5.9	0
8	0	0.01	0	I	0	0.03	0	0.01	0	27	0	0
9	0	0.01	0	I	0	0.03	0	0	0.01	0.14	0	0
10	0	0.02	0	0	0	0.04	0	0.02	0	0.18	0	0
11	0	0	0	0.02	0	0.04	0	0	0	0	5.4	0
12	0	0.02	0	0	I	0.01	0	0	0.01	0	0.26	0
13	0	0.04	0	0	I	0.02	0	0.01	0	0	0.26	0
14	0	0.04	0	0	0	0.02	0	0.09	0	0	0.28	0
15	0	0.04	0	I	0	0.04	0	0	0.01	0	0	0
16	0	0.03	0.01	0	0	0.04	0	0	0.01	0	0	0
17	0	0.05	0	0.04	0	0.15	0	0	0.01	0	0	0
18	0	0.03	0	0	0	0	0	0.02	0.01	0	0	0
19	0	0.03	0	0	0	0.01	0	0	0.01	0	0	0
20	0	0.02	0	I	0	0	0.02	0	0.01	0	0	0
21	0	0.04	0	I	0	0	0.01	0	0.01	0	0	0
22	0	0	0.37	I	0	0.01	0	0	0.01	0	0	0
23	0	0	0.02	I	0	0.01	0	0	0.01	0	0	0
24	0	0	0	0	0	0	0.01	0	0	0	0	0
25	0	0	0.14	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	101	0	2.6
27	0	0	0	0	0	0	0	0	0	1.0	0	51
28	0	0	0.01	0	0	0	0.01	0	0.01	0.42	0	50
29	0	0	0.04	0.01		0	I	0	0.02	39	0	50
30	0	0	0.23	0		0	0	0	0.02	1.7	0	0.06
31	0		0.08	0		0		0		1.7	0	

* I = Ice or snow present in channel.

E040 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	1.33	0.02	0	0	0.01	0	0	0	13	2.3	15	32
Max Daily Peak (ft³/s)	0	10	0.37	0	0	0.15	0	0.09	0.12	101	5.9	51	101
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	10	2	0	1	0	0	0	0	0	13

E042.1 Los Alamos above Low Head Weir

Location. Lat 35° 52' 2", long -106° 13' 25", NW ¼, Sec. 20, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 10.13 mi².

Period of Record. May 4, 2010, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6377 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 229 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 740 ft³/s, September 13, 2013, gage height 5.59 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 51 ft³/s, September 29, 2017, gage height 1.36 ft.



E042.1 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, a shaft encoder float system, and a Sutron Accubar air-purge bubble sensor housed in a NEMA shelter. On November 2, 2016, a VegaPuls WL 61 radar sensor was added to the sensor array. The shelter is secured atop a stilling well, a vertical 2-ft-diameter CMP. An outside staff gage is available for reference. A trapezoidal supercritical flume with a 1-ft-wide throat controls flow through the gage reach. No provision has been made for direct discharge measurements above the wading stage.

Two ISCO pump samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples are triggered by stage through the data logger. The station is powered by a solar-panel battery system. The samplers and batteries are in a 3- x 4-ft steel storage box, separate from the other instrumentation. A tipping bucket rain gage with 0.01-in. resolution is mounted about 30 ft from the station.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. Rating No. 1 is based on precalibrated data for the flume used (Kilpatrick and Schneider 1983) and was used throughout the period.

No discharge measurements were made during the year.

Discharge. Discharge was computed directly by Rating No. 1 for the entire water year. Days estimated were based on precipitation and nearby gage stations for verification. Flow is partially regulated by the Los Alamos Reservoir, located about 7.8 mi upstream.

E042.1 Daily Mean Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	2.5	0	0	0	0	0
2	0	0	0	0	0	0	2.5	0	0	0	0	0
3	0	0	0	0	0	0	1.9	0	0	0	0	0
4	0	0	0	0	0	0	2.3	0	0	0	0	0
5	0	0	0	0	0	0	2.5	0	0	0	0	0
6	0	12	0	0	0	0	2.0	0	0	0	0	0
7	0	0	0	0	0	0	1.7	0	0	0	0	0
8	0	0	0	0	0	0	1.6	0	0	0	0	0
9	0	0	0	0	0	0	1.9	0	0	0	0	0
10	0	0	0	0	0	0	2.3	0	0	0	0	0
11	0	0	0	0	0	0	2.5	0	0	0	0	0
12	0	0	0	0	0	0	2.3	0	0	0	0	0
13	0	0	0	0	0	0	2.2	0	0	0	0	0
14	0	0	0	0	0	0	2.3	0	0	0	0	0
15	0	0	0	0	0	0	2.5	0	0	0	0	0
16	0	0	0	0	0	0	2.5	0	0	0	0	0
17	0	0	0	0	0	0	2.2	0	0	0	0	0
18	0	0	0	0	0	0	2.2	0	0	0	0	0
19	0	0	0	0	0	0	1.7	0	0	0	0	0
20	0	0	0	0	0	0	1.4	0	0	0	0	0
21	0	0	0	0	0	0	1.1	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	1.6	0	0	0	0	0	0
24	0	0	0	0	0	1.7	0	0	0	0	0	0
25	0	0	0	0	0	1.6	0	0	0	0	0	0
26	0	0	0	0	0	1.4	0	0	0	30	0	0
27	0	0	0	0	0	1.3	0	0	0	0.07	0	25
28	0	0	0	0	0	1.8	0	0	0	0	0	11
29	0	0	0	0		2.3	2.8	0	0	5.9	0	51
30	0	0	0	0		1.9	0.14	0	0	1.1	0	0
31	0		0	0		2.3		0		0	0	

E042.1 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0.82	0	0	0	22	61	0	0	3.5	0	18	105
Max Daily Peak (ft³/s)	0	12	0	0	0	2.3	2.8	0	0	30	0	51	51
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E050.1 Los Alamos Canyon below Low Head Weir

Location. Lat 35° 52' 2", long -106° 13' 3", NE ¼, sec. 20, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 10.44 mi².

Period of Record. July 22, 2010, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6340 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 117 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 740 ft³/s, September 13, 2013, gage height 5.81 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 56 ft³/s, September 29, 2017, gage height 1.44 ft.



E050.1 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, a shaft encoder float system, a Milltronics sonic probe mounted to an arm above the channel, and a Sutron Accubar air-purge bubble sensor, housed in a NEMA shelter. The shelter is secured atop a stilling well, a vertical 2-ft-diameter CMP. An outside staff gage is available for reference. A trapezoidal supercritical flume with a 1-ft-wide throat controls flow through the gage reach. No provision has been made for direct discharge measurements above the wading stage.

The station is equipped with two ISCO pump samplers (one 12-count 1-L glass or polyethylene bottle sampler and one 24-count polyethylene bottle sampler) to collect water-quality samples. The ISCOs samplers are housed in a separate shelter, a 3- x 4-ft metal box. The samplers are triggered by stage through the data logger. A line-of-sight radio transceiver provides 5-min stage data from the bubble sensor, sonic probe, and encoder.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the entire year.

Rating. Rating No. 1 is based on precalibrated data for the flume used (Kilpatrick and Schneider 1983) and was used throughout the period.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying Rating No. 1 for the entire water year.

E050.1 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0.76	0	0	0	0	0
2	0	0	0	0	0	0	0.66	0	0	0	0	0
3	0	0	0	0	0	0	0.28	0	0	0	0	0
4	0	0	0	0	0	0	0.50	0	0	0	0	0
5	0	0	0	0	0	0	0.35	0	0	0	0	0
6	0	0	0	0	0	0	0.25	0	0	0	0	0
7	0	0	0	0	0	0	0.22	0	0	0	0	0
8	0	0	0	0	0	0	0.22	0	0	0	0	0
9	0	0	0	0	0	0	0.32	0	0	0	0	0
10	0	0	0	0	0	0	0.42	0	0	0	0	0
11	0	0	0	0	0	0	0.50	0	0	0	0	0
12	0	0	0	0	0	0	0.35	0	0	0	0	0
13	0	0	0	0	0	0	0.35	0	0	0	0	0
14	0	0	0	0	0	0	0.50	0	0	0	0	0
15	0	0	0	0	0	0	0.50	0	0	0	0	0
16	0	0	0	0	0	0	0.50	0	0	0	0	0
17	0	0	0	0	0	0	0.35	0	0	0	0	0
18	0	0	0	0	0	0	0.32	0	0	0	0	0
19	0	0	0	0	0	0	0.18	0	0	0	0	0
20	0	0	0	0	0	0	0.11	0	0	0	0	0
21	0	0	0	0	0	0	0.07	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0.15	0	0	0	0	0	0
27	0	0	0	0	0	0.15	0	0	0	0	0	32
28	0	0	0	0	0	0.50	0	0	0	0	0	26
29	0	0	0	0		0.96	0	0	0	0	0	56
30	0	0	0	0		0.50	0	0	0	0	0	0.42
31	0		0	0		0.50		0		0	0	

E050.1 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	3.4	10	0	0	0	0	28	41
Max Daily Peak (ft³/s)	0	0	0	0	0	0.96	0.76	0	0	0	0	56	56
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E055 Pueblo Canyon above Acid Canyon

Location. Lat 35° 53' 20", long -106° 18' 14", SE ¼, Sec. 9, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 3.42 mi².

Period of Record. October 1, 2002, to September 30, 2017.

Revised Record. Average discharge (2007, 2008).

Gage. Data logger with radio telemetry. Elevation of gage is 6943 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 64 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 1200 ft³/s, September 13, 2013, gage height 6.86 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 33 ft³/s, September 27, 2017, gage height 1.13 ft.



E055 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler (12-count 1-L glass or polyethylene bottles) to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the entire year except January 5-10, 2017, because of ice and snow in the channel.

Rating. The channel comes into the gage from a left-to-right bend and bends hard left at about 100 ft below the gage. The bed consists of unstable sand and gravel with some boulders. The left bank downstream from the gage is heavily wooded, tending to hold the flow to the right, away from the reach of the gage. The lower end of any stage-discharge relation will be unstable here. Rating No. 2 was developed using one critical-depth measurement of 850 ft³/s and various low-flow measurements from previous years. The low-water definition is poor, and the high end needs to be confirmed. The low end of the rating was verified by a dye study and was used to enhance the rating. Rating No. 2 is good. Rating No.3 was developed using Rating No. 2 and by extending the upper range.

No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 3.

E055 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0.58	3.5	0	0	0	0.08	0
2	0	0	0	0	0	0	2.6	0	0	0	0	0
3	0	0	0	0	0	0	0.42	0	0	0	0	0
4	0	0	0	0	0	0	2.8	0	0	0	0	0
5	0	8.3	0	I*	0	0	1.4	0	0	0	0	0
6	0	5.5	0	I	0	0	0.08	0	0	0	0	0
7	0	0	0	I	0	0	0	0	0	0	0	0
8	0	0	0	I	0	0	0	0	0	0	0.25	0
9	0	0	0	I	0	0	0	0	0	0	0	0
10	0	0	0	I	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	1	0	0	7.3	0
12	0	0	0	0	0	0	0	0	0	0	2.2	0
13	0	0	0	0	0	0	0	0	0	0	0.50	0
14	0	0	0	0	0	0	0	0	0	0	0.42	0
15	0	0	0	0	0	0	0	0	0	0	0.58	0
16	0	0	0	0	0	0	0	0	0	0	0.17	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	2.2	0	0	0.33	0
22	0	0	0	0	0	0	0	0.17	0	0	0.08	0
23	0	0	0	0	0	0	0	0	0	0	16	0
24	0	0	0	0	0	0	0	0	0	0	1.0	0
25	0	0	2.2	0	0	0	0	0	0	0	1.8	0
26	0	0	0	0	0	0	0	0	0	0.75	0.17	0
27	0	0	0	0	0	0	0	0	0	0	0	33
28	0	0	0	0	0.92	0	0	0	0	0	0	19
29	0	0	0	0		0	0	0	0	16	0	22
30	0	0	0	0		0	0	0	0	3.7	0	15
31	0		0	0		0		0		0.42	0	

* I = Ice or snow present in channel.

E055 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	1.3	0.27	0	0.44	0.32	4.7	1.1	0	4.7	12	37	62
Max Daily Peak (acre-ft)	0	8.3	2.2	0	0.92	0.58	3.5	2.2	0	16	16	33	33
Min Daily Peak (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	6	0	0	0	0	0	0	0	0	6

E055.5 South Fork of Acid Canyon

Location. Lat 35° 53' 10", long -106° 18' 26", SE ¼, Sec. 9, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.08 mi².

Period of Record. August 18, 2004, to September 30, 2017.

Revised Record. Period of record (2009).

Gage. Data logger with radio telemetry. Elevation of gage is 7101 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 14 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge 90 ft³/s, September 13, 2013, gage height 6.2 ft.

Maximum Discharge for Current Water Year. No calculated maximum discharge. September 29, 2017, gage height maximum 6.16 ft.



E055.5 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and an OTT RLS radar sensor, which replaced the Sutron Accubar bubble sensor on May 12, 2017, housed in a NEMA shelter on the left bank. The system is powered by a solar-panel battery system. The station is equipped with an ISCO pump sampler (12-count 1-L glass or polyethylene bottles) to collect water-quality samples. The samples are triggered by stage through the data logger. The samplers are housed in a separate shelter, a 3- x 4-ft metal box. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

The station is also equipped with a tipping bucket rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. None. The levels from November 8, 2005, found the gage to be within limits. No corrections were needed.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record, except for December 16, 2016, to May 12, 2017, because of ice and snow in the channel and May 13 to May 17, 2017, when maintenance was performed.

Rating. The channel is straight for about 75 ft upstream and 100 ft downstream. The channel is trapezoidal with little vegetation. The bed is rock with gravel and should not be subject to very much movement.

Rating No. 1 was developed by one discharge measurement of low flow and one slope-area measurement of peak flow. The rating curve was extended to 6.22, based on a critical-depth computation.

No discharge measurements were made during the year.

Discharge. Discharge was computed by applying Rating No. 1.

E055.5 Daily Peak Stage (ft)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	3.35	3.35	3.06	I ^a	I	I	I	I	4.35	3.87	0	4.57
2	3.35	3.35	3.36	I	I	I	I	I	3.87	3.87	4.39	4.18
3	3.35	3.35	3.34	I	I	I	I	I	3.74	3.87	4.47	4.08
4	3.35	4.09	3.34	I	I	I	I	I	3.69	3.86	4.47	4.06
5	3.35	4.2	3.35	I	I	I	I	I	3.68	3.87	4.45	4.05
6	3.35	3.76	3.34	I	I	I	I	I	3.94	3.86	4.46	4.06
7	3.35	3.61	3.34	I	I	I	I	I	4.05	3.85	5.4	4.06
8	3.35	3.52	3.34	I	I	I	I	I	3.9	5.4	4.8	4.08
9	3.35	3.31	3.34	I	I	I	I	I	3.8	4.52	5.5	4.08
10	3.46	3.12	3.34	I	I	I	I	I	3.83	4.5	3.99	4.08
11	3.38	3.35	3.35	I	I	I	I	I	3.94	4.18	4.98	4.08
12	3.35	3.35	3.35	I	I	I	I	I	3.91	4.15	4.45	4.64
13	3.35	3.35	3.35	I	I	I	I	T ^b	3.79	4.22	4.2	4.04
14	3.35	3.35	3.35	I	I	I	I	T	3.7	4.22	4.09	4.06
15	3.35	3.35	3.35	I	I	I	I	T	3.75	4.22	4.1	4.12
16	3.35	3.35	I	I	I	I	I	T	3.78	4.21	4.09	4.05
17	3.35	3.35	I	I	I	I	I	3.73	3.84	4.21	4.09	4.08
18	3.35	3.35	I	I	I	I	I	3.73	3.83	4.49	4.1	4.2
19	3.35	3.35	I	I	I	I	I	3.93	3.85	4.25	4.7	4.21
20	3.35	3.35	I	I	I	I	I	3.89	3.73	4.25	4.91	4.21
21	3.35	3.91	I	I	I	I	I	3.75	3.63	4.18	4.51	4.21
22	3.35	3.51	I	I	I	I	I	3.69	3.71	4.19	4.21	4.2
23	3.35	3.53	I	I	I	I	I	3.69	3.6	4.19	5.16	4.19
24	3.35	3.42	I	I	I	I	I	3.69	3.58	4.19	4.78	4.2
25	3.35	3.24	I	I	I	I	I	3.68	4.27	4.18	4.15	4.2
26	3.35	3.07	I	I	I	I	I	3.69	4.56	6.16	4.16	5.04
27	3.35	3.5	I	I	I	I	I	3.68	3.85	4.74	4.2	5.18
28	3.35	3.43	I	I	I	I	I	3.69	3.83	4.71	4.19	5.96
29	3.35	3.35	I	I		I	I	3.69	3.83	5.35	4.6	5
30	3.35	3.22	I	I		I	I	3.7	3.87	4.65	4.24	5.04
31	3.35		I	I		I		3.69		4.66	4.23	

^a I = Ice or snow present in channel.^b T = Testing or maintenance performed.

E055.5 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	na ^a	na	I ^b	I	I	I	I	na	na	na	na	na	na
Max Daily Stage (ft)	3.46	4.6	I	I	I	I	I	3.93	4.56	6.16	5.5	6.0	6.16
Min Daily Stage (ft)	0	0	0	I	I	I	I	3.66	0	0	0	0	0
Missing Days	0	0	15	31	28	31	30	16	0	0	0	0	151

^a na = Not available.^b I = Ice or snow present in channel.

E056 Acid Canyon above Pueblo Canyon

Location. Lat 35° 53' 19", long -106° 18' 14" SE ¼, Sec. 9, T, 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.452 mi².

Period of Record. October 1, 2006, to September 30, 2017.

Revised Record. Period of record (2008).

Average Volume. 6 yr, 55 acre-ft/yr.

Gage. Data logger with radio telemetry. Elevation of gage is 6944 ft using LANL LIDAR DEM with NAD 83.

Maximum Discharge for Period of Record. Maximum discharge, 470 ft³/s, September 13, 2013, gage height 8.6 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 24 ft³/s, July 26, 2017, gage height 2.85 ft.



E056 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor mounted on a 6-in. channel cantilevered over the streambed. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler (12-count 1-L glass or polyethylene bottles) to collect water-quality samples. An ISCO sampler is housed in a separate shelter, a 3- × 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provisions have been made for measurements above the wading stage.

Datum Correction. None. The levels are from June 6, 2006. The gage is within acceptable limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the entire year, except for January 17–18, 2017, when the gage was affected by ice.

Rating. The channel is about 20 ft wide and straight for about 15 ft upstream and straight for about 40 ft downstream and 20 ft above the confluence of Pueblo Canyon. The streambed through this reach is primarily sand and cobbles. The low-water control is a 90-degree sharp-crested weir. At high flow, the channel becomes the control.

Rating No. 3 is based on four discharge measurements and six indirect measurements made by a concurrent dye study at the site. Shifts were applied to low flow using “V” diagrams. Rating No. 4 is based on Rating No. 3 with an extension of the upper range.

No discharge measurements were taken during the year.

Discharge. Discharge was computed by applying the gage height to Rating No. 4.

E056 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.08
2	0	0	0.04	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.08
3	0	0	0.10	0.10	0.06	0.08	0.06	0.06	0.06	0.07	0.08	0.08
4	0	0	0.04	0.04	0.06	0.08	0.06	0.06	0.06	0.08	0.06	0.08
5	0	17	0.04	0.45	0.06	0.08	0.06	0.06	0.06	0.08	0.08	0.08
6	0	8.0	0.04	0.08	0.06	0.08	0.06	0.06	0.06	0.06	0.08	0.08
7	0	0.06	0.04	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.67	0.08
8	0	0.06	0.04	0.04	0.06	0.06	0.06	0.06	0.08	2.6	0.08	0.08
9	0	0.10	0.04	0.04	0.06	0.06	0.06	0.06	0.08	0.06	0.08	0.08
10	0	0.08	0.04	0.04	0.06	0.06	0.06	0.06	0.08	0.08	0.08	0.06
11	0	0.08	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.55	0.06
12	0	0.06	0.04	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.08
13	0	0.06	0.04	0.04	0.08	0.06	0.06	0.06	0.06	0.06	0.08	0.08
14	0	0.06	0.04	0.12	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
15	0	0.06	0.04	0.12	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
16	0	0.06	0.06	0.12	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
17	0	0.06	0.06	I*	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
18	0	0.04	0.04	I	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
19	0	0.04	0.04	0.12	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
20	0	0.04	0.04	0.10	0.08	0.06	0.06	0.06	0.06	0.06	0.08	0.06
21	0	0.04	0.04	0.10	0.08	0.06	0.06	0.06	0.06	0.06	0.08	0.06
22	0	0.04	0.04	0.08	0.08	0.06	0.06	0.06	0.06	0.06	0.08	0.06
23	0	0.04	0.04	0.04	0.08	0.06	0.06	0.06	0.06	0.06	4.7	0.06
24	0	0.04	0.06	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.06
25	0	0.04	7.3	0.04	0.08	0.06	0.06	0.06	0.06	0.06	0.08	0.06
26	0	0.04	0.04	0.04	0.06	0.06	0.06	0.06	0.49	24	0.08	2.3
27	0	0.04	0.06	0.04	0.06	0.06	0.06	0.06	0.06	0.16	0.08	4.7
28	0	0.04	0.06	0.04	0.06	0.06	0.06	0.06	0.06	0.06	0.08	12
29	0	0.04	0.06	0.06		0.06	0.04	0.06	0.06	4.4	0.08	3.6
30	0	0.06	0.06	0.06		0.06	0.06	0.06	0.06	0.08	0.08	3.5
31	0		0.06	0.06		0.06		0.06		0.08	0.08	

*I = Ice or snow present in channel.

E056 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	6.1	2.8	0	3.4	3.8	3.3	3.8	3.7	4.9	4.8	7.4	44
Max Daily Peak (acre-ft)	0	17	7.3	0.12	0.08	0.08	0.06	0.06	0.49	24	4.7	12	24
Min Daily Peak (acre-ft)	0	0	0.04	0	0.04	0.04	0.04	0.04	0.06	0.06	0.06	0.06	0
Missing Days	0	0	0	2	0	0	0	0	0	0	0	0	2

E059.5 Pueblo Canyon below Los Alamos County WWTF

Location. Lat 35° 52' 52.72" N, long -106° 14' 22.89" W, Zone 13S, NM23, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 3.26 mi².

Period of Record. May 10, 2014, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6483 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 3 yr, 238 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 97 ft³/s, July 31, 2014, gage height 6.23 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 61 ft³/s, September 29, 2017, gage height 1.52 ft.



E059.5 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. Two ISCO pump samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples are triggered by stage through the data logger. The station is powered by a solar-panel battery system. The samplers and batteries are in a 3- x 4-ft steel storage box, separate from the other instrumentation. No flow-control structure exists in the channel. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. Open channel.

Rating No. 1 was developed from a step-backwater survey conducted in September 2010. The control is the channel at all flows. The channel bed is highly mobile sand, and stage shifts will be required to account for frequent reshaping of the channel by discharge.

No discharge measurements were made during the year.

Discharge. Discharge was computed using Rating No. 1.

E059.5 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	1.1	0.07	0.13	0.17	0.43	1.1	2.0	0.27	0	0	0.40	0.17
2	1.4	0	0.13	0.17	0.43	1.1	2.2	0.27	0.27	0.03	0.40	0.10
3	1.1	0.03	0.13	0.13	0.43	1.0	2.2	0.17	0.23	0	0.40	0.10
4	1.7	0	0.13	0.17	0.47	1.4	1.7	0.10	0.40	0	0.40	0.17
5	1.1	0.40	0.20	0.17	3.1	1.4	1.7	0	0.33	0	0.47	0.10
6	0.72	0.40	0.17	0.20	0.72	1.7	1.4	0	0.37	0	0.40	0.07
7	0.72	0.17	0.13	0.20	0.47	1.4	0.43	0.07	0.33	0	0.47	0.03
8	0.72	0.17	0.10	0.27	0.60	1.7	0.40	0.03	0.37	0	0.33	0
9	1.4	0.13	0.10	0.23	0.47	2.0	0.43	0.13	0.30	4.1	0.33	0
10	2.0	0.13	0.13	0.37	0.60	1.4	0.60	0.10	0.27	0	0.27	0
11	0.85	0.13	0.13	0.33	0.72	1.1	0.33	0.20	0.33	0	0.40	0
12	0.50	0.13	0.17	0.30	1.0	1.4	0.33	0.33	0.27	0	0.43	0
13	0.47	0.13	0.17	0.27	2.0	1.4	0.27	0.13	0.03	0	0.43	0.03
14	0.13	0.17	0.13	0.27	2.0	0.43	0.17	0.10	0	0.20	0.43	0
15	0.07	0.07	0.13	0.47	2.0	1.7	0.17	0.10	0	0.37	0.43	0.03
16	0.07	0.07	0.17	0.37	2.2	1.1	0.27	0.37	0	0.20	0.47	0.03
17	0	0.10	0.20	0.37	1.4	0.47	0.20	0.40	0	0.13	0.33	0
18	0	0.10	0.17	0.37	1.4	0.43	0.17	0.40	0	0	0.13	0
19	0	0.13	0.30	0.37	1.4	1.4	0.10	0.30	0	0.10	0.20	0.03
20	0	0.13	0.33	0.37	1.7	0.60	0.10	0.50	0	0.23	0.47	0
21	0	0.17	0.17	0.37	1.4	0.85	0.07	0.60	0	0	0.37	0
22	0	0.13	0.13	0.40	1.1	0.50	0.07	0.40	0	0.10	0.40	0
23	0.07	0.13	0.10	0.40	1.4	0.50	0.20	0.20	0	0.27	0.40	0
24	0.07	0.13	0.17	0.40	1.4	0.60	0.13	0.10	0	0	0.40	0.03
25	0.13	0.10	0.13	0.40	1.4	1.0	0.13	0.20	0.03	0.30	6.9	0.27
26	0.07	0.10	0.17	0.40	1.7	0.40	0.07	0.13	0	0.03	0.37	0.33
27	0.13	0.13	0.13	0.30	3.6	0.60	0.10	0	0	0.30	0.37	12
28	0.13	0.10	0.13	0.43	3.1	0.60	0.07	0	0.03	0.37	0.33	21
29	0.10	0.13	0.13	0.40		1.0	0.27	0	0	0.43	0.27	61
30	0.13	0.13	0.13	0.40		0.72	0.17	0	0	0.43	0.17	0.17
31	0.10		0.17	0.37		1.4		0		0.43	0.20	

E059.5 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	12	1.7	3.2	8.5	23	17	8.4	2.3	1.6	3.1	10	11	102
Max Daily Peak (ft³/s)	2.0	0.40	0.33	0.47	3.6	2.00	2.2	0.60	0.40	4.1	6.9	61	61
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E059.8 Pueblo Canyon below Wetlands

Location. Lat 35° 52' 38.489" N, long -106° 13' 35.418" W, Zone 13N, NM17, T. 19 N., R. 7 E., Santa Fe County

Drainage Area. 7.75 mi².

Period of Record. October 9, 2015, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6410 ft using LANL LIDAR DEM with NAD 83.

Average Volume. <2 yr, 65 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 10 ft³/s, October 21, 2015, gage height 1.51 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 1.9 ft³/s, September 29, 2017, gage height 1.17 ft.



E059.8 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. Two ISCO pump samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples are triggered by stage through the data logger. The station is powered by a solar-panel battery system. The samplers and batteries are in a 3- x 4-ft steel storage box, separate from the other instrumentation. A v-notch weir is the control. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. 90-degree v-notch weir with a board-crested weir above the notch.

Rating No. 1 was developed from a 90-degree weir plate formula and broad-crested weir computation above the notch.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying using Rating No. 1 for the entire year.

E059.8 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.08	0	0.29	0.08	0.10	0.09	0.11	0.00	0	0	0	0
2	0.12	0	0.29	0.09	0.09	0.11	0.14	0.03	0	0	0	0
3	0.15	0	0.36	0.06	0.09	0.11	0.12	0.02	0	0	0	0
4	0.12	0	0.36	0.07	0.11	0.12	0.09	0.04	0	0	0	0
5	0.17	0.15	0.39	0.10	0.29	0.15	0.31	0	0	0	0	0
6	0.10	0.29	0.34	0.11	0.10	0.15	0.34	0	0	0	0	0
7	0.00	0.20	0.31	0.11	0.09	0.10	0.31	0	0	0	0	0
8	0.00	0.17	0.29	0.12	0.09	0.10	0.05	0	0	0	0	0
9	0.11	0.18	0.27	0.14	0.07	0.10	0.10	0.01	0	0	0	0
10	0.14	0.20	0.36	0.23	0.09	0.09	0.11	0	0	0	0	0
11	0.15	0.21	0.36	0.18	0.11	0.05	0.06	0	0	0	0	0
12	0.01	0.20	0.44	0.14	0.12	0.12	0	0.01	0	0	0	0
13	0	0.21	0.36	0.10	0.17	0.14	0	0.05	0	0	0	0
14	0.09	0.21	0.36	0.10	0.12	0	0	0.05	0	0	0	0
15	0.09	0.20	0.31	0.27	0.11	0	0	0.05	0	0	0	0
16	0.05	0.08	0.41	0.21	0.12	0	0	0.01	0	0	0	0
17	0.01	0.10	0.41	0.21	0.11	0	0	0	0	0	0	0
18	0	0.17	0.39	0.12	0.10	0	0	0	0	0	0	0
19	0	0.21	0.74	0.11	0.07	0	0	0	0	0	0	0
20	0	0.23	0.74	0.11	0.08	0	0.01	0	0	0	0	0
21	0	0.39	0.39	0.14	0.09	0	0.01	0	0	0	0	0
22	0	0.41	0.34	0.14	0.08	0	0	0.03	0	0	0	0
23	0	0.23	0.36	0.15	0.09	0	0	0	0	0	0	0
24	0	0.25	0.47	0.15	0.06	0	0	0	0	0	0	0
25	0	0.15	0.39	0.09	0.10	0	0	0	0	0	0	0
26	0	0.20	0.36	0.09	0.10	0	0	0	0	0	0	0
27	0	0.34	0.34	0.08	0.25	0	0	0	0	0	0	0
28	0	0.34	0.34	0.12	0.25	0	0.01	0	0	0	0	0
29	0	0.31	0.31	0.14	0.10	0.03	0.01	0	0	0	0	1.9
30	0	0.27	0.36	0.12		0.03	0	0	0	0	0	0.02
31	0.05		0.39	0.10		0.01		0		0	0	

E059.8 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0.88	6	12	3	2	1.0	1.1	0.2	0	0	0.0	0.5	27
Max Daily Peak (ft³/s)	0.16	0.41	0.74	0.27	0.29	0.15	0.34	0.05	0	0	0.0	1.9	1.9
Min Daily Peak (ft³/s)	0	0.	0.03	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E060.1 Pueblo Canyon below Grade Control Structure

Location. Lat 35° 52' 17", long -106° 12' 53", NE ¼, Sec. 20, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 8.30 mi².

Period of Record. April 15, 2010, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6329 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 38 acre-ft/yr.

Maximum Discharge for Current Water Year. Maximum discharge, 1400 ft³/s, September 13, 2013, gage height 6.23 ft.

Maximum Discharge for Period of Record. Maximum discharge, 0.58 ft³/s, November 4, 2017, gage height 0.30 ft.



E060.1 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, a shaft encoder float system, a Milltronics sonic probe mounted on an arm above the channel, and a Sutron Accubar air-purge bubble sensor, housed in a NEMA shelter. The shelter is secured atop a stilling well, a vertical 2.5-ft-diameter corrugated metal culvert pipe. An outside staff gage is available for reference. A trapezoidal supercritical flume with a 1-ft-wide throat controls flow through the gage reach. No provision has been made for direct discharge measurements above the wading stage.

Two ISCO pump samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples are triggered by stage through the data logger. The station is powered by a solar-panel battery system. The samplers and batteries are in a 3- x 4-ft steel storage box, separate from the other instrumentation. A line-of-sight radio transceiver provides 5-min stage data from the encoder and bubbler.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. Rating No. 1 is based on precalibrated data for the flume used (Kilpatrick and Schneider 1983) and was used throughout the period.

No discharge measurements were taken during the year.

Discharge. Discharge was computed by directly applying Rating No. 1 for the entire water year.

E060.1 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0.04	0	0.18	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0.58	0	0	0	0	0	0	0	0	0	0
5	0	0.58	0	0	0	0	0	0	0	0	0	0
6	0	0.08	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0.15	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0.18	0	0	0	0	0	0	0.18	0	0.18	0.18	0
10	0.01	0	0	0	0	0	0	0.04	0	0	0	0
11	0.01	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0.08
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0.11	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0.25	0	0
27	0	0	0	0	0	0	0	0	0	0.04	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0.04
29	0	0	0	0		0	0	0	0	0	0	0.08
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E060.1 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0.04	0.31	0	0	0	0	0	0	0	0.01	0.01	0	0.36
Max Daily Peak (ft³/s)	0.18	0.58	0	0	0	0	0.04	0.18	0.18	0.25	0.18	0.08	0.58
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

Sandia Watershed

The Sandia Canyon and Mortandad Canyon watersheds are located within the central part of LANL. The Sandia watershed heads on LANL property within Technical Area 03 (TA-03) at an elevation of approximately 7300 ft and trends east-southeast across LANL property, Bandelier National Monument, and Pueblo de San Ildefonso. Sandia Canyon empties into the Rio Grande in White Rock Canyon at an elevation of 5450 ft. The area of the Sandia watershed is approximately 5.5 mi². There are no significant tributaries to the Sandia watershed. Perennial stream flow occurs in the upper and middle portions of the canyon system as a result of sanitary wastewater and cooling tower effluent discharge to the canyon from operating facilities. The only known perennial spring in the watershed (Sandia Spring) is located in lower Sandia Canyon near the Rio Grande. The Sandia watershed contains, or may influence, eight wetland areas totaling approximately 5.39 acres.

Figure 4 shows the total monthly volume of discharge for the five stream gage discharge stations within Sandia watershed. Station E123 is located downstream of the Sandia wetland. Gage stations E121 and E122 both discharge into the wetland. Station E121 is directly downstream from the power plant and receives a constant or nearly constant base flow from the power plant. Station E124 is located in lower Sandia Canyon, adjacent to East Jemez Road. Station E125 is located near the edge of LANL property at the intersection of East Jemez Road and NM 4. Both E124 and E125 rarely have flow. Variations within the discharge are the result of the precipitation events throughout the monsoon season or a change in the volume of effluent from the cooling tower.




Figure 4 The total monthly volume (acre-ft) for WY 2017 for Sandia Canyon

E121 Sandia Canyon Right Fork at Power Plant

Location. Lat 35° 52' 31", long -106° 19' 7", SW ¼, Sec. 16, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.08 mi².

Period of Record. October 1, 2006, to September 30, 2017.

Revised Record. Period of record (2008).

Gage. Data logger with radio telemetry. Elevation of gage is 7280 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 379 acre-ft/yr.

Maximum Discharge for Current Water Year. Maximum discharge, 191 ft³/s, June 21, 2002, from peak-flow computation, gage height 7.62 ft.

Maximum Discharge for Period of Record. Maximum discharge, 4.7 ft³/s, March 23, 2017, gage height 7.06 ft.



E121 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler (12-count 1-L glass and polyethylene bottles) to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is straight for about 30 ft with a steep upstream slope and straight for 50 ft downstream with a sharp slope. The streambed through this reach consists primarily of sand, gravel, and cobbles, more so below the gage. The low-water control is a bedrock riffle below the gage.

Rating No. 5 was developed based on previous measurements.

No discharge measurements were made during the year.

Discharge. Discharge was computed by applying Rating No. 5.

E121 Daily Mean Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.81	0.86	1.2	0.29	1.1	1.0	4.0	1.2	3.03	0.57	0.39	7.05
2	0.79	0.86	1.4	0.44	0.77	0.8	2.8	0.9	0.86	0.50	0.41	0.97
3	1.7	0.81	1.2	0.77	0.95	1.0	1.2	1.1	0.57	0.50	0.42	0.83
4	1.2	8.	1.2	0.90	0.77	0.7	2.2	0.9	0.57	0.64	0.40	0.76
5	0.48	16	1.2	2.46	0.72	0.8	1.7	1.1	1.11	0.50	0.43	0.58
6	0.81	1.34	1.2	0.86	0.90	1.1	1.0	1.0	25	0.37	0.38	0.62
7	1.1	0.95	1.1	1.05	0.80	0.9	1.2	1.0	0.86	0.34	2.37	0.50
8	1.5	0.90	1.1	0.95	0.90	1.2	1.0	1.0	0.77	5.37	3.08	0.51
9	1.2	1.1	0.64	1.67	0.6	1.0	0.9	15	1.05	0.35	1.05	0.47
10	0.77	0.90	0.61	0.81	0.9	1.1	1.1	2.0	0.95	0.81	1.09	0.57
11	0.86	0.90	0.61	1.05	0.6	1.0	0.9	0.9	0.90	0.27	6.50	0.51
12	1.1	0.86	0.61	0.77	0.6	0.9	1.1	1.1	0.90	2.46	1.02	0.85
13	0.90	0.86	0.77	1.00	1.0	1.1	0.9	1.0	0.43	0.35	1.11	0.50
14	0.90	0.90	0.77	2.33	0.8	1.0	1.2	1.0	0.50	0.32	1.32	0.98
15	1.2	0.86	0.77	3.98	0.9	1.1	0.6	1.0	0.50	0.29	0.99	0.41
16	0.81	0.86	1.96	0.98	0.6	0.9	0.5	0.7	0.50	0.35	1.03	0.61
17	0.81	0.90	2	1.25	0.9	1.1	0.86	0.9	0.39	0.34	0.97	0.61
18	0.77	0.90	0.86	1.03	0.9	0.6	0.9	0.5	0.35	36.47	1.59	0.65
19	0.80	0.86	0.81	0.83	0.57	0.6	1.1	2.3	0.41	0.72	1.36	0.63
20	0.77	0.72	1.11	1.05	0.57	0.9	0.7	0.7	0.37	0.68	1.49	0.61
21	0.72	3.92	0.90	1.00	1	0.6	1.1	0.7	0.34	0.57	8.59	0.54
22	0.72	0.90	1.05	0.81	1.0	1.0	0.8	0.9	0.44	0.53	1.55	0.50
23	1.0	0.64	1.5	0.95	0.68	1.7	0.8	0.7	0.29	0.30	12	1.8
24	0.903	0.64	3.0	0.77	1.0	1.3	1.1	0.7	0.29	0.43	0.72	0.55
25	0.856	0.90	2.7	0.90	0.68	1.1	1.8	0.6	21	0.41	1.33	0.48
26	0.81	0.90	1.16	0.64	0.68	1.1	1.2	0.8	33	87	1.67	14
27	0.81	1.961	1.00	0.90	1.05	1.3	1.0	0.5	0.64	6.8	1.28	18
28	0.39	1.054	0.90	0.90	1.34	1.2	2.0	0.5	0.81	0.37	1.00	49
29	0.8	1.05	1.00	0.90		2.0	1.8	1.7	0.68	29	0.93	13
30	1.2	1	0.81	1.11		0.9	2.2	0.7	0.64	0.39	0.90	14
31	0.90		0.68	0.86		1.2		0.8		1.69	0.82	

E121 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	42	50	49	43	34	49	49	44	33	25	47	50	514
Max Daily Peak (ft³/s)	1.7	16	3.0	4.0	1.3	2.0	4.0	15	33	87	12	49	87
Min Daily Peak (ft³/s)	0.94	0.37	0.81	0.81	0.64	0.68	0.44	0.61	0.50	0.27	0.41	0.37	0.27
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E122 Sandia Canyon near Roads and Grounds at TA-03

Location. Lat 35° 52' 31", long -106° 9' 6", SW ¼, Sec. 16, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.08 mi².

Period of Record. October 1, 2006, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 7288 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 61 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 18 ft³/s, September 13, 2013, gage height 3.03 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 9.1 ft³/s, July 26, 2017, gage height 2.13 ft.



E122 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a VegaPuls WL 61 radar sensor, which replaced the Milltronics sonic probe on November 29, 2016. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is also equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

Datum Correction. None. The levels of July 25, 2005, found the gage to be within limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record the entire year, except for November 29–30, 2016, and August 1, 2017, when equipment maintenance was performed.

Rating. The channel is straight for about 20 ft above the gage with a steep downstream slope and straight for 15 ft downstream with a sharp slope 5 ft downstream. The streambed through this reach is primarily bedrock with some cobbles below the gage. The low-water control is a bedrock riffle below the gage.

Rating No. 2 was developed based on past measurements.

One discharge measurement was made during the year.

Discharge. Discharge was computed from Rating No. 2.

E122 Daily Mean Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.14	0.14	0.09	0.10	0.11	0.09	0.78	0.09	0.83	0.11	T*	1.9
2	0.14	0.15	0.12	0.09	0.11	0.08	0.49	0.09	0.14	0.11	0.09	0.11
3	0.39	0.15	0.09	0.08	0.11	0.08	0.09	0.08	0.10	0.11	0.10	0.11
4	0.14	2.0	0.09	0.08	0.10	0.08	0.39	0.08	0.10	0.12	0.10	0.11
5	0.13	2.0	0.09	0.60	0.10	0.08	0.16	0.09	0.11	0.14	0.10	0.11
6	0.13	0.21	0.07	0.10	0.09	0.11	0.09	0.09	2.25	0.12	0.12	0.11
7	0.15	0.14	0.09	0.10	0.11	0.08	0.08	0.09	0.09	0.15	0.93	0.11
8	0.34	0.13	0.13	0.15	0.10	0.08	0.08	0.09	0.09	0.90	0.58	0.11
9	0.13	0.13	0.11	0.32	0.10	0.08	0.08	2.2	0.09	0.11	0.10	0.11
10	0.12	0.11	0.11	0.09	0.10	0.08	0.08	0.40	0.09	0.10	0.10	0.11
11	0.12	0.11	0.06	0.10	0.09	0.08	0.08	0.09	0.09	0.11	0.98	0.11
12	0.13	0.15	0.09	0.09	0.11	0.08	0.08	0.09	0.10	0.65	0.11	0.20
13	0.11	0.11	0.09	0.09	0.17	0.08	0.08	0.08	0.10	0.11	0.10	0.11
14	0.13	0.11	0.09	0.49	0.15	0.08	0.08	0.08	0.10	0.11	0.16	0.30
15	0.15	0.17	0.09	0.85	0.11	0.08	0.08	0.09	0.10	0.11	0.10	0.11
16	0.16	0.17	0.42	0.16	0.09	0.08	0.08	0.08	0.10	0.11	0.11	0.11
17	0.13	0.06	0.40	0.22	0.09	0.08	0.08	0.08	0.10	0.11	0.10	0.11
18	0.14	0.11	0.09	0.11	0.09	0.08	0.08	0.09	0.10	5.32	0.10	0.11
19	0.15	0.15	0.08	0.11	0.09	0.08	0.08	0.40	0.10	0.12	0.10	0.11
20	0.14	0.16	0.09	0.10	0.09	0.08	0.08	0.09	0.10	0.10	0.10	0.11
21	0.13	0.90	0.09	0.15	0.09	0.08	0.08	0.08	0.10	0.10	1.78	0.11
22	0.15	0.13	0.15	0.14	0.09	0.08	0.08	0.08	0.11	0.10	0.11	0.11
23	0.15	0.13	0.25	0.12	0.09	0.25	0.08	0.09	0.11	0.11	3.1	0.67
24	0.12	0.14	0.80	0.15	0.08	0.12	0.09	0.10	0.11	0.15	0.26	0.11
25	0.12	0.15	0.56	0.09	0.09	0.09	0.33	0.10	2.8	0.16	0.11	0.11
26	0.14	0.13	0.20	0.09	0.08	0.10	0.10	0.09	4.6	9.08	0.15	2.9
27	0.15	0.42	0.13	0.09	0.11	0.09	0.08	0.09	0.10	1.91	0.11	3.2
28	0.13	0.11	0.10	0.09	0.25	0.18	0.29	0.09	0.11	0.10	0.11	5.5
29	0.14	T	0.09	0.11		0.37	0.34	0.83	0.11	4.7	0.11	1.8
30	0.13	T	0.09	0.11		0.09	0.34	0.17	0.11	0.11	0.11	2.5
31	0.15		0.09	0.11		0.09		0.10		0.51	0.11	

*T = Testing or maintenance performed.

E122 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	4.4	5.2	4.5	5.5	4.7	4.9	5.1	5.4	5.9	6.7	6.0	8.8	67
Max Daily Peak (ft³/s)	0.39	2.0	0.80	0.85	0.25	0.37	0.78	2.2	4.6	9	3.1	5.5	9
Min Daily Peak (ft³/s)	0	0	0	0	0	0.01	0.01	0.01	0	0	0.01	0.01	0
Missing Days	0	2	0	0	0	0	0	0	0	0	1	0	3

E123 Sandia Canyon below Wetlands

Location. Lat 35° 52' 23", long -106° 18' 35", SE ¼, Sec. 16, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.29 mi².

Period of Record. August 1, 1999, to September 30, 2017.

Revised Record. Drainage area (2006); Section (2007).

Gage. Data logger with radio telemetry. Elevation of gage is 7201 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 578 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge 110 ft³/s, September 13, 2013, gage height 4.86 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 78 ft³/s, July 26, 2017, gage height 3.82 ft.



E123 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is also equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft steel storage box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

An auxiliary 6-in. Parshall flume, located downstream from E123, is used to verify the low-flow record.

Datum Correction. None; the levels run June 27, 2008, were found to be within limits.

Gage-Height Record. The data logger referenced to the inside gage height gave a complete and satisfactory record for the year, except for December 27, 2016, January 5, 7, 14-15, and 26, 2017, when the gage was affected by ice.

Rating. The channel is trapezoidal with a rock outcrop and small depositional bars within pools. The banks have some grass, not very tall or thick. The channel is straight for about 100 ft above and below the gage. Rating No.5 was developed based on low-flow measurements and point-of-zero flow measurements during the water year and a slope-area measurement high flow in 2005.

One discharge measurement was made during the year.

Discharge. Discharge was computed from Rating No. 5.

E123 Daily Mean Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.46	0.53	1.2	0.20	1.1	2	6.1	2.4	9.3	0.80	0.53	4.4
2	0.46	0.53	1.8	0.46	0.90	1	4.4	1.7	2.1	0.70	0.46	0.60
3	2.2	0.46	1.5	0.90	1.1	1	1.8	2.2	1.4	0.70	0.46	0.40
4	0.90	12	1.5	1.1	0.80	1	4.6	1.6	1.4	0.90	0.40	0.40
5	0.10	15	1.5	I*	0.80	1.1	2.7	2.0	2.2	0.80	0.40	0.32
6	0.40	12	1.4	1.7	0.90	1.5	1.6	1.9	16	0.53	0.40	0.32
7	0.53	0.70	1.4	I	1.0	1.3	2.1	1.9	2.1	0.53	4.0	0.32
8	1.8	0.60	1.2	2.1	1.4	1.7	1.6	1.9	1.8	7.1	3.5	0.32
9	1.0	0.80	0.53	3	1.1	1.3	1.5	13.1	2.4	0.53	1.2	0.32
10	0.46	0.70	0.53	1.2	1.4	1.6	1.9	5.0	2.4	0.53	1.0	0.32
11	0.53	0.70	0.60	1.3	1.1	1.2	1.5	1.8	2.4	3.1	9.0	0.32
12	0.70	0.70	0.70	0.90	1.0	1.2	1.9	2.2	2.4	3.1	0.90	0.60
13	0.53	0.70	1.0	1.3	1.9	1.6	1.6	2.1	0.90	1.0	0.70	0.46
14	0.53	0.80	1.0	I	1.6	1.5	2.2	2.1	0.80	0.60	0.80	0.90
15	0.70	0.80	1.0	I	1.5	1.7	1.4	2.0	1.0	0.60	0.46	0.40
16	0.53	0.80	3.6	1.6	1.0	1.7	1.2	1.3	1.0	0.80	0.53	0.40
17	0.53	0.60	3.2	2.8	1.3	1.8	1.6	1.6	0.80	0.80	0.53	0.60
18	0.53	0.70	1.3	1.4	1.3	1.0	1.5	0.9	0.70	14	0.90	0.70
19	0.53	0.70	1.4	1.1	1.0	1.0	2	5.8	0.70	2.30	0.90	0.70
20	0.46	0.6	1.9	1.3	1.0	1.4	1.5	1.6	0.70	0.90	0.80	0.70
21	0.46	6.3	1.0	1.5	1.1	1.0	1.9	1.4	0.70	0.80	10	0.60
22	0.46	1.2	1.7	1.1	1.6	1.6	1.5	1.9	0.60	0.80	0.80	0.60
23	0.40	0.40	2.8	1.2	1.1	2.8	1.6	1.8	0.60	0.46	12	3.49
24	0.70	0.46	1.5	1.1	1.5	1.9	2.1	1.7	0.53	0.53	1.00	0.90
25	0.70	0.70	5.5	1.3	1.1	1.7	3.4	1.3	30	0.60	0.90	0.70
26	0.46	0.70	2.2	I	1.1	1.6	2.4	1.7	35	78	0.40	19
27	0.46	2.8	I	2.2	1.6	1.9	1.9	1.3	0.90	8.37	0.60	27
28	0.09	1.0	1.4	2.6	2.8	1.5	4.9	1.3	0.70	1.69	0.32	54
29	0.4	1.0	1.1	2.3		4.0	5.1	6.0	0.60	29	0.32	53
30	0.6	0.60	1.1	1.9		1.4	5.1	1.9	0.80	1.60	0.40	9.0
31	0.53		1.0	1.1		1.7		2.1		3.10	0.40	

*I = Ice or snow present in channel.

E123 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	25	43	58	48	53	75	99	96	67	41	33	48	685
Max Daily Peak (ft³/s)	2.2	15	5.5	3.0	2.8	4.0	6.1	13	35	78	12	54	78
Min Daily (ft³/s)	0.20	0.32	0.80	0.80	0.90	0.53	0.20	0.14	0.05	0.01	0.26	0.07	0.01
Missing Days	0	0	1	5	0	0	0	0	0	0	0	0	6

E124 Sandia above Firing Range

Location. Lat 35° 51' 54.90" N, long -106° 15' 46.36" W, Zone 13S, NM23, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 1.14 mi².

Period of Record. October 1, 2013, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6736 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 4 yr, 7 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge 50 ft³/s, July 31, 2014, gage height 2.2 ft.

Maximum Discharge for Current Water Year. Maximum discharge 34 ft³/s, July 26, 2017, gage height 1.40 ft.



E124 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year, except for December 23-25, 2016, January 5-6, 9-10, and 15-16, 2017, because of snow and ice in the channel.

Rating. Rating No. 2 was developed based on slope-area computations and discharge measurements.

There were no discharge measurements made this year.

Discharge. Discharge was computed from Rating No. 2

E124 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	I*	0	0	0	0	0	0	0	0
6	0	1.0	0	I	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	I	0	0	0	1.0	0	0	0	0
10	0	0	0	I	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	15	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	I	0	0	0	0	0	0	0	0
16	0	0	0	I	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	I	0	0	0	0	0	0	0	0.82	0
24	0	0	I	0	0	0	0	0	0	0	0	0
25	0	0	I	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	2.5	34	0	0.73
27	0	0	0	0	0	0	0	0	0	0	0	16
28	0	0	0	0	0	0	0	0	0	0	0	13
29	0	0	0	0		0	0	0	0	0.18	0	33
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

*I = Ice or snow present in channel.

E124 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0.04	0	0	0	0	0	0.06	0.22	3.7	2.7	18	25
Max Daily Peak (ft³/s)	0	1.0	0	0	0	0	0	1.0	2.5	34	15	33	34
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	3	6	0	0	0	0	0	0	0	0	9

E125 Sandia Canyon above SR 4

Location. Lat 35° 51' 32", long -106° 13' 34", SW ¼, Sec. 20, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 2.05 mi².

Period of Record. October 1, 1994, to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6495 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 3 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 104 ft³/s, September 13, 2013, gage height 5.08 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 1.1 ft³/s, July 26, 2017, gage height 1.2 ft.



E125 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system. All equipment is housed in a NEMA shelter on an 18-in. CMP well. The station is equipped with an ISCO pump sampler (12-count 1-L glass and polyethylene bottles) to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. The control is a concrete broad-crested weir. No provision has been made for measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is straight for 150 ft above and 100 ft below the gage. The bed material is sand with vegetation on the banks, and the bottom is well supported.

Rating No. 2 was developed and applied beginning October 1, 2009, to account for 1 ft of channel aggradation along the reach. The channel slopes smoothly through the reach, replacing the broad-crested concrete weir as the control. The rating was computed using Manning's equation and measured channel characteristics of the 2-ft point of zero flow (PZF) to top of weir walls at 3.20 ft. Greater flow will require the extension of Rating No. 2 with a more detailed channel survey.

No discharge measurements were made during the year.

Discharge. Discharge was directly computed from Rating No. 2.

E125 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	1.1	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E125 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	1.1	0	0	1.1
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

Mortandad Watershed

The Mortandad Canyon watershed is located in the central portion of LANL and covers approximately 10 mi². The watershed contains a stream that is entirely ephemeral; neither perennial springs nor natural perennial reaches occur. The Mortandad watershed trends east-to-southeast and heads on the Pajarito Plateau near the main LANL complex at TA-03 at an elevation of 7380 ft. The drainage extends from its headwaters to its confluence with the Rio Grande at an elevation of 5440 ft. Mortandad Canyon crosses Pueblo de San Ildefonso land for several miles before joining the Rio Grande. The Mortandad watershed may be influenced by two significant tributaries: Ten Site Canyon and Cañada del Buey. Snowmelt runoff and storm water runoff from seasonal snow and rain storms flow for a limited distance in the upper canyon and occasionally as far as the sediment traps. Ten Site Canyon lies south of and extends parallel to Mortandad Canyon for about 1.5 mi. Ten Site Canyon joins Mortandad Canyon in the lower portion of the drainage. Cañada del Buey heads on LANL property at TA-52 and TA-36 at an elevation of approximately 7200 ft and trends east-southeast across LANL, Pueblo de San Ildefonso land, and Los Alamos County and ends at its confluence with Mortandad Canyon at an elevation of 5620 ft, approximately 0.5 mi upstream of the Rio Grande.

Figure 5 shows the total monthly volume of discharge at the four stream gage stations within the Mortandad Canyon and Cañada del Buey watershed.




Figure 5 Total monthly volume (acre-ft) for WY 2017 in Mortandad Canyon and Cañada del Buey

E201 Mortandad Canyon above Ten Site Canyon

Location. Lat 35° 51' 46", long -106° 16' 29", SW ¼, Sec. 22, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.25 mi².

Period of Record. October 1, 2006, to September 30, 2017.

Revised Record. Period of Record (2008).

Gage. Data logger with radio telemetry and a steel-fabricated nonstandard flume. Elevation of the gage is 6865 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 5 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 107 ft³/s, September 13, 2013, gage height 3.0 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 2.9 ft³/s, September 29, 2017, gage height 0.97 ft.



E201 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Milltronics sonic probe mounted on a 10-ft flume. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- × 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year, except for December 17-31, 2016; January 1, 5-9, and 20-23, 2017; and February 12-13, 2017, because of ice and snow in the channel.

Rating. The channel is straight above and below the modified flume. Flow is confined to the cutbanks. The channel bottom is 3 ft wide with some vegetation above and below the flume.

The streambed is sand and gravel, and the flume is subject to fill from low-flow events. The control is a fabricated steel flume 10 ft at the throat.

Rating No. 2 was developed based on slope-area computations and discharge measurements.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying Rating No. 2.

E201 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	I*	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	I	0	0	0	0	0	0	0	0
6	0	0	0	I	0	0	0	0	0	0	0	0
7	0	0	0	I	0	0	0	0	0	0	0	0
8	0	0	0	I	0	0	0	0	0	0	0	0
9	0	0	0	I	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	I	0	0	0	0	0	0	0
13	0	0	0	0	I	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	I	0.27	0	0	0	0	0	0	0	0
18	0	0	I	1.2	0	0	0	0	0	0	0	0
19	0	0	I	0	0	0	0	0	0	0	0	0
20	0	0	I	I	0	0	0	0	0	0	0	0
21	0	0	I	I	0	0	0	0	0	0	0	0
22	0	0.29	I	I	0	0	0	0	0	0	0	0
23	0	0	I	I	0	0	0	0	0	0	0	0
24	0	0	I	0	0	0	0	0	0	0	0	0
25	0	0	I	0	0	0.06	0	0	0	0	0	0
26	0	0	I	0	0	0	0	0	0	0	0	0
27	0	0	I	0	0	0	0	0	0	0	0	0
28	0	0	I	0	0	0	0	0	0	0	0	0
29	0	0	I	0		0	0.79	0	0	0	0	2.9
30	0	0	I	0		0.19	0	0	0	0	0	0
31	0		I	0		0		0		0	0	

*I = Ice or snow present in channel.

E201 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	I*	0	0	0.14	0	0	0	0	0.54	0.68
Max Daily Peak (ft³/s)	0	0.29	0	1.2	0	0.19	0.79	0	0	0	0	2.9	2.9
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	15	10	2	0	0	0	0	0	0	0	27

*I = Ice or snow present in channel.

E201.5 Ten Site Canyon above Mortandad Canyon

Location. Lat 35° 51' 38", long -106° 16' 30", SE ¼, Sec. 23, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 0.32 mi².

Period of Record. October 2000 to September 30, 2017.

Revised record. Drainage area (2006).

Gage. Data logger with radio telemetry and 90° sharp-crested weir. Elevation of gage is 6858 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 6 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 303 ft³/s, August 25, 2006, gage height 4.6 ft (from slope-area measurement of peak flow).

Maximum Discharge for Current Water Year. Maximum discharge, 31 ft³/s, July 26, 2017, gage height 3.46 ft



E201.5 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubble sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is also equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provisions have been made for measurements above the wading stage.

Datum Correction. On May 24, 2007, the gage was set to correct the datum. The gage was destroyed by flood on August 25, 2006. The bubbler outlet was reset to a gage datum of 1.33 ft.

Gage-Height Record. The data logger reference to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is about 8 ft wide and straight for about 60 ft upstream and straight for about 30 ft downstream. The streambed through this reach is primarily sand with gravel.

Rating No. 2 is based on a theoretical computation for the 90-degree sharp-crested weir and one critical-depth computation.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying Rating No. 2.

E201.5 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	31	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0	0	0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E201.5 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0.45	0	0	0.45
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	31	0	0	31
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E204 Mortandad Canyon at LANL Boundary

Location. Lat 35° 51' 21", long -106° 14' 43", NW ¼, Sec. 30, T. 19 N., R. 7 E., Santa Fe County.

Drainage Area. 1.61 mi².

Period of Record. October 1, 1993, to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6654 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 5 yr, 1 acre-ft.

Maximum Discharge for Period of Record. Maximum discharge, 102 ft³/s, September 13, 2013, gage height 1.85 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 3.1 ft³/s, September 19, 2017, gage height 1.06 ft.



E204 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on top of a 24-in. CMP well. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage. All high-flow measurements will be by slope-area or critical-depth computation methods.

Datum Correction. Levels run on May 24, 2007, showed the gage to be reading within allowable limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record, except for July 20 to 24, 2017, when the datalogger malfunctioned.

Rating. The channel is straight above and below the gage for 100 ft. The channel is not well defined and resembles a low grass-covered swale. Flow is infrequent. The control is a broad-crested weir with a v-notch 5 ft downstream from the gage.

Rating No. 1 was developed using slope-area computations. The PZF is well defined for the concrete broad-crested weir.

No discharge measurements were made during the year.

Discharge. No flow occurs most of the time. Discharge was computed by directly applying Rating No. 1.

E204 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0.23	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	3.1
20	0	0	0	0	0	0	0	0	0	E*	0	0
21	0	0	0	0	0	0	0	0	0	E	0	0
22	0	0	0	0	0	0	0	0	0	E	0	0
23	0	0	0	0	0	0	0	0	0	E	0	0
24	0	0	0	0	0	0	0	0	0	E	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	1.3	0	0
27	0	0	0	0	0	0	0	0	0	0.06	0	0.25
28	0	0	0	0	0	0	0	0	0	0	0	0.32
29	0	0	0	0		0	0	0	0	0	0	0.29
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

*E = Equipment failure.

E204 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0.16	0.01	0.09	0.26
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	1.3	0.23	3.1	3.1
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	5	0	0	5

E229.3 Cañada del Buey at SR 4

Location. Lat 35° 49' 41", long -106° 13' 23", Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 1.81 mi².

Period of Record. April 24, 2013, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6510 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 5 yr, 2 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 28 ft³/s, August 8, 2013, gage height 1.84 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 1.5 ft³/s, September 29, 2017, gage height 0.46 ft.



E229.3 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS radio transceiver, and a Sutron Accubar air-purge bubble sensor, housed in a NEMA shelter. Also, a Milltronics Sonic probe sits atop a 2-ft-wide by 1.5-ft-deep Parshall flume. No provision has been made for direct discharge measurements above the wading stage. The station is equipped with an ISCO pump sampler (12-count 1-L glass and polyethylene bottles) to collect water-quality samples. The ISCO is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. A line-of-sight radio transceiver provides 5-min stage data from the bubble sensor and probe.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record, except for January 20–26, 2017; and April 29, 2017, when the gage was affected by ice and snow.

Rating. Rating No. 1 is based on the formula for a 2-ft-wide by 1.5-ft-deep Parshall flume, with additional flow added for flow over the flume, based on a broad-crested weir equation. A gabion wall, for the flume overflow, forms a raised, rectangular cross-section 1.5 ft deep x 15 ft wide.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying Rating No. 1.

E229.3 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0.11	0	0	0	0	0	0	0	0
7	0	0	0	0.06	0	0	0	0	0	0	0	0
8	0	0	0	0.11	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0.05	0	0	0	0	0	0	0
13	0	0	0	0	0.71	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	I*	0	0	0	0	0	0	0	0
21	0	0.03	0	I	0	0	0	0	0	0	0	0
22	0	0	0.17	I	0	0	0	0	0	0	0	0
23	0	0	0.08	I	0	0	0	0	0	0	0	0
24	0	0	0	I	0	0	0	0	0	0	0	0
25	0	0	0	I	0	0	0	0	0	0	0	0
26	0	0	0	I	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0.88
28	0	0	0	0	0	0	0	0	0	0	0	0.61
29	0	0	0	0		0	I	0	0	0	0	1.5
30	0	0	0	0		0	0	0	0	0	0	0.06
31	0		0	0		0		0		0	0	

*I = Ice or snow present in channel.

E229.3 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0.02	I*	0.25	0	0	0	0	0	0	0.05	0.32
Max Daily Peak (ft³/s)	0	0.03	0.17	0.11	0.71	0	0	0	0	0	0	1.5	1.5
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	7	0	0	1	0	0	0	0	0	8

*I = Ice or snow present in channel.

Pajarito Watershed

The Pajarito Canyon watershed is located in the central portion of LANL and is approximately 13.6 mi² in area. The head of the watershed is located in the Sierra de los Valles at an elevation of 10,441 ft at Pajarito Mountain. The watershed is a long, east-southeast trending canyon that extends across Valles Caldera National Preserve land and Santa Fe National Forest before it enters LANL's western boundary. Two major tributary canyons, Two Mile and Three Mile Canyons, intersect Pajarito Canyon on LANL property. The watershed reaches the Rio Grande at an elevation of approximately 5410 ft. Two Mile Canyon heads in the Sierra de los Valles and has a length of approximately 5 mi and a drainage area of 3.1 mi², 70% of which is on LANL land. Sections of the upper portion of Pajarito watershed burned during the Las Conchas fire in June and July 2011. Both Two Mile and Three Mile Canyons contain ephemeral and intermittent streams. Seasonal springs in Two Mile Canyon and perennial springs in Three Mile Canyon support short reaches of ephemeral and perennial flow, respectively. East of the confluence with Three Mile Canyon, Pajarito Canyon is ephemeral across LANL property to a point approximately 0.4 mi upstream from the confluence with the Rio Grande. In most years, snowmelt runoff extends onto LANL property downstream to near the confluence with Three Mile Canyon. Local runoff and stream flow from seasonal rainstorms occasionally extend downstream as far as the Rio Grande.

The Pajarito watershed contains, or may influence, 12 wetland areas totaling approximately 15.80 acres. Figure 6 shows the total monthly volume of discharge for the four stream discharge gage stations within the Pajarito watershed. E245.5 received the most discharge during the July/August monsoon months.




Figure 6 Total monthly volume (acre-ft) for WY 2017 for Pajarito Canyon

E240 Pajarito Canyon below SR 501

Location. Lat 35° 52' 02", long -106° 21' 05", NW ¼, Sec. 19, T. 19 N., R. 6 E., Los Alamos County.

Drainage Area. 1.90 mi².

Period of Record. October 1993 to June 28, 2000 (destroyed by flood); April 2001 to September 30, 2017.

Revised Record. Water Data Report 1997: Gage height "Extremes for Period of Record." Drainage area (2006). Levels date published as 2004, correction to December 2001 (2008).

Gage. Data logger with radio telemetry. Elevation of gage is 7719 ft using LANL LIDAR DEM with NAD 83. Formerly published as "Pajarito Canyon above Highway 501 near Los Alamos, NM" at different datum.

Average Volume. 6 yr, 11 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 1020 ft³/s, June 28, 2000, from peak-flow computation; gage height not determined.

Maximum Discharge for Current Water Year. Maximum discharge, 0.14 ft³/s, September 28, 2017, gage height 0.81 ft.



E240 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on top of a 24-in. CMP well. The station is equipped with two ISCO pump samplers to collect water-quality samples. The ISCO samplers are housed in a separate shelter, a 3- × 4-ft metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage.

The station is also equipped with a rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. The levels run December 11, 2001, show the gage to be within limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The gage is about 300 ft below the outlet of two round culverts through the NM 501 road bed. The channel bed is sand and gravel and subject to movement. The grass and brush are fairly thick in overbank areas. The banks are not high (about 1 to 2 ft in most places). Two gabions were installed in the fall of 2001, which act as low-water controls. One is 2 ft below the gage across the entire width of the channel with a 6-in. v-notch for low water. Another gabion is 50 ft above the gage.

Rating No. 4 was developed based on the six measurements and slope area from previous years.

No discharge measurements were made during the year.

Discharge. Discharge was computed by applying the gage height to Rating No. 3 using variable shift diagrams.

E240 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0.06
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0.07
28	0	0	0	0	0	0	0	0	0	0	0	0.14
29	0	0	0	0		0	0	0	0	0	0	0.07
30	0	0	0	0		0	0	0	0	0	0	0.01
31	0		0	0		0		0		0	0	

E240 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0.03	0.03
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0.14	0.14
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E243 Pajarito Canyon above Two Mile Canyon

Location. Lat 35° 51' 14", long -106° 17' 48", Sec. 27, T. 19N., R. 6 E., Ramon Vigil Grant, Los Alamos County.

Drainage Area. 4.24 mi².

Period of Record. February 2002 to August 11, 2011, and August 5, 2014, to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry. Elevation of gage 6941 ft above NGVD from global positioning system (GPS) survey.

Average Volume. 3 yr, 1 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 746 ft³/s, August 21, 2011, estimated from high-water mark survey.

Maximum Discharge for Current Water Year. Maximum discharge, 0.14 ft³/s, September 29, 2017, gage height 3.70 ft.



E243 Stream gage downstream view

Equipment. Station is equipped with a Sutron 9210 data logger (5-min interval) with a Sutron Accubar bubble sensor with cellular telemetry and speech modem. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler for water quality sample collection. The ISCO is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. No provision has been made for direct measurement above the wading stage. During the August 21, 2011, severe storm event, a bubbler line was destroyed along with a shelter, a data logger, and the associated ISCO intake suction lines. The gage was deemed unusable and the logged data was irretrievable. The gage station was restored to working condition in August 2014.

Datum Correction. None. The levels run on April 7, 2006, found the gage to be within limits. No corrections were needed.

Gage-Height Record. The data logger referenced to the outside staff gave a complete and satisfactory record for the year.

Rating. The channel is straight for 150 ft above and below the gage. The channel is trapezoidal with the bed fairly well armored with large gravel and some cobbles. The banks are fairly well vegetated with grasses and should remain stable at all flows.

Rating No. 4 was continued in use.

Discharge. Discharge was computed by applying gage height to Rating No. 4 with shifts at low flow applied by "V" diagrams. The PZF shows some estimated zero flow in winter from icing over the orifice; the stream was frozen dry during this time.

E243 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0.01	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0.01	0	0	0	0
20	0	0	0	0.03	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0.01	0	0	0	0
22	0	0	0	0	0	0	0	0.01	0	0	0	0
23	0	0	0	0	0	0	0	0.01	0	0	0	0
24	0	0	0	0	0	0	0	0.02	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0.14
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E243 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	<0.010	0	0	0	<0.010	0.01
Max Daily Peak (ft³/s)	0	0	0	0.03	0	0	0	0.02	0	0	0	0.14	0.14
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E244 Two Mile Canyon above Pajarito Canyon

Location. Lat 35° 51' 15", long -106° 17' 46", Sec. 27, T. 19 N., R. 6 E., Ramon Vigil Grant, Los Alamos County.

Drainage Area. 3.15 mi².

Period of Record. October 1, 2002, to July 13, 2011, and June 18, 2014, to September 30, 2017.

Revised Record. Drainage area (2006). Period of record (2008). Period of record (2014).

Gage. Data logger and radio telemetry. Elevation of gage is 6940 ft above NGVD from GPS survey.

Average Volume. 3 yr, 26 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 628 ft³/s, August 25, 2006, gage height 6.01 ft (from flood marks). No flow most of time.

Maximum Discharge for Current Water Year. Maximum discharge, 31 ft³/s, May 24, 2017, gage height 6.35 ft.



E244 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval) and milltronics sonic probe with cellular phone and speech modem. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler for water quality sample collection. The ISCO is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. Wading measurements can be in the vicinity of the gage. No provision has been made for measurement above the wading stages.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year, except for January 5-31, 2017; February 1-11, 2017, because of snow and ice in the channel; and June 20-23, 2017, when maintenance was performed.

Rating. The channel at the gage is straight for about 150 ft above gage and 50 ft below gage. The channel expands quite a bit below gage. The bed material is coarse sand and gravel. The banks are grassy with some small trees and outcrops affecting roughness at higher flows.

No discharge measurements were made during the year.

Rating No. 2 was developed from previous measurements and one slope area measurement.

Discharge. Discharge was computed by directly applying Rating No. 2.

E244 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0.06	0	I ^a	0	0	0	0	0	0	0
2	0	0	0	0	I	0	0	0	0	0.12	0.02	0.04
3	0	0	0.02	0	I	0	0	0	0	0	0	0.04
4	0	0	0.06	0	I	0	0	0	0	0	0	0.04
5	0	0.07	0.02	I	I	0	0	0	0	0	0	0
6	0	0	0	I	I	0	0	0	0	0.04	0	0
7	0	0	0	I	I	0	0	0	11	0.02	0	0
8	0	0	0.02	I	I	0	0	0	22	0.02	0	0
9	0	0	0.06	I	I	0	0	0	0	0.02	0	0.02
10	0	0	0.02	I	I	0	0	0	0	0.04	0.02	0.02
11	0	0	0	I	I	0	0	12	0	0	0	0.04
12	0	0	0	I	0.06	0	0	12	0	0.04	0	0.02
13	0	0	0	I	0.38	0	0	12	0	0	0	0.04
14	0	0	0	I	0	0	0	12	0	0	0.02	0
15	0	0	0	I	0.04	0	0	11	0	0	0	0.04
16	0	0	0	I	0.09	0	0	12	0	0	0	0.02
17	0	0	0	I	0	0	0	12	0	0	0	0.04
18	0	0.04	0.09	I	0	0	0	12	0	0.02	2.5	0
19	0	0.02	0.12	I	0	0	0	17	15	0.02	0	0.04
20	0	0	0.06	I	0	0	0	12	T ^b	0.00	0	0.04
21	0	0	0	I	0	0	0	12	T	0.00	0	0.06
22	0	0	0.21	I	0	0	0	11	T	0.00	0	0.09
23	0	0.11	0.19	I	0	0	0	12	T	0.04	0	0.04
24	0	0	0.15	I	0.14	0	0	31	0	0.00	0	0.06
25	0	0.02	0.15	I	0.19	0	0	0	0	0.00	0	0.06
26	0	0.02	0.19	I	0.12	0	0.74	8.7	0	0.25	0	0.00
27	0	0	0.19	I	0.15	0	0	0	0	0.00	0.04	0.38
28	0	0	0.15	I	0	0	0	13	0	0.00	0.00	2.3
29	0	0	0.14	I		0	0.74	0	0	0.00	0.00	3.7
30	0	0	0.15	I		0	0.25	0	0.02	0	0.02	0
31	0		0.17	I		0		0		0	0	

^a I = Ice or snow present in channel.^b T = Testing or maintenance performed.

E244 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0.95	I*	I	0	0.20	1.2	0.55	0	0.02	0.76	4.0
Max Daily Peak (ft³/s)	0	0.11	0.21	I	0.38	0.19	0.74	31	22	0.25	2.5	3.7	31
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	27	11	0	0	0	4	0	0	0	42

*I = Ice or snow present in channel.

E245.5 Pajarito Canyon above Three Mile Canyon

Location. Lat 35° 50' 45.3", long -106° 16' 29", Sec. 16, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 7.81 mi².

Period of Record. October 1, 2002, to September 30, 2017.

Revised Record. Drainage area (2008).

Gage. Data logger and radio telemetry. Elevation of gage is 6796 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 146 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 630 ft³/s, September 13, 2013, gage height 4.82 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 43 ft³/s, September 29, 2017, gage height 2.84 ft.



E245.5 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Milltronics sonic probe. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stage.

The station is also equipped with a tipping bucket rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. Levels run May 12, 2008, show the gage to be within limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is straight for 80 ft above and below the gage. The banks have some vegetation, and the streambed is sand and gravel.

Rating No. 4 was developed from previous measurements and one critical-depth computation.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying Rating No. 4.

E245.5 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.33	0.10	0	0	0.20	0	0	0	0.80	0.23	0	0.07
2	0.23	0.70	0	0.03	0.17	0	0	0	0.97	0.63	0	0.07
3	0.50	0.87	0	0	0.20	0	0	0	0.97	0.70	0	0.03
4	0.50	0	0	0.07	0.23	0.7	0	0.13	0.87	1.1	0	0.10
5	0	0	0	0.10	0.20	0	0.07	0.20	0.83	0.17	0	0.10
6	0	0.20	0.07	0.53	0.17	0	0	0.27	1.87	0.07	0.03	0.23
7	0	0.40	0.07	0.63	0.10	1.0	0.03	0.23	0.87	0.07	0.17	0.27
8	0	0.33	0	0.60	0.13	0.5	0.03	0.27	0.80	0.03	0	0.37
9	0	0.40	0	0.20	0.10	1.4	0.13	0.23	2.7	0.00	0	0.37
10	0	0.60	0	0	0.13	0	0.27	2.0	2.1	0.00	0.63	0.23
11	0	0.87	0.13	0.07	0	0	0.03	1.9	2.5	0.13	1.0	0.47
12	0	0.37	0	0.03	0.53	0	0	0.63	2.5	0.80	11	0.43
13	0	0	0	0.03	1.0	0	0.43	1.6	0.87	0.37	1.4	0.43
14	0	0	0	0	0	0	0.40	2.4	0.03	0.00	3.5	0.50
15	0	0	0	0	0	0	0.37	0.83	0.20	0.00	0.07	0.53
16	0	0	0	0	0	0	0.43	0.93	0.60	0.00	0.03	0.77
17	0	0	0	0	0	0	0.30	0.70	0.37	0.00	0.03	0.57
18	0	0	0.03	0.03	0	0	2.8	0.90	0.83	0.00	0.10	1.5
19	0	0	0	0.07	0	0	0.67	1.9	0.33	0.00	0.03	1.6
20	0	0	0	0.17	0	0	0.23	1.1	0.07	0.10	0.07	1.7
21	0	0	0	2.0	0	0	0.27	6.4	0.23	0.00	0.17	1.3
22	0	0	0.67	1.1	0	0	0	2.3	1.00	0.43	0.27	1.1
23	0	0	0.67	1.3	0.13	0	0	1.4	1.87	0.87	0.33	0.70
24	0.4	0	0.37	0.63	0	0	0	2.4	0.60	0.93	0.17	0.67
25	0	0	0.13	0.63	0	0	0.70	2.4	0.57	1.4	0.10	2.3
26	1.1	0	0.20	0.50	0	0	0.03	2.0	0.43	0.03	0.13	2.1
27	0.07	0	0.23	0.53	0	0	0.23	2.0	0.70	0.07	0.17	0.33
28	0.63	0	0.17	0.43	0	0	0.17	0	0.97	0.07	0.03	1.7
29	0.73	0	0.07	0.50		0	1.9	0	0.87	0	0.07	43
30	0.77	0	0	0.27		0	0	0.5	0.67	0	0.03	0.27
31	0.17		0	0.20		0		0.9		0	0.13	

E245.5 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	1.7	2.4	2.0	12	1.4	2.2	0.74	21	11	2.0	5.6	29	91
Max Daily Peak (ft³/s)	1.1	0.87	0.67	2.0	1.0	1.4	2.8	6.4	2.7	1.4	11	43	43
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E246 Three Mile Canyon above Pajarito Canyon

Location. Lat 35° 50' 20", long -106° 16' 17", Sec. 35, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 1.62 mi².

Period of Record. October 1998 to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger and 9-in. Parshall flume with radio telemetry. Elevation of gage is 6759 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 4 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 900 ft³/s, September 13, 2013, gage height 4.6 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 0.09 ft³/s, April 29, 2017, gage height 0.15 ft.



E246 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Milltronics sonic probe mounted on a 9-in. Parshall flume. The system is powered by a solar-panel battery system housed in a NEMA shelter on the right bank. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. The staff gage in the 90-in. Parshall flume is the reference gage. No provision has been made for direct discharge measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record, except for December 22–January 11, January 21–26, and February 12–15, 2017, when the gage was affected by ice.

Rating. The channel is straight above and below the gage. Streamflow is confined to the main channel by cutbanks on both sides. The bottom is 10 ft wide; the channel is prone to some shifting with vegetation on each bank. The low-water control is the 9-in. Parshall flume.

Rating No. 1 was developed based on the computation of the 9-in. Parshall flume and was extended on the basis of two critical-depth computations. The PZF is 0.00 gage height.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 1.

E246 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	I*	0	0	0	0	0	0	0	0
2	0	0	0	I	0	0	0	0	0	0	0	0
3	0	0	0	I	0	0	0	0	0	0	0	0
4	0	0	0	I	0	0	0	0	0	0	0	0
5	0	0	0	I	0	0	0	0	0	0	0	0
6	0	0	0	I	0	0	0	0	0	0	0	0
7	0	0	0	I	0	0	0	0	0.02	0	0	0
8	0	0	0	I	0	0	0	0	0	0	0	0
9	0	0	0	I	0	0	0	0	0	0	0	0
10	0	0	0	I	0	0	0	0	0	0	0	0
11	0	0	0	I	0	0	0	0	0	0	0	0
12	0	0	0	0	I	0	0	0	0	0	0	0
13	0	0	0	0	I	0	0	0	0	0	0	0
14	0	0	0	0	I	0	0	0	0	0	0	0
15	0	0	0	0	I	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	I	0	0	0	0	0	0	0	0
22	0	0	I	I	0	0	0	0	0	0	0	0
23	0	0	I	I	0	0	0	0	0	0	0	0
24	0	0	I	I	0	0	0	0	0	0	0	0
25	0	0	I	I	0	0	0	0	0	0	0	0
26	0	0	I	I	0	0	0	0	0	0	0	0
27	0	0	I	0	0	0	0	0	0	0	0	0
28	0	0	I	0	0	0	0	0	0	0	0	0
29	0	0	I	0		0	0.11	0	0	0	0	0
30	0	0	I	0		0	0	0	0	0	0	0
31	0		I	0		0		0		0	0	

*I = Ice or snow present in channel.

E246 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	I*	0	0	0.03	0	0	0	0	0	0.03
Max Daily Peak (acre-ft)	0	0	0	I	0	0	0.11	0	0.02	0	0	0	0.11
Min Daily Peak (acre-ft)	0	0	0	I	0	0	0	0	0	0	0	0	0
Missing Days	0	0	10	17	4	0	0	0	0	0	0	0	31

*I = Ice or snow present in channel.

E250 Pajarito Canyon above SR 4

Location. Lat 35° 49' 26", long -106° 13' 40", Sec. 5, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 10.6 mi².

Period of Record. November 1993 to August 25, 2006 (destroyed by flood); September 2006 to September 13, 2013 (damaged by high-flow event); and October 1, 2014, to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6535 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 3 yr, 2 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 960 ft³/s, September 13, 2013, gage height 5.23 ft.

Maximum Discharge for Current Water Year. No measured discharge for the year.



E250 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on an 18-in. CMP well. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stage.

Datum Correction. None. The most recent levels run on November 17, 2004, found the gage to be within acceptable limits.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year, except September 14 and 15, 2017, when equipment maintenance was performed.

Rating. The channel is straight for 50 ft above and 100 ft below the gage. The streambed material is gravel. The control is concrete with a 90-degree weir plate.

Rating No. 1 was developed from a 90-degree weir plate formula and broad-crested weir computation above the notch. Rating No. 1 has been used and is considered good.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 1.

E250 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	T*
15	0	0	0	0	0	0	0	0	0	0	0	T
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

*T=testing or maintenance performed.

E250 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Max Daily Peak (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Min Daily (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	2	2

Water/Cañon de Valle Watershed

The Water Canyon/Cañon de Valle watershed is an east-to-southeast trending drainage that originates on the eastern slopes of the Sierra de los Valles in the Valles Caldera National Preserve at an elevation of 10,380 ft. The watershed remains on the Valles Caldera National Preserve for 0.4 mi, and then passes through 2.8 mi of the Santa Fe National Forest before it crosses into LANL property at the western boundary of TA-16. Primary canyons within this watershed are Cañon de Valle, the primary tributary to Water Canyon, and Potrillo and Fence Canyons.

The Water/Cañon de Valle watershed consists mainly of occasional perennial reaches arising from springs that occur in the upper reaches of the watershed; however, streams in Potrillo and Fence Canyons are entirely ephemeral in nature. Springs on the flanks of the Jemez Mountains, west of LANL's western boundary, supply flow to the upper reaches of the Water/Cañon de Valle watershed. Perennial water exists from NM 501 to the eastern edge of TA-28 in upper Water Canyon and from Peter Seep in Cañon de Valle. Streams in middle and lower Water Canyon are ephemeral, except for a perennial reach in the lower canyon supported by Spring 5AA. The Water/Cañon de Valle watershed contains, or may influence, three wetland areas totaling approximately 0.23 acres.

Water Canyon has a channel length of 13.8 mi and a drainage area of 8.8 mi². Several perennial springs are located in the upper reaches of Water Canyon and Cañon de Valle (the major subdrainage to Water Canyon). Stream flow is ephemeral over most of the canyon passing through LANL property. Several perennial springs are located in upper Water Canyon in the Santa Fe National Forest, including Armistead and American Springs. These springs result in perennial reaches. A small perennial spring in lower Water Canyon, below the confluence with Potrillo Canyon, supports a very short perennial reach. Snowmelt seldom extends downstream as far as the LANL boundary.

Cañon de Valle originates west of LANL property, on the eastern slopes of the Sierra de los Valles in the Valles Caldera National Preserve at an elevation of 10,389 ft. The canyon extends east-southeast for 0.4 mi, crosses into the Santa Fe National Forest, and continues east-southeast for 2.8 mi before entering LANL property at the western boundary. Cañon de Valle has a channel length of 7.5 mi and a drainage area of 4.2 mi². Flow in Cañon de Valle is interrupted upstream of LANL's western boundary and is largely ephemeral on LANL property with short perennial reaches in the upper portion of the canyon. Several perennial springs located in the Santa Fe National Forest in upper Cañon de Valle result in perennial reaches.

Figure 7 shows the total monthly volume of discharge for the five stream gage discharge stations within the Water Canyon and Cañon de Valle watershed.




Figure 7 Total monthly volume (acre-ft) for WY 2017 in Water Canyon, Cañon de Valle, and Fence Canyon

E252 Water Canyon above SR 501

Location. Lat 35° 50' 18", long -106° 21' 42", Sec. 36, T. 19 N., R. 5 E., Los Alamos County in Santa Fe National Forest.

Drainage Area. 3.25 mi².

Period of Record. October 1994 to June 2000 (destroyed by flood); April 2001 to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry. Elevation of gage is 7556 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 20 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 1577 ft³/s, August 21, 2011, estimated with high-water-mark survey.

Maximum Discharge for Current Water Year. Maximum discharge, 0.21 ft³/s, May 09, 2017, gage height 4.25 ft.



E252 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system (5-min interval). The system is powered by a solar-panel battery system housed in a NEMA shelter on a 24-in. CMP well. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- × 4-ft steel storage box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. There is no low-water control. No provision has been made for direct discharge measurements above the wading stage.

Datum Correction. None. Levels were run when the gage was established on April 16, 2001. The new gage is at the same datum as the old and is about 20 ft upstream.

Gage-Height Record. The data logger referenced to the inside staff gage and reference point gave a complete and satisfactory record for the year.

Rating. The channel at the gage is 30 ft wide and straight for about 40 ft upstream, then bends to the left; downstream the gage is straight for 100 ft. The streambed through this reach is primarily sand, gravel, and cobbles. The low-flow control is a rock riffle 5 ft below the gage. The channel has been scoured and filled significantly by high flows resulting from both the Cerro Grande and Las Conchas fires.

Rating No. 4 was based on a step-backwater survey conducted on November 18, 2011, following major channel aggradation during an August 21, 2011, runoff event. Steep slopes in the gage reach and throughout the region cause considerable movement of material as either scours or fills.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the inside gage height to Rating No. 4.

E252 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.02	0.01	0.01	0.01	0	0.11	0.03	0	0.09	0.05	0.01	0
2	0.01	0.01	0.01	0	0	0.10	0.03	0	0.07	0.05	0.01	0
3	0.01	0.01	0.01	0	0	0.10	0.03	0	0.07	0.05	0.01	0
4	0.01	0.01	0.01	0	0.01	0.10	0.03	0.15	0.07	0.04	0.01	0
5	0.01	0.01	0.01	0	0.01	0.11	0.03	0.17	0.06	0.04	0.01	0
6	0.01	0.01	0.01	0	0.01	0.11	0.03	0.17	0.08	0.03	0.02	0
7	0.01	0.01	0.01	0	0.01	0.11	0.03	0.14	0.06	0.03	0.02	0
8	0.01	0.01	0.01	0	0.01	0.11	0.03	0.15	0.06	0.03	0.02	0
9	0.01	0.01	0.01	0	0.01	0.11	0.03	0.21	0.06	0.02	0.02	0
10	0.01	0.01	0.01	0	0.05	0.12	0.03	0.15	0.06	0.02	0.01	0
11	0.01	0.01	0.01	0	0.12	0.15	0.03	0.14	0.05	0.02	0.02	0
12	0.01	0.01	0.01	0	0.19	0.15	0.03	0.14	0.05	0.08	0.01	0
13	0.01	0.01	0.01	0	0.19	0.15	0.03	0.12	0.05	0.02	0.01	0
14	0.01	0.01	0.01	0	0.19	0.11	0.03	0.12	0.05	0.02	0.01	0
15	0.01	0.01	0.01	0	0.17	0.05	0.03	0.11	0.05	0.02	0.01	0
16	0.01	0.01	0.01	0.01	0.15	0.02	0.02	0.11	0.05	0.02	0.01	0
17	0.01	0.01	0.01	0.01	0.15	0.05	0.02	0.11	0.05	0.02	0.01	0
18	0.01	0.01	0.01	0.01	0.15	0.05	0.02	0.10	0.05	0.02	0	0
19	0.01	0.01	0.01	0.01	0.15	0.05	0.02	0.10	0.05	0.02	0	0
20	0.01	0.01	0.01	0.01	0.15	0.05	0.02	0.10	0.05	0.02	0	0
21	0.01	0.01	0.01	0.01	0.15	0.04	0.02	0.09	0.05	0.02	0	0
22	0.01	0.01	0.01	0.01	0.19	0.04	0.02	0.09	0.05	0.01	0	0
23	0.01	0.01	0.01	0.01	0.19	0.04	0.01	0.08	0.05	0.01	0	0
24	0.01	0.01	0.01	0.01	0.17	0.04	0.01	0.08	0.05	0.01	0	0
25	0.01	0.01	0.01	0.01	0.17	0.03	0.01	0.08	0.09	0.01	0	0
26	0.01	0.01	0.01	0.01	0.15	0.03	0.01	0.08	0.05	0.01	0.01	0
27	0.01	0.01	0.01	0.01	0.14	0.03	0.06	0.08	0.05	0	0.01	0.01
28	0.01	0.01	0.01	0.01	0.12	0.03	0.05	0.07	0.05	0	0.01	0.02
29	0.01	0.01	0.01	0.01		0.03	0.05	0.07	0.05	0.01	0.01	0.02
30	0.01	0.01	0.01	0		0.03	0.04	0.07	0.05	0	0.01	0.05
31	0.01		0.01	0		0.03		0.07		0.01	0	

E252 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0.62	0.66	0.67	0.33	5.5	4.6	1.5	6.0	3.0	1.2	0.41	0.08	24
Max Daily Peak (ft³/s)	0.02	0.01	0.01	0.01	0.19	0.15	0.06	0.21	0.09	0.08	0.02	0.05	0.21
Min Daily Peak (ft³/s)	0	0	0	0	0	0.01	0	0	0	0	0	0.01	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E253 Cañon de Valle above SR 501

Location. Lat 35° 51' 6", long -106° 21' 17", NE ¼, Sec. 25, T. 19 N., R. 5 E., Los Alamos County in Santa Fe National Forest.

Drainage Area. 2.27 mi².

Period of Record. October 1994 to June 2000 (gage destroyed by flood); January 31, 2001, to September 30, 2017.

Revised Record. Period of record (2012).

Gage. Data logger and 120-degree weir plate, rain gage with radio telemetry. Elevation of gage is 7707 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 47 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 1450 ft³/s, August 21, 2011, gage height 10 ft.

Maximum Discharge for Current Water Year. No measurable discharge for the water year.



E253 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on a 24-in. CMP well, 16 ft long attached to a 60-ft metal walkway. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft steel storage box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stage.

The station is also equipped with a rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. None. The levels were run on April 16, 2001, when the gage was reestablished.

Gage-Height Record. Stream gage E253 did not receive any discharge for WY 2017.

Rating. The channel at the gage is about 8 ft wide and straight for about 50 ft upstream, then bends to the left and straight for 100 ft downstream and bends to the right. The streambed through this reach is primarily gravel with cobbles. The low-flow control is a 120-degree sharp-crested weir. The channel becomes the control at high flow.

Rating No. 4 was developed from PZF measurement levels on October 28, 2011. Stage values were adjusted +0.10 for each discharge to continue to match the v-notch weir table.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 4.

E253 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E253 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E256 Cañon de Valle below MDA P

Location. Lat 35° 51' 01", long -106° 19' 56.4", Sec. 29, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 3.25 mi².

Period of Record. January 24, 2002, to August 21, 2011; August 15, 2014, to September 30, 2017.

Revised Record. Period of record (2014).

Gage. Data logger and 24-in. Parshall flume. Elevation of gage is 7329 ft above NGVD 29 from global positioning system survey.

Average Volume. 4 yr, 24 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 1024 ft³/s, August 21, 2011, estimated with high-water-mark survey.

Maximum Discharge for Current Water Year. Maximum discharge, 1.9 ft³/s, September 29, 2017, gage height 0.65 ft.



E256 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval) and a Sutron Accubar bubble sensor within a 24-in. Parshall flume. The system is powered by a solar-panel battery system housed in a NEMA shelter on the left bank. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. An outside staff gage is available for reference. No provision has been made for discharge measurements above the wading stage. During the August 21, 2011, severe storm event, the bubbler line was destroyed along with the shelter, the data logger, and associated ISCO intake suction lines. The gage was deemed unusable. The gage site was rebuilt in August 2014.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the inside staff gage gave a complete and satisfactory record for the year, except December 22, 2016, to January 6, 2017, when equipment failure occurred.

Rating. The channel is straight for 50 ft upstream and 20 ft downstream from the gage. The streambed consists of sand with gravel and is subject to filling behind the flume from flow events and gage silting problems. The banks are covered with vegetation. Rating No. 1 is based on the 24-in. Parshall flume. The rating curve was extrapolated to accommodate the peak stage of 3.75 ft.

Discharge. Discharge was computed by applying the gage height to Rating No. 1 using variable shift.

E256 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0.06	E*	0.06	0.13	0.42	0.38	0.11	0.02	0	0
2	0	0.02	0.05	E	0.05	0.13	0.42	0.38	0.11	0.02	0	0
3	0	0.02	0.05	E	0.05	0.13	0.38	0.38	0.11	0.08	0	0
4	0	0.06	0.05	E	0.06	0.16	0.42	0.38	0.11	0.20	0	0
5	0	0.34	0.05	E	0.06	0.20	0.38	0.34	0.11	0	0	0
6	0	0.23	0.05	E	0.06	0.16	0.38	0.34	0.47	0	0.13	0.77
7	0	0.06	0.05	0.20	0.27	0.13	0.42	0.34	0.16	0	0	0
8	0	0.05	0.05	0.05	0.27	0.16	0.42	0.30	0.11	0	0	0
9	0	0.03	0.11	0.34	0.30	0.16	0.42	0.56	0.11	0	0	0
10	0	0.03	0.05	0.13	0.51	0.66	0.42	0.30	0.08	0	0	0
11	0	0.03	0.05	0.06	0.51	0.20	0.42	0.27	0.08	0	0	0
12	0	0.03	0.05	0.06	0.30	0.16	0.42	0.27	0.08	0.34	0	0
13	0	0.03	0.05	0.06	0.23	0.13	0.47	0.27	0.06	0.03	0	0
14	0	0.05	0.05	0.23	0.16	0.13	0.42	0.27	0.06	0	0	0
15	0	0.05	0.05	0.66	0.16	0.13	0.42	0.23	0.06	0	0	0
16	0	0.05	0.13	0.20	0.16	0.11	0.42	0.23	0.06	0	0	0
17	0	0.05	0.11	0.13	0.16	0.11	0.47	0.20	0.06	0	0	0
18	0	0.05	0.08	0.13	0.20	0.11	0.47	0.20	0.06	0.02	0	0
19	0	0.05	0.20	0.08	0.23	0.11	0.47	0.23	0.05	0	0	0
20	0	0.05	0.30	0.08	0.20	0.11	0.42	0.20	0.06	0	0	0
21	0	0.16	0.06	0.23	0.20	0.11	0.42	0.16	0.06	0	0	0
22	0	0.08	E	0.08	0.27	0.11	0.42	0.16	0.05	0	0	0
23	0	0.06	E	0.08	0.23	0.13	0.42	0.16	0.05	0	0	0
24	0	0.05	E	0.08	0.16	0.13	0.42	0.16	0.06	0	0	0
25	0	0.05	E	0.13	0.13	0.16	0.47	0.13	1.4	0	0	0
26	0	0.05	E	0.51	0.13	0.16	0.47	0.13	0.11	0	0	0.03
27	0.02	0.06	E	1.1	0.13	0.20	0.42	0.13	0.05	0	0	0.71
28	0.02	0.05	E	1.7	0.16	0.24	0.47	0.13	0.03	0	0	1.7
29	0	0.05	E	0.08		0.38	0.47	0.11	0.02	0.08	0	1.9
30	0	0.05	E	0.11		0.30	0.42	0.13	0.02	0.02	0	0.27
31	0.02		E	0.11		0.34		0.11		0	0	

*E = Equipment failure.

E256 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total Volume (acre-ft)	0	2.1	E*	E	7.5	8.7	24	14	3.8	0.07	0.01	2.2	62
Max Daily Peak (ft³/s)	0.02	0.34	0.30	1.7	0.51	0.66	0.47	0.56	1.4	0.34	0.13	1.9	1.9
Min Daily Peak (ft³/s)	0	0	E	E	0	0	0	0	0	0	0	0	0
Missing Days	0	0	10	6	0	0	0	0	0	0	0	0	16

*E = Equipment failure.

E265 Water Canyon below SR 4

Location. Lat 35° 48' 18", long -106° 14' 31", Sec. 7, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 13.11 mi².

Period of Record. October 1993 to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry and stabilized natural rock control. Elevation of gage is 6311 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 46 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 2560 ft³/s, September 13, 2013, gage height 6.23 ft.

Maximum Discharge for Current Water Year. Maximum discharge, 0.34 ft³/s, November 5, 2016, gage height 0.30 ft.



E265 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on a 24-in. CMP well. The station is equipped with two ISCO pump samplers to collect water-quality samples. The ISCO samplers are housed in a separate shelter, a 3- x 4-in. metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage.

The station is also equipped with a tipping bucket rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is straight for 100 ft above and below the gage. The banks are low and have very little vegetation. The streambed is mostly rock with lenses of sand.

Rating No. 5 was used for the entire water year.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 5.

E265 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0.05	0.03	0.03	0	0.15	0	0	0.02	0.02	0.01
2	0	0	0	0	0	0	0	0	0	0.02	0.02	0.01
3	0	0	0	0	0	0	0	0	0	0.02	0.02	0.01
4	0	0	0.03	0	0	0	0	0	0	0.02	0.01	0.01
5	0	0.34	0.02	0.23	0	0	0	0	0	0.02	0.02	0.01
6	0	0.03	0.00	0.04	0	0	0	0	0	0.02	0.02	0.01
7	0	0	0.02	0.11	0	0	0	0	0	0.02	0.02	0.02
8	0	0	0.03	0.13	0	0	0	0	0	0.02	0.02	0.02
9	0	0	0.04	0.07	0	0	0	0.03	0	0.01	0.02	0.01
10	0	0	0.02	0.03	0	0	0	0	0	0.02	0.02	0
11	0	0	0	0	0	0	0	0	0	0.02	0.02	0.01
12	0	0	0	0	0	0	0	0	0	0.01	0.02	0.00
13	0	0	0	0	0.025	0	0	0	0	0.01	0.02	0.01
14	0	0	0	0	0	0	0	0	0	0.01	0.02	0
15	0	0	0	0	0	0	0	0	0	0.01	0.02	0
16	0	0	0	0	0	0	0	0	0	0.01	0.02	0
17	0	0	0	0	0	0	0	0	0	0.01	0.02	0.01
18	0	0	0.03	0	0	0	0	0	0	0.01	0.02	0.01
19	0	0	0.06	0	0	0	0	0	0	0.01	0.02	0.01
20	0	0	0.06	0	0	0	0	0	0	0.01	0.01	0.01
21	0	0.05	0.04	0	0	0	0	0	0	0.01	0.02	0.01
22	0	0	0.01	0.01	0	0	0	0	0	0.01	0.01	0.01
23	0	0	0	0	0	0	0	0	0	0.01	0.01	0.01
24	0	0	0	0	0	0	0	0	0	0.01	0.01	0.01
25	0	0	0	0.02	0.01	0	0	0	0	0.02	0.01	0
26	0	0	0.03	0.05	0	0	0	0	0	0.02	0.01	0
27	0	0	0.06	0.08	0	0	0	0	0	0.02	0.01	0.04
28	0	0	0.03	0.08	0	0	0	0	0.02	0.02	0.01	0.00
29	0	0	0.03	0.08		0	0.17	0	0.02	0.02	0.01	0.07
30	0	0	0.04	0.07		0	0	0	0.02	0.02	0.01	0
31	0		0.04	0.05		0		0		0.02	0.01	

E265 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	0.08	0.64	1.1	0.03	0.03	0.09	0.01	0.10	0.75	0.68	0.27	3.8
Max Daily Mean (ft³/s)	0	0.34	0.06	0.23	0.03	0.03	0.17	0.03	0.02	0.02	0.02	0.07	0.34
Min Daily Mean (ft³/s)	0	0	0	0	0	0	0	0	0	0.01	0.01	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E267 Potrillo Canyon above SR 4

Location. Lat 35° 48' 48", long -106° 14' 00", Sec. 6, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 2.26 mi².

Period of Record. October 1, 1995, to September 30, 2017.

Revised Record. LA-13551-PR (1998): Station number. Drainage area (2006).

Gage. Data logger with radio telemetry and concrete control. Elevation of gage is 6455 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 1 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 99 ft³/s, September 13, 2013, gage height 2.94 ft.

Maximum Discharge for Current Water Year. No measureable discharge for the water year.



E267 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter on an 18-in. CMP well. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3-x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for direct discharge measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside staff gage gave a complete and satisfactory record for the year.

Rating. The channel is fairly straight for 300 ft above the gage and 150 ft below. The streambed is mostly sand. The brush is thick along the stream bank. The control is a concrete broad-crested weir.

Rating No. 2 is considered good.

The original shape and definition of the rating was derived by computation using weir geometry with the slope area used to define peak discharge and slope of the upper end.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 2.

E267 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E267 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

Ancho/Chaquehui Watershed

Ancho Canyon is located in the southeastern portion of LANL and originates on LANL property in TA-49 at an elevation of approximately 7285 ft. The watershed extends southeast across LANL and enters the Rio Grande along the boundary between TA-33 and TA-70 at an elevation of approximately 5410 ft. Ancho Canyon is joined by North Ancho Canyon before it flows into the Rio Grande. The area of Ancho watershed is approximately 6.8 mi², and it has a channel length of 7.3 mi. Stream flow in Ancho Canyon is ephemeral over most of the canyon length, until about 0.8 mi upstream of the confluence with the Rio Grande, where Ancho Spring is located. This perennial spring supports perennial flow for a very short segment of the canyon where it converges with the Rio Grande.

Chaquehui Canyon originates in Bandelier National Monument at an elevation of 6580 ft. The watershed begins at the northeast corner of the monument, extending 0.4 mi before entering LANL property at the northwestern corner of TA-33 and trends southeast. The watershed continues across 2 mi of TA-33 and enters the Rio Grande at an elevation of 5370 ft. The area of the Chaquehui watershed is approximately 1.6 mi². Stream flow in Chaquehui Canyon is ephemeral.

Figure 8 shows the total monthly volume of discharge for the three stream gage discharge stations within the Ancho Canyon and Chaquehui Canyon watersheds.




Figure 8 Total monthly volume (acre-ft) for WY 2017 in Ancho Canyon and Chaquehui Canyon

E275 Ancho Canyon below SR 4

Location. Lat 35° 46' 54", long -106° 14' 42", Sec. 19, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 4.75 mi².

Period of Record. December 1993 to September 30, 2017.

Revised Record. Drainage area (2006).

Gage. Data logger with radio telemetry and concrete stabilized natural control. Elevation of gage is 6193 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 6 yr, 39 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge, 536 ft³/s, August 4, 2008, estimated from high-water-mark survey.

Maximum Discharge for Current Water Year. Maximum discharge, 252 ft³/s, June 25, 2017, gage height 2.15 ft.



E275 Stream gage upstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a shaft encoder float system. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with an ISCO pump sampler to collect water-quality samples. The ISCO sampler is housed in a separate shelter, a 3- x 4-ft metal box. The sampler is triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the outside gage gave a complete and satisfactory record for the year, except for November 4, 2016, when maintenance was performed.

Rating. The streambed is a series of outcrops and sand pockets with moderate sand movement during flow events. The high-water channel is straight for 200 ft upstream. Flow below the gage becomes supercritical as the fall increases radically below the station. A channel a quarter-mile upstream has very low banks and may spread out to large widths. The channel contracts markedly from there to the gage. The control is a natural rock outcrop stabilized by concrete.

Rating No. 1 was developed from the PZF and previous measurement and slope area.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 1.

E275 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	T*	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	252	0	0	0
26	0	0	0	0	0	0	0	0	0.28	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	15
29	0	0	0	0		0	0	0	0	0	0	74
30	0	0	0	0		0	0	0	0	0	0	0.40
31	0		0	0		0		0		0	0	

*T = Testing or maintenance performed.

E275 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	0	0	0	0	0	0	0	11	0	0	6	17
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	252	0	0	74	252
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	1	0	0	0	0	0	0	0	0	0	0	1

E338 Chaquehui at TA-33

Location. Lat 35° 46' 11", long -106° 15' 7", Sec. 19, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 12.18 mi².

Period of Record. October 1, 1999, to January 8, 2001; October 4, 2001, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6227 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 5 yr, 9 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge 239 ft³/s, September 13, 2013, gage height 2.98 ft.

Maximum Discharge for Current Water Year. Maximum discharge 3.0 ft³/s, April 29, 2017, gage height 0.69 ft.



E338 Stream gage downstream view

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval) and a Milltronics sonic probe. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with two ISCO samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples. The ISCO samplers are housed in a separate 3- × 4-ft metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage. All high-flow measurements will be by slope-area or critical-depth computation methods.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the inside staff gage gave a complete and satisfactory record for the entire year.

Rating. The channel makes a 30-degree turn approximately 25 ft upgrade from the staff plate and then runs straight downgrade for 80 ft. The channel is confined by steep cutbanks on both sides that should remain stable with flows confined within the channel. The channel bottom is approximately 4 ft wide and made up of fine sand and pumice cobble. The control is the open channel.

Rating No. 1 was developed from previous measurement and slope area.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 1.

E338 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0.91	0	0	0	0	0	0	0	0
7	0	0	0	1.0	0	0	0	0	0	0	0	0
8	0	0	0	1.3	0	0	0	0	0	0	0	0
9	0	0	0	0.27	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0.55	0	0	0	0	0	0	0
13	0	0	0	0	2.3	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	1.4	0	0	0	0	0	0	0	0
22	0	0	0.82	0	0	0	0	0	0	0	0	0
23	0	0	0.82	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0.36	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	3.0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E338 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	0	0.68	1.9	0.95	0	0.40	0	0	0	0	0	4.0
Max Daily Peak (ft³/s)	0	0	0.82	1.4	2.3	0	3.0	0	0	0	0	0	3.0
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

E340 Chaquehui Tributary at TA-33

Location. Lat 35° 46' 46", long -106° 15' 1", Sec. 19, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Drainage Area. 1.33 mi².

Period of Record. February 7, 2001, to October 14, 2003; May 14, 2004, to September 30, 2017.

Revised Record. None.

Gage. Data logger with radio telemetry. Elevation of gage is 6423 ft using LANL LIDAR DEM with NAD 83.

Average Volume. 5 yr, 2 acre-ft/yr.

Maximum Discharge for Period of Record. Maximum discharge 38 ft³/s, September 14, 2013, gage height 1.2 ft.

Maximum Discharge for Current Water Year. No discharge for the year.



E340 Stream gage, downstream to the right

Equipment. The station is equipped with a Sutron 9210 data logger (5-min interval), an MDS 4710 radio transceiver, and a Sutron Accubar bubbler sensor. The system is powered by a solar-panel battery system housed in a NEMA shelter. The station is equipped with two ISCO samplers (one 12-count 1-L glass and polyethylene bottle sampler and one 24-count 1-L polyethylene bottle sampler) to collect water-quality samples. The ISCO samplers are housed in a separate 3- × 4-ft metal box. The samplers are triggered by stage through the data logger. An outside staff gage is available for reference. No provision has been made for measurements above the wading stage. All high-flow measurements will be by slope-area or critical-depth computation methods.

Datum Correction. None.

Gage-Height Record. The data logger referenced to the inside staff gage gave a complete and satisfactory record for the year.

Rating. The channel zigzags downslope while dropping off low bedrock shelves into sandy bottoms both above and below the gage station. The channel maintains approximately a 3-ft width while being contained by soil banks that may erode with heavy flows but otherwise remain stable with low flows. The control is a bedrock open channel and is very stable at the staff plate.

Rating No. 1 was developed from previous measurement and slope area.

No discharge measurements were made during the year.

Discharge. Discharge was computed by directly applying the gage height to Rating No. 1.

E340 Daily Peak Discharge (ft³/s)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0
21	0	0	0	0	0	0	0	0	0	0	0	0
22	0	0	0	0	0	0	0	0	0	0	0	0
23	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0
25	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0
27	0	0	0	0	0	0	0	0	0	0	0	0
28	0	0	0	0	0	0	0	0	0	0	0	0
29	0	0	0	0		0	0	0	0	0	0	0
30	0	0	0	0		0	0	0	0	0	0	0
31	0		0	0		0		0		0	0	

E340 Monthly Summary Table

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	WY
Total (acre-ft)	0	0	0	0	0	0	0	0	0	0	0	0	0
Max Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Min Daily Peak (ft³/s)	0	0	0	0	0	0	0	0	0	0	0	0	0
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0	0

PRECIPITATION GAGE STATIONS

Data Collection and Computation

A complete record at a precipitation gage station consists of precipitation measurements directly observed using a tipping bucket. There were 5-min records of precipitation provided from a data logger, validated, and archived. The total daily precipitation is a sum of the 5-min precipitation records for the calendar day.

Accuracy of Records

The number of significant figures used to report daily precipitation is based solely on measured precipitation to the nearest hundredth.

Factors that affect the accuracy of the precipitation record include the following:

- Debris in the tipping bucket
- Precipitation in the form of hail or snow

Data Presentation

The records published in this report consist of two parts for each precipitation gage station:

- Station analysis summary with photo when available
- Data table for the water year (October 1, 2016, to September 30, 2017)

The station analysis supplements each daily values table and includes a description of gage location, the period of record, gage information, a description of monitoring equipment, fieldwork visits, the maximum daily total precipitation for the period of record and the current monsoon season, and a description of the precipitation record.

Location: The most accurate and available maps, coupled with LIDAR DEM using NAD 83, provide location information.

Period of Record: The period of record is the time during which published records exist for a station or its equivalent station. An equivalent station is one that was in operation when the present station was not in operation and was located so its records can be reasonably considered equivalent to records from the present station.

Gage: This section describes the datum of the current gage referred to in NAD 83.

Equipment: This section describes the equipment located at each site.

Fieldwork: Totals are presented for rain gage inspections and rain gage maintenance performed by field crews during the water year.

Maximum Daily Total Precipitation for Period of Record: The record includes the maximum daily precipitation. Unless otherwise qualified, the maximum precipitation is the total daily maximum.

Maximum Daily Total Precipitation for Current Monsoon Season: Maximums given are similar to those for the period of record. The time for daily totals is expressed in 24-hr local standard time.

Precipitation Record: The precipitation record includes the periods when the gage station was shut down for winterization and when the record was incomplete because of problems with data collection.

The monthly total precipitation table records the total monthly precipitation from October 2016 to September 2017. The row titled "Total (in.)" contains the sum of the daily precipitation for each month in inches, the row titled "Mean Total for Period of Record (in.)" contains the mean total for each month in inches, the row titled "Max Daily Total (in.)" contains the maximum daily total precipitation for each month in inches, and the row titled "Missing Days" contains the number of days missing for each month.

The table below shows the total precipitation for May 1 to September 30, 2017. Most of the annual precipitation occurs during the monsoon season. The column titled "Days with Rain" shows the total number of days precipitation occurred during this period for each rain gage. The column titled "Total Precipitation" contains the sum of the daily precipitation for this period for each precipitation gage.

Precipitation Summary for Monsoon Season, May 1, 2017–September 30, 2017

Rain Gage	Days with Rain	Total Precipitation (in.)	Maximum Daily Total Precipitation (in.)	Elevation (ft)
E038	62	8.78	1.37	7087
E042.1	55	7.62	1.19	6379
R055.5	66	10.78	1.47	7102
E121.9	63	11.2	1.52	7336
E200.5	52	9.41	1.26	7214
E203	57	10.51	1.36	6817
E240	60	12.01	1.71	7719
E245.5	56	9.59	1.23	6796
E253	67	11.78	1.69	7719
E257	63	11.90	1.49	7360
E262.4	57	9.68	1.25	7124
E265	56	7.36	1.23	6311
E267.4	59	8.95	1.23	6865
E340	58	7.94	1.16	6423
TA-06	57	10.80	1.59	7423
TA-49	44	10.52	1.42	7045
TA-53	45	8.93	1.41	6992
TA-54	46	6.75	1.19	6553
North Community	53	9.82	1.54	7414


Extended Precipitation Network

Measurement, collection, and management of precipitation data and calculated results are required by LANL's National Pollutant Discharge Elimination System (NPDES) Multi-Sector General Permit (NMR05GB21), the Construction General Permit, and the NPDES Individual Permit for Storm Water Discharge from Solid Waste Management Units and Areas of Concern (NM0030759), issued to LANL by the U.S. Environmental Protection Agency (EPA). The precipitation data are also used by Consent Order and environmental surveillance storm water projects to guide field activities such as monitoring station

inspections and sample retrieval. The use of the extended rain gage network allows the storm water projects to optimize field team response to only those areas where precipitation likely resulted in runoff or exceeded a pre-established trigger amount.

The extended precipitation network consists of 14 precipitation gage stations. The gages collect 5-min precipitation data in tipping buckets. The network is active from April to November when precipitation as rain is most likely to occur on the Pajarito Plateau. Each precipitation gage station is named after its collocated or formerly collocated stream gage station per the USGS Water Resources Division's naming convention previously described in the stream discharge gage station section of this report.

Figure 9 shows the total monthly precipitation for the 14 extended network gages from October 2016 to September 2017, with December 2016 to March 2017 omitted because the gages were shut down for winter.



Note: The gages are listed in ascending order, from lowest elevation (E265 at 6311 ft) to highest elevation (E240 at 7719 ft).

Figure 9 Total monthly precipitation for the extended precipitation network gages for WY 2017, excluding December 2016 to March 2017, when the gages were shut down for winter

E038 DP Canyon above TA-21

Location. Lat 35° 52' 49", long -106° 16' 58", SW ¼, Sec. 14, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. April 23, 2008, to September 30, 2017.

Gage. Elevation of gage is 7087 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.08 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.37 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 12, 2017, when the gage was shut down for winter.



E038 Precipitation gage

E038 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.17	0	0.12	0	0	0.05
2	0.10	0	IA	IA	IA	IA	0.09	0	0	0	0	0
3	0.01	0	IA	IA	IA	IA	0	0	0	0	0.07	0
4	0	0.53	IA	IA	IA	IA	0.14	0	0	0	0.01	0
5	0	0.61	IA	IA	IA	IA	0	0	0.04	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.27	0	0.04	0
7	0	0	IA	IA	IA	IA	0	0	0.26	0.06	0.45	0
8	0.12	0	IA	IA	IA	IA	0	0	0	0.35	0.02	0.01
9	0.03	0	IA	IA	IA	IA	0	0.26	0	0.03	0	0
10	0.01	0	IA	IA	IA	IA	0	0.16	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0.01	0	0.01	0.4	0
12	0	0	IA	IA	IA	IA	0	0	0	0.06	0	0.09
13	0	0	IA	IA	IA	0	0	0	0	0.04	0	0
14	0	0	IA	IA	IA	0	0	0	0	0.01	0.06	0.01
15	0	0	IA	IA	IA	0	0	0	0	0	0	0
16	0	0	IA	IA	IA	0	0	0	0	0	0.01	0
17	0	0	IA	IA	IA	0	0	0	0	0	0	0.01
18	0	0	IA	IA	IA	0	0	0	0	0.04	0	0
19	0.02	0	IA	IA	IA	0	0	0.2	0	0	0.02	0.02
20	0	0.03	IA	IA	IA	0	0	0	0.01	0	0.25	0
21	0	0.34	IA	IA	IA	0	0	0	0	0	0.03	0
22	0	0	IA	IA	IA	0	0	0	0.1	0	0	0
23	0	0.01	IA	IA	IA	0	0	0	0	0	0.07	0.21
24	0	0	IA	IA	IA	0.06	0	0	0	0	0.09	0.01
25	0	0	IA	IA	IA	0	0.03	0.01	0.21	0.07	0.01	0.01
26	0	0.12	IA	IA	IA	0	0	0	0.05	0.5	0.06	0.35
27	0	0.02	IA	IA	IA	0.02	0	0	0	0.45	0.01	1.37
28	0	0	IA	IA	IA	0	0.27	0	0	0.1	0.01	0.78
29	0	0.02	IA	IA		0.26	0.33	0.04	0	0.17	0.1	0.16
30	0	0	IA	IA		0	0.01	0	0	0.01	0	0.24
31	0		IA	IA		0.01		0.02		0.09	0	

* IA = Inactive gage during seasonal shutdown.

E038 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.29	1.68	IA ^a	IA	IA	0.35 ^b	1.04	0.70	1.06	1.99	1.71	3.32
Mean Monthly Total for Period of Record (in.)	1.15	0.45	IA	IA	IA	IA	0.77	0.75	0.62	2.24	2.36	1.58
Max Daily Total (in.)	0.12	0.61	IA	IA	IA	0.26	0.33	0.26	0.27	0.50	0.45	1.37
Missing Days	0	0	31	31	28	12	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity.

E042.1 Los Alamos above Low Head Weir

Location. Lat 35° 52' 2", long -106° 13' 25", NW ¼, Sec. 20, T. 19 N., R. 7 E., Santa Fe County.

Period of Record. July 27, 2010, to September 30, 2017.

Gage. Elevation of gage is 6377 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.27 in. on September 12, 2013, estimated.

Maximum Daily Total Precipitation for Monsoon Season. 1.19 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 23, 2017, when the gage was shut down for winter.



E042.1 Precipitation gage

E042.1 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.28	0	0.2	0	0	0.06
2	0.05	0.02	IA	IA	IA	IA	0	0	0	0	0	0
3	0.01	0	IA	IA	IA	IA	0.06	0	0	0	0.04	0
4	0	0.36	IA	IA	IA	IA	0.06	0	0.07	0	0.01	0
5	0	0.7	IA	IA	IA	IA	0.01	0	0.02	0	0	0
6	0	0.01	IA	IA	IA	IA	0	0	0.13	0	0.01	0.02
7	0	0.01	IA	IA	IA	IA	0	0	0.05	0.01	0.27	0
8	0.08	0	IA	IA	IA	IA	0	0	0	0.1	0.02	0
9	0.15	0	IA	IA	IA	IA	0	0.39	0	0.15	0.25	0
10	0	0	IA	IA	IA	IA	0	0.16	0	0.08	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.03	0.32	0
12	0	0	IA	IA	IA	IA	0	0	0	0.05	0	0.17
13	0	0	IA	IA	IA	IA	0	0	0	0.02	0	0
14	0	0	IA	IA	IA	IA	0	0	0	0.01	0.15	0
15	0	0	IA	IA	IA	IA	0	0	0	0	0	0
16	0	0	IA	IA	IA	IA	0	0	0	0	0	0
17	0	0	IA	IA	IA	IA	0	0.01	0	0.01	0	0.05
18	0	0	IA	IA	IA	IA	0	0	0	0	0	0
19	0	0	IA	IA	IA	IA	0	0.22	0	0	0	0
20	0	0.02	IA	IA	IA	IA	0	0	0	0	0.14	0
21	0	0.41	IA	IA	IA	IA	0	0	0	0	0.01	0
22	0	0	IA	IA	IA	IA	0	0	0.03	0	0.04	0
23	0	0.01	IA	IA	IA	IA	0	0.02	0	0	0	0.39
24	0	0.01	IA	IA	IA	0	0	0	0	0.04	0.04	0
25	0	0	IA	IA	IA	0	0.04	0	0.08	0.06	0	0
26	0	0.08	IA	IA	IA	0	0	0	0.03	0.34	0.02	0.29
27	0	0.01	IA	IA	IA	0.04	0	0	0	0.34	0	1.19
28	0	0	IA	IA	IA	0	0.26	0	0	0.02	0	1.03
29	0	0.07	IA	IA		0.01	0.42	0.08	0	0.1	0	0.06
30	0	0	IA	IA		0	0.01	0	0	0.01	0	0.15
31	0		IA	IA		0.07		0.01		0.02	0	

* IA = Inactive gage during seasonal shutdown.

E042.1 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.29	1.71	IA ^a	IA	IA	0.12 ^b	1.14	0.89	0.61	1.39	1.32	3.41
Mean Monthly Total for Period of Record (in.)	1.06	0.62	IA	IA	IA	IA	0.75	0.90	0.52	2.05	2.15	1.98
Max Daily Total (in.)	0.15	0.70	IA	IA	IA	0.07	0.42	0.39	0.20	0.34	0.32	1.19
Missing Days	0	0	31	31	28	23	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

R055.5 South Fork of Acid Canyon

Location. Lat 35° 53' 10", long -106° 18' 26", SE ¼, Sec. 9, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. July 29, 2008, to September 30, 2017.

Gage. Elevation of gage is 7102 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.26 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.47 in. on September, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 30, 2016, to March 23, 2017, when the gage was shut down for winter.



R055.5 Precipitation gage

R055.5 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.21	0	0.18	0	0.01	0.14
2	0.14	0	IA	IA	IA	IA	0.27	0	0	0	0	0
3	0	0	IA	IA	IA	IA	0.03	0	0	0	0.05	0
4	0	0.73	IA	IA	IA	IA	0.2	0	0	0	0.07	0
5	0	0.63	IA	IA	IA	IA	0	0	0.02	0	0.01	0
6	0	0	IA	IA	IA	IA	0	0	0.13	0	0.08	0
7	0	0.01	IA	IA	IA	IA	0	0	0.06	0.03	0.37	0
8	0.13	0	IA	IA	IA	IA	0	0.01	0.02	0.52	0	0.01
9	0.01	0	IA	IA	IA	IA	0	0.35	0	0	0.01	0
10	0	0	IA	IA	IA	IA	0	0.16	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0	0.52	0
12	0	0	IA	IA	IA	IA	0	0	0	0.06	0.01	0.12
13	0	0	IA	IA	IA	IA	0	0	0	0.06	0	0
14	0	0	IA	IA	IA	IA	0	0	0	0.01	0.07	0.05
15	0	0	IA	IA	IA	IA	0	0	0.01	0	0	0
16	0	0	IA	IA	IA	IA	0	0	0	0	0	0
17	0	0	IA	IA	IA	IA	0	0.01	0	0	0	0.02
18	0	0	IA	IA	IA	IA	0	0	0	0.16	0.01	0.01
19	0	0	IA	IA	IA	IA	0	0.18	0	0	0.1	0
20	0	0.02	IA	IA	IA	IA	0	0	0	0	0.3	0
21	0	0.43	IA	IA	IA	IA	0	0	0	0	0.02	0
22	0	0	IA	IA	IA	IA	0	0	0.08	0	0.02	0
23	0	0	IA	IA	IA	IA	0	0	0	0	0.39	0.19
24	0	0	IA	IA	IA	0.11	0	0	0	0.06	0.07	0
25	0	0	IA	IA	IA	0.02	0.08	0	0.24	0.06	0.01	0.01
26	0	0.15	IA	IA	IA	0	0	0	0.26	0.6	0.04	0.62
27	0	0.01	IA	IA	IA	0.02	0.01	0	0	0.17	0	1.47
28	0	0	IA	IA	IA	0	0.34	0	0	0.13	0	1.13
29	0	0	IA	IA		0.32	0.24	0.1	0	0.41	0.08	0.1
30	0	IA	IA	IA		0	0.01	0.03	0.01	0.02	0	0.43
31	0		IA	IA		0.01		0.01		0.08	0.01	

* IA = Inactive gage during seasonal shutdown.

R055.5 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.28	1.98	IA*	IA	IA	0.48	1.39	0.85	1.01	2.37	2.25	4.30
Mean Total for Period of Record (in.)	1.43	0.54	IA	IA	IA	IA	0.77	1.04	1.02	3.41	2.11	2.11
Max Daily Total (in.)	0.14	0.73	IA	IA	IA	0.32	0.34	0.35	0.26	0.60	0.52	1.47
Missing Days	0	1	31	31	28	23	0	0	0	0	0	0

* IA = Inactive gage during seasonal shutdown.

E121.9 Sandia Canyon East of Power Plant

Location. Lat 35° 52' 30", long -106° 19' 10", SW ¼, Sec. 16, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. May 2, 2007, to September 30, 2017.

Gage. Elevation of gage is 7336 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.35 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.52 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 30, 2016, to March 22, 2017, when the gage was shut down for winter.



E121.9 Precipitation gage

E121.9 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.18	0	0.18	0	0	0.29
2	0.1	0	IA	IA	IA	IA	0.32	0	0.03	0	0	0
3	0	0	IA	IA	IA	IA	0.05	0	0	0	0.03	0
4	0	0.71	IA	IA	IA	IA	0.2	0	0	0	0.02	0
5	0	0.7	IA	IA	IA	IA	0	0	0.02	0	0.01	0
6	0	0	IA	IA	IA	IA	0	0	0.21	0.02	0.06	0
7	0	0	IA	IA	IA	IA	0	0	0.01	0.01	0.26	0
8	0.14	0	IA	IA	IA	IA	0	0.02	0	0.17	0.01	0
9	0.04	0	IA	IA	IA	IA	0	0.42	0	0	0	0
10	0	0	IA	IA	IA	IA	0	0.12	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0	0.48	0
12	0	0	IA	IA	IA	IA	0	0	0.01	0.15	0	0.09
13	0	0	IA	IA	IA	IA	0	0	0	0.04	0	0
14	0	0	IA	IA	IA	IA	0	0	0	0	0.09	0.06
15	0	0	IA	IA	IA	IA	0	0	0	0.01	0	0
16	0	0	IA	IA	IA	IA	0	0	0	0.01	0	0
17	0	0	IA	IA	IA	IA	0	0.01	0	0	0	0.01
18	0	0	IA	IA	IA	IA	0	0	0	0.29	0	0
19	0.02	0	IA	IA	IA	IA	0	0.17	0	0	0.03	0
20	0	0.02	IA	IA	IA	IA	0	0	0.03	0	0.31	0
21	0	0.44	IA	IA	IA	IA	0	0	0	0.01	0.01	0
22	0	0	IA	IA	IA	IA	0	0.02	0.02	0	0	0
23	0	0	IA	IA	IA	0.07	0	0	0.01	0	0.22	0.18
24	0	0	IA	IA	IA	0.04	0	0	0	0.06	0.04	0
25	0	0	IA	IA	IA	0	0.09	0	0.44	0.05	0	0
26	0	0.14	IA	IA	IA	0.01	0	0	0.5	0.99	0.07	0.67
27	0	0.01	IA	IA	IA	0	0.01	0	0.01	0.21	0	1.52
28	0	0	IA	IA	IA	0.27	0.3	0	0	0.03	0.01	1.20
29	0	0.02	IA	IA		0	0.18	0.1	0	0.47	0.02	0.12
30	0	IA	IA	IA		0.02	0	0.03	0	0.01	0	0.38
31	0		IA	IA		0.18		0		0.12	0	

* IA = Inactive gage during seasonal shutdown.

E121.9 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.30	2.04	IA ^a	IA	IA	0.59 ^b	1.33	0.89	1.47	2.65	1.67	4.52
Mean Total for Period of Record (in.)	1.35	0.52	IA	IA	IA	IA	0.91	1.11	1.00	3.19	2.77	2.38
Max Daily Total (in.)	0.14	0.71	IA	IA	IA	0.27	0.32	0.42	0.50	0.99	0.48	1.52
Missing Days	0	1	31	31	28	22	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E200.5 Mortandad Canyon Tributary Batch Plant at Sigma

Location. Lat 35° 51' 57", long -106° 17' 24", NE ¼, Sec. 22, T.19 N., R. 6 E., Los Alamos County.

Period of Record. July 25, 2007, to September 30, 2017.

Gage. Elevation of gage is 7214 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.53 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.26 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 29, 2016, to March 13, 2017, when the gage was shut down for winter.



E200.5 Precipitation gage

E200.5 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.14	0	0.13	0	0	0.07
2	0.07	0	IA	IA	IA	IA	0.16	0	0	0	0	0
3	0.01	0	IA	IA	IA	IA	0.03	0	0	0	0.05	0
4	0	0.67	IA	IA	IA	IA	0.11	0	0	0	0.01	0
5	0	0.61	IA	IA	IA	IA	0	0	0.01	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.35	0	0.16	0
7	0	0	IA	IA	IA	IA	0	0	0.15	0.04	0.32	0
8	0.15	0	IA	IA	IA	IA	0	0	0	0.3	0	0
9	0.07	0	IA	IA	IA	IA	0	0.32	0	0	0	0
10	0	0	IA	IA	IA	IA	0	0.15	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.01	0.42	0
12	0	0	IA	IA	IA	IA	0.01	0	0	0.12	0	0.23
13	0	0	IA	IA	IA	IA	0	0	0	0.02	0	0
14	0	0	IA	IA	IA	0	0	0	0	0	0.12	0.05
15	0	0	IA	IA	IA	0	0	0	0	0	0	0
16	0	0	IA	IA	IA	0	0	0	0	0	0	0
17	0	0	IA	IA	IA	0	0	0	0	0	0	0.02
18	0	0	IA	IA	IA	0	0	0	0	0.1	0	0
19	0	0	IA	IA	IA	0	0	0.18	0	0	0.01	0
20	0	0.02	IA	IA	IA	0	0	0	0.02	0	0.25	0.01
21	0	0.39	IA	IA	IA	0	0	0	0	0	0.03	0
22	0	0	IA	IA	IA	0	0	0	0.06	0	0.01	0
23	0	0	IA	IA	IA	0.01	0	0	0	0	0.11	0.17
24	0	0	IA	IA	IA	0.02	0	0	0	0	0.07	0
25	0	0	IA	IA	IA	0	0.06	0	0.18	0.05	0	0
26	0	0.1	IA	IA	IA	0	0	0	0.07	1.1	0.06	0.47
27	0	0	IA	IA	IA	0.02	0	0	0.01	0.25	0	1.26
28	0	0	IA	IA	IA	0	0.2	0	0	0.17	0.01	0.73
29	0	IA	IA	IA		1.08	0.02	0.05	0	0.35	0.15	0.11
30	0	IA	IA	IA		0	0.1	0	0	0	0	0.19
31	0		IA	IA		0		0.01		0.12	0	

* IA = Inactive gage during seasonal shutdown.

E200.5 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.30	1.79	IA ^a	IA	IA	1.13 ^b	0.83	0.71	0.98	2.63	1.78	3.31
Mean Total for Period of Record (in.)	1.04	0.56	IA	IA	IA	IA	0.60	0.80	0.55	2.81	2.31	2.07
Max Daily total (in.)	0.15	0.67	IA	IA	IA	1.08	0.20	0.32	0.35	1.10	0.42	1.26
Missing Days	0	2	31	31	28	13	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E203 Mortandad Canyon below Sediment Traps

Location. Lat 35° 51' 39", long -106° 16' 6", SE ¼, Sec. 23, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. May 1, 2007, to September 30, 2017.

Gage. Elevation of gage is 6817 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.34 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.36 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 29, 2016, to March 13, 2017, when the gage was shut down for winter.



E203 Precipitation gage

E203 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0.02	0	IA*	IA	IA	IA	0.23	0	0.17	0	0	0.12
2	0.08	0	IA	IA	IA	IA	0.06	0	0	0	0	0
3	0	0	IA	IA	IA	IA	0.03	0	0	0	0.06	0
4	0	0.57	IA	IA	IA	IA	0.11	0	0.01	0	0	0
5	0	0.64	IA	IA	IA	IA	0.01	0	0.01	0.02	0	0
6	0	0.01	IA	IA	IA	IA	0	0	0.27	0	0.09	0
7	0	0	IA	IA	IA	IA	0	0	0.26	0.01	0.43	0
8	0.11	0	IA	IA	IA	IA	0	0	0	0.13	0.02	0
9	0.12	0	IA	IA	IA	IA	0	0.37	0	0.1	0	0
10	0.01	0.01	IA	IA	IA	IA	0	0.19	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.05	0.41	0
12	0	0	IA	IA	IA	IA	0	0	0	0.07	0	0.18
13	0	0	IA	IA	IA	IA	0	0	0.01	0.02	0	0
14	0	0	IA	IA	IA	0	0	0	0	0	0.25	0.03
15	0	0	IA	IA	IA	0	0	0	0	0.01	0	0
16	0	0	IA	IA	IA	0	0	0	0	0	0	0
17	0	0	IA	IA	IA	0	0	0.01	0	0	0	0.01
18	0	0	IA	IA	IA	0	0	0	0	0.02	0	0
19	0	0	IA	IA	IA	0	0	0.2	0	0	0	0.02
20	0	0.02	IA	IA	IA	0	0	0	0.01	0	0.27	0
21	0	0.44	IA	IA	IA	0	0	0	0	0	0.05	0
22	0	0.01	IA	IA	IA	0	0	0	0.07	0	0	0
23	0	0	IA	IA	IA	0.03	0	0	0	0	0.05	0.18
24	0	0	IA	IA	IA	0.02	0	0	0	0.03	0.15	0.01
25	0	0	IA	IA	IA	0	0.05	0	0.2	0.02	0	0
26	0	0.11	IA	IA	IA	0	0	0	0.04	1.09	0.03	0.45
27	0	0.01	IA	IA	IA	0.04	0	0	0	1.03	0	1.36
28	0	0	IA	IA	IA	0	0.26	0	0	0.05	0.08	0.92
29	0	IA	IA	IA		0.23	0.31	0.04	0	0.35	0.17	0.05
30	0	IA	IA	IA		0.01	0.03	0	0	0.01	0	0.16
31	0		IA	IA		0.02		0		0.09	0	

* IA = Inactive gage during seasonal shutdown.

E203 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.34	1.82	IA*	IA	IA	0.35	1.09	0.81	1.05	3.10	2.06	3.49
Mean Total for Period of Record (in.)	1.08	0.73	IA	IA	IA	IA	0.74	1.02	0.64	2.27	1.75	1.63
Max Daily Total (in.)	0.12	0.64	IA	IA	IA	0.23	0.31	0.37	0.27	1.09	0.43	1.36
Missing Days	0	2	31	31	28	13	0	0	0	0	0	0

* IA = Inactive gage during seasonal shutdown.

E240 Pajarito Canyon below SR 501

Location. Lat 35° 52' 02", long -106° 21' 05", NW ¼, Sec. 19, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. June 5, 2002, to September 30, 2017.

Gage. Elevation of gage is 7719 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.20 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.71 in. on September 27, 2017.

Equipment. The station is equipped with a rain gage, Rain Collection II. All equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 30, 2016, to March 8, 2017, when the gage was shut down for winter.



E240 Precipitation gage

E240 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.1	0	0.1	0	0	0.61
2	0.19	0	IA	IA	IA	IA	0.28	0	0.01	0	0	0
3	0	0	IA	IA	IA	IA	0.04	0	0	0	0.03	0
4	0	0.66	IA	IA	IA	IA	0.23	0	0.08	0	0.06	0
5	0	0.6	IA	IA	IA	IA	0.04	0	0.06	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.11	0	0.08	0.02
7	0	0	IA	IA	IA	IA	0	0	0	0	0.02	0.04
8	0.11	0	IA	IA	IA	IA	0	0.06	0	0.02	0	0
9	0.04	0	IA	IA	IA	0	0	0.48	0	0.11	0.01	0
10	0	0	IA	IA	IA	0	0	0.08	0	0	0	0
11	0	0	IA	IA	IA	0	0	0	0	0	0.43	0
12	0	0	IA	IA	IA	0	0	0	0	0.17	0.04	0.11
13	0	0	IA	IA	IA	0	0	0	0	0.05	0	0
14	0	0	IA	IA	IA	0	0	0	0	0	0.09	0.1
15	0	0	IA	IA	IA	0	0	0	0	0.01	0	0
16	0	0	IA	IA	IA	0	0	0	0	0	0	0
17	0	0	IA	IA	IA	0	0	0.02	0	0	0	0
18	0	0	IA	IA	IA	0	0	0	0	0.26	0	0
19	0	0	IA	IA	IA	0	0	0.12	0	0	0.06	0
20	0	0.04	IA	IA	IA	0	0	0	0.02	0	0.23	0
21	0	0.38	IA	IA	IA	0	0	0	0	0	0.01	0
22	0	0.05	IA	IA	IA	0	0	0	0.06	0	0	0.02
23	0	0.01	IA	IA	IA	0.07	0	0	0	0	0.37	0.24
24	0	0	IA	IA	IA	0.08	0	0	0.02	0.04	0.07	0
25	0	0	IA	IA	IA	0.05	0.13	0	0.67	0.11	0	0
26	0	0.17	IA	IA	IA	0	0	0	0.48	0.31	0.02	0.63
27	0	0.02	IA	IA	IA	0.01	0.01	0	0	0.41	0	1.71
28	0	0.01	IA	IA	IA	0	0.33	0.01	0	0.02	0	1.10
29	0	0	IA	IA		0.31	0.16	0.06	0	0.54	0.17	0.14
30	0	IA	IA	IA		0	0.02	0.13	0	0.23	0	0.48
31	0		IA	IA		0		0.03		0.24	0	

* IA = Inactive gage during seasonal shutdown.

E240 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.34	1.94	IA*	IA	IA	IA	1.34	0.99	1.61	2.52	1.69	5.20
Mean Total for Period of Record (in.)	1.21	0.60	IA	IA	IA	IA	0.61	1.18	0.70	2.28	2.06	2.05
Max Daily Total (in.)	0.19	0.66	IA	IA	IA	0.31	0.33	0.48	0.67	0.54	0.43	1.71
Missing Days	0	1	31	31	28	8	0	0	0	0	0	0

* IA = Inactive gage during seasonal shutdown.

E245.5 Pajarito Canyon above Three Mile Canyon

Location. Lat 35° 50' 45.3", long -106° 16' 29", Sec. 16, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Period of Record. May 18, 2007, to September 30, 2017.

Gage. Elevation of gage is 6796 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.06 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.23 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 29, 2016, to March 11, 2017, when the gage was shut down for winter.



E245.5 Precipitation gage

E245.5 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.24	0	0.2	0	0	0.08
2	0.08	0	IA	IA	IA	IA	0.12	0	0	0	0	0
3	0.02	0	IA	IA	IA	IA	0.02	0	0	0	0.13	0
4	0	0.55	IA	IA	IA	IA	0.13	0	0	0	0.01	0
5	0	0.52	IA	IA	IA	IA	0.01	0	0	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.42	0	0.15	0
7	0	0.01	IA	IA	IA	IA	0	0	0.13	0	0.52	0
8	0.13	0	IA	IA	IA	IA	0	0	0	0.04	0.02	0
9	0.08	0	IA	IA	IA	IA	0	0.33	0	0.06	0	0
10	0	0	IA	IA	IA	IA	0	0.1	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.03	0.41	0.01
12	0	0	IA	IA	IA	0	0	0	0	0.07	0	0.3
13	0	0	IA	IA	IA	0	0	0	0	0.04	0.01	0
14	0	0	IA	IA	IA	0	0	0	0	0	0.43	0.06
15	0	0	IA	IA	IA	0	0	0	0	0	0	0.02
16	0	0	IA	IA	IA	0	0	0	0	0	0	0
17	0	0	IA	IA	IA	0	0	0	0	0	0	0.02
18	0	0	IA	IA	IA	0	0	0	0	0.07	0	0
19	0	0	IA	IA	IA	0	0	0.19	0	0	0	0
20	0	0.02	IA	IA	IA	0	0	0	0	0.01	0.29	0
21	0	0.44	IA	IA	IA	0	0	0	0	0	0.03	0
22	0	0	IA	IA	IA	0.05	0	0	0.03	0.02	0	0
23	0	0.01	IA	IA	IA	0	0	0	0.01	0	0.05	0.2
24	0	0	IA	IA	IA	0	0	0	0	0.07	0.03	0
25	0	0	IA	IA	IA	0	0.06	0	0.23	0.01	0	0
26	0	0.08	IA	IA	IA	0.03	0	0	0.06	0.62	0.15	0.39
27	0	0.04	IA	IA	IA	0.01	0	0	0.01	0.42	0	1.23
28	0	0	IA	IA	IA	0.62	0.23	0	0	0.05	0.02	0.93
29	0	IA	IA	IA		0	0.37	0.02	0	0.44	0.12	0.07
30	0	IA	IA	IA		0.02	0.02	0.01	0	0.02	0	0.13
31	0		IA	IA		0.24		0		0.07	0	

* IA = Inactive gage during seasonal shutdown.

E245.5 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.31	1.67	IA ^a	IA	IA	0.97 ^b	1.20	0.65	1.09	2.04	2.37	3.44
Mean Total for Period of Record (in.)	0.99	0.71	IA	IA	IA	IA	0.69	0.86	0.68	2.61	2.00	2.10
Max Daily Total (in.)	0.13	0.55	IA	IA	IA	0.62	0.37	0.33	0.42	0.62	0.52	1.23
Missing Days	0	2	31	31	28	11	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E253 Cañon de Valle above SR 501

Location. Lat 35° 51' 6", long -106° 21' 17", NE ¼, Sec. 25, T. 19 N., R. 5 E., Los Alamos County in Santa Fe National Forest.

Period of Record. October 10, 2007, to September 30, 2017.

Gage. Elevation of gage is 7719 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.59 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.69 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 8, 2017, when the gage was shut down for winter.



E253 Precipitation gage

E253 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.17	0	0.09	0	0	0.25
2	0.15	0	IA	IA	IA	IA	0.29	0	0.02	0	0	0
3	0	0	IA	IA	IA	IA	0.03	0	0	0	0.1	0
4	0	0.63	IA	IA	IA	IA	0.2	0	0.13	0	0.1	0
5	0	0.71	IA	IA	IA	IA	0.01	0	0.02	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.17	0	0.25	0.04
7	0	0	IA	IA	IA	IA	0	0	0	0	0.05	0.03
8	0.1	0	IA	IA	IA	IA	0	0.11	0.01	0.02	0	0
9	0.06	0	IA	IA	IA	0	0	0.52	0	0.05	0	0
10	0	0	IA	IA	IA	0	0	0.05	0	0	0	0
11	0	0	IA	IA	IA	0	0	0.01	0	0.01	0.4	0
12	0	0	IA	IA	IA	0	0	0	0	0.66	0.03	0.1
13	0	0	IA	IA	IA	0	0	0	0	0.02	0	0.01
14	0	0	IA	IA	IA	0	0	0	0	0	0.1	0.06
15	0	0	IA	IA	IA	0	0	0	0	0.02	0.01	0
16	0	0	IA	IA	IA	0	0	0	0	0.01	0	0
17	0	0	IA	IA	IA	0	0	0.01	0	0	0	0
18	0	0	IA	IA	IA	0	0	0	0	0.19	0	0
19	0	0	IA	IA	IA	0	0	0.15	0	0	0.01	0
20	0	0.04	IA	IA	IA	0	0	0	0	0	0.21	0
21	0	0.44	IA	IA	IA	0	0	0	0	0	0.01	0
22	0	0.08	IA	IA	IA	0	0	0	0.02	0	0	0.02
23	0	0	IA	IA	IA	0.09	0	0	0	0	0.37	0.25
24	0	0	IA	IA	IA	0.11	0	0	0.05	0.03	0.05	0.01
25	0	0	IA	IA	IA	0.04	0.14	0.01	1.18	0.03	0.01	0
26	0	0.17	IA	IA	IA	0.01	0	0	0.36	0.08	0.03	0.6
27	0	0.05	IA	IA	IA	0.01	0	0	0.01	0.12	0	1.69
28	0	0.02	IA	IA	IA	0	0.23	0	0	0.02	0	1.28
29	0	0.04	IA	IA		0.34	0.15	0.01	0	0.57	0.08	0.11
30	0	0	IA	IA		0	0.05	0.1	0	0.1	0	0.36
31	0		IA	IA		0		0.03		0.17	0	

*IA = Inactive gage during seasonal shutdown.

E253 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.31	2.18	IA ^a	IA	IA	0.60 ^b	1.27	1.00	2.06	2.10	1.81	4.81
Mean Total for Period of Record (in.)	2.13	0.52	IA	IA	IA	IA	1.02	1.40	1.11	4.62	4.28	2.33
Max Daily Total (in.)	0.15	0.71	IA	IA	IA	0.34	0.29	0.52	1.18	0.66	0.40	1.69
Missing Days	0	0	31	31	28	8	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E257 Cañon de Valle Tributary at TA-16 Burn Grounds

Location. Lat 35° 50' 47", long -106° 19' 50", Sec. 29, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Period of Record. April 27, 2007, to September 30, 2016.

Gage. Elevation of gage is 7360 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.63 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.49 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 12, 2017, when the gage was shut down for winter.



E257 Precipitation gage

E257 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.15	0	0.13	0	0	0.11
2	0.12	0	IA	IA	IA	IA	0.33	0	0.01	0	0	0
3	0	0	IA	IA	IA	IA	0.04	0	0	0	0.14	0
4	0	0.57	IA	IA	IA	IA	0.21	0	0.02	0	0.04	0
5	0	0.72	IA	IA	IA	IA	0	0	0.01	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.7	0	0.46	0.02
7	0	0	IA	IA	IA	IA	0	0	0	0	0.11	0.21
8	0.16	0	IA	IA	IA	IA	0	0.02	0.03	0.04	0.01	0
9	0.02	0	IA	IA	IA	IA	0	0.47	0	0.04	0	0
10	0	0	IA	IA	IA	IA	0	0.13	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.02	0.37	0
12	0	0	IA	IA	IA	IA	0	0	0	0.51	0.02	0.09
13	0	0	IA	IA	IA	0	0	0	0	0.01	0	0
14	0	0	IA	IA	IA	0	0	0	0	0.02	0.13	0.08
15	0	0	IA	IA	IA	0	0	0	0	0	0	0
16	0	0	IA	IA	IA	0	0	0	0.01	0	0	0
17	0	0	IA	IA	IA	0	0	0.01	0	0	0	0.01
18	0	0	IA	IA	IA	0	0	0.01	0	0.35	0	0
19	0	0	IA	IA	IA	0	0	0.18	0	0	0.02	0
20	0	0.03	IA	IA	IA	0	0	0	0	0	0.28	0
21	0	0.52	IA	IA	IA	0	0	0	0	0	0.01	0
22	0	0.02	IA	IA	IA	0	0	0	0.02	0.25	0	0.01
23	0	0	IA	IA	IA	0.03	0	0	0	0	0.2	0.19
24	0	0	IA	IA	IA	0.1	0	0	0.06	0.02	0.05	0
25	0	0	IA	IA	IA	0.03	0.09	0	1.17	0.04	0	0
26	0	0.12	IA	IA	IA	0	0	0	0.3	0.06	0.05	0.6
27	0	0.04	IA	IA	IA	0	0	0	0	0.24	0	1.49
28	0	0.01	IA	IA	IA	0.01	0.27	0	0	0.05	0.03	1.07
29	0	0.03	IA	IA		0.78	0.23	0	0	0.46	0.15	0.14
30	0	0	IA	IA		0	0.01	0.03	0	0.03	0	0.19
31	0		IA	IA		0		0		0.17	0	

* IA = Inactive gage during seasonal shutdown.

E257 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.30	2.06	IA ^a	IA	IA	0.95 ^b	1.33	0.85	2.46	2.31	2.07	4.21
Mean Total for Period of Record (in.)	1.52	0.74	IA	IA	IA	IA	0.96	1.28	0.97	3.40	3.19	2.38
Max Daily Total (in.)	0.16	0.72	IA	IA	IA	0.78	0.33	0.47	1.17	0.51	0.46	1.49
Missing Days	0	0	31	31	28	12	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E262.4 PHERMEX

Location. Lat 35° 49' 57", long -106° 17' 47", Sec. 34, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Los Alamos County.

Period of Record. August 8, 2004, to September 30, 2017.

Gage. Elevation of gage is 7124 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.27 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.25 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 6, 2016, to March 23, 2017, when the gage was shut down for winter.



E262.4 Precipitation gage

E262.4 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0.01	IA*	IA	IA	0.25	0	0.19	0	0	0.07
2	0.11	0	0	IA	IA	IA	0.15	0	0	0	0	0
3	0.02	0	0	IA	IA	IA	0.01	0	0	0	0.11	0
4	0	0.7	0	IA	IA	IA	0.19	0	0	0	0.02	0
5	0	0.52	0	IA	IA	IA	0	0	0	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.55	0	0.22	0.01
7	0	0	IA	IA	IA	IA	0	0	0.09	0.01	0.06	0.08
8	0.17	0	IA	IA	IA	IA	0	0	0	0.06	0.03	0
9	0.07	0	IA	IA	IA	IA	0	0.47	0	0.01	0	0
10	0	0	IA	IA	IA	IA	0	0.11	0	0	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.05	0.49	0
12	0	0	IA	IA	IA	IA	0	0	0	0.22	0	0.16
13	0	0	IA	IA	IA	IA	0	0	0	0.04	0	0
14	0	0.01	IA	IA	IA	IA	0	0	0	0.01	0.07	0.07
15	0	0	IA	IA	IA	IA	0	0	0.01	0	0	0.02
16	0	0	IA	IA	IA	IA	0	0	0	0	0	0
17	0	0	IA	IA	IA	IA	0	0	0	0	0	0.01
18	0	0	IA	IA	IA	IA	0	0.02	0	0.23	0	0
19	0	0	IA	IA	IA	IA	0	0.17	0	0	0.01	0
20	0	0.03	IA	IA	IA	IA	0	0	0	0	0.32	0
21	0	0.5	IA	IA	IA	IA	0	0	0	0	0.03	0
22	0	0	IA	IA	IA	IA	0	0	0.02	0.2	0	0
23	0	0.01	IA	IA	IA	IA	0	0	0	0	0.08	0.25
24	0	0	IA	IA	IA	0.03	0	0	0.05	0.03	0.09	0
25	0	0	IA	IA	IA	0	0.08	0	0.71	0.01	0	0
26	0	0.1	IA	IA	IA	0	0	0	0.15	0.13	0.15	0.6
27	0	0.02	IA	IA	IA	0.01	0	0	0	0.22	0	1.25
28	0	0	IA	IA	IA	0.02	0.28	0	0	0.1	0.03	0.89
29	0	0.01	IA	IA		0.79	0.32	0	0	0.4	0.02	0.06
30	0	0	IA	IA		0	0.01	0	0	0.01	0	0.13
31	0		IA	IA		0.01		0		0.08	0	

* IA = Inactive gage during seasonal shutdown.

E262.4 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.37	1.90	IA*	IA	IA	IA	1.29	0.77	1.77	1.81	1.73	3.60
Mean Total for Period of Record (in.)	1.37	0.60	IA	IA	IA	IA	0.89	1.11	0.85	3.15	2.17	2.24
Max Daily Total (in.)	0.17	0.70	IA	IA	IA	0.79	0.32	0.47	0.71	0.40	0.49	1.25
Missing Days	0	0	26	31	28	23	0	0	0	0	0	0

* IA = Inactive gage during seasonal shutdown.

E265 Water Canyon below SR 4

Location. Lat 35° 48' 18", long -106° 14' 31" Sec. 7, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Period of Record. May 15, 2007, to September 30, 2017.

Gage. Elevation of gage is 6311 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 3.08 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.23 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 8, 2017, when the gage was shut down for winter.



E265 Precipitation gage

E265 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.28	0	0.01	0	0	0.06
2	0.03	0	IA	IA	IA	IA	0.1	0	0	0	0	0
3	0.04	0	IA	IA	IA	IA	0.03	0	0	0	0.07	0
4	0	0.39	IA	IA	IA	IA	0.08	0	0.02	0	0.04	0
5	0	0.67	IA	IA	IA	IA	0	0	0.01	0	0.04	0
6	0	0.01	IA	IA	IA	IA	0	0	0.16	0	0.01	0
7	0	0	IA	IA	IA	IA	0	0	0.11	0	0	0.03
8	0.14	0	IA	IA	IA	IA	0	0	0	0	0.09	0
9	0.05	0	IA	IA	IA	0	0	0.65	0	0.02	0	0
10	0	0	IA	IA	IA	0	0	0.04	0	0.05	0	0
11	0	0	IA	IA	IA	0	0	0	0	0.05	0.17	0
12	0	0	IA	IA	IA	0	0	0.01	0	0.12	0	0.05
13	0	0.01	IA	IA	IA	0	0	0	0	0.06	0	0
14	0	0	IA	IA	IA	0	0	0	0	0	0.11	0.04
15	0	0	IA	IA	IA	0	0	0	0	0	0	0.02
16	0	0	IA	IA	IA	0	0	0	0	0	0	0
17	0	0	IA	IA	IA	0	0	0	0	0	0	0
18	0	0	IA	IA	IA	0	0	0	0	0.1	0	0
19	0	0	IA	IA	IA	0	0	0.16	0	0	0	0
20	0	0.02	IA	IA	IA	0	0	0	0	0	0.2	0.01
21	0	0.46	IA	IA	IA	0	0	0	0.02	0	0.03	0
22	0	0	IA	IA	IA	0.07	0	0	0.02	0	0.01	0
23	0	0.01	IA	IA	IA	0	0	0.05	0	0	0.02	0.25
24	0	0	IA	IA	IA	0	0	0	0	0.08	0.04	0
25	0	0	IA	IA	IA	0	0.06	0	0.52	0.04	0	0
26	0	0.05	IA	IA	IA	0.02	0	0	0.01	0.24	0.01	0.42
27	0	0.01	IA	IA	IA	0.04	0	0	0	0.19	0	1.23
28	0	0	IA	IA	IA	0.37	0.18	0	0.04	0.01	0.06	1.09
29	0	0.01	IA	IA		0.01	0.46	0	0	0.07	0.19	0.01
30	0	0.01	IA	IA		0.05	0	0.03	0	0	0	0.15
31	0		IA	IA		0.28		0		0.02	0	

* IA = Inactive gage during seasonal shutdown.

E265 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.26	1.65	IA ^a	IA	IA	0.84 ^b	1.19	0.94	0.92	1.05	1.09	3.36
Mean Total for Period of Record (in.)	1.16	0.69	IA	IA	IA	IA	0.78	0.94	0.59	2.66	1.69	2.07
Max Daily Total (in.)	0.14	0.67	IA	IA	IA	0.37	0.46	0.65	0.52	0.24	0.20	1.23
Missing Days	0	0	31	31	28	8	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E267.4 TA-36 Minie Site

Location. Lat 35° 49' 38", long -106° 16' 36", Sec. 35, T. 19 N., R. 6 E., Ramon Vigil Land Grant, Santa Fe National Forest.

Period of Record. July 13, 2007, to September 30, 2017.

Gage. Elevation of gage is 6865 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.13 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.23 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. The equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for November 30, 2016, to March 22, 2017, when the gage was shut down for winter.



E267.4 Precipitation gage

E267.4 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.21	0	0.15	0	0	0.05
2	0.06	0	IA	IA	IA	IA	0.17	0	0	0	0	0
3	0.01	0	IA	IA	IA	IA	0.03	0	0	0	0.18	0
4	0	0.42	IA	IA	IA	IA	0.13	0	0	0.01	0.02	0
5	0	0.11	IA	IA	IA	IA	0	0	0	0	0.03	0
6	0	0.02	IA	IA	IA	IA	0	0	0.39	0	0.06	0
7	0	0	IA	IA	IA	IA	0	0	0.25	0.02	0.06	0.03
8	0.11	0	IA	IA	IA	IA	0	0	0	0	0.06	0.02
9	0.09	0.01	IA	IA	IA	IA	0	0.33	0	0.01	0	0
10	0	0.2	IA	IA	IA	IA	0	0.04	0	0	0	0
11	0	0.01	IA	IA	IA	IA	0	0	0	0.03	0.47	0
12	0	0	IA	IA	IA	IA	0	0	0	0.11	0	0.3
13	0	0	IA	IA	IA	IA	0	0	0	0.15	0.03	0
14	0	0	IA	IA	IA	IA	0	0	0	0.01	0.07	0.04
15	0	0	IA	IA	IA	IA	0	0	0	0	0	0
16	0	0	IA	IA	IA	IA	0	0	0.02	0	0	0
17	0	0	IA	IA	IA	IA	0	0.01	0	0	0	0
18	0	0	IA	IA	IA	IA	0	0.02	0	0.08	0	0
19	0	0	IA	IA	IA	IA	0	0.16	0	0	0.01	0
20	0	0.02	IA	IA	IA	IA	0	0	0	0	0.32	0
21	0	0.6	IA	IA	IA	IA	0	0	0.04	0	0.02	0
22	0	0.03	IA	IA	IA	IA	0	0	0.01	0.2	0	0
23	0	0.01	IA	IA	IA	0.03	0	0	0	0	0.04	0.21
24	0	0	IA	IA	IA	0.02	0	0	0.03	0.09	0.07	0
25	0	0	IA	IA	IA	0	0.09	0	0.49	0.02	0	0
26	0	0.07	IA	IA	IA	0	0	0	0.07	0.17	0.2	0.36
27	0	0.02	IA	IA	IA	0.03	0	0	0	0.23	0	1.23
28	0	0	IA	IA	IA	0.02	0.21	0	0	0.06	0.02	0.96
29	0	0.01	IA	IA		0.69	0.37	0	0	0.62	0.04	0.05
30	0	IA	IA	IA		0	0.01	0	0	0.01	0	0.11
31	0.01		IA	IA		0.01		0		0.06	0	

* IA = Inactive gage during seasonal shutdown.

E267.4 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.28	1.53	IA ^a	IA	IA	0.80 ^b	1.22	0.56	1.45	1.88	1.70	3.36
Mean Total for Period of Record (in.)	1.25	0.54	IA	IA	IA	IA	0.72	0.97	0.65	2.59	2.03	2.17
Max Daily Total (in.)	0.11	0.60	IA	IA	IA	0.69	0.37	0.33	0.49	0.62	0.47	1.23
Missing Days	0	0	18	31	29	11	0	0	0	0	0	0

^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

E340 Chaquehui Tributary at TA-33

Location. Lat 35° 46' 46", long -106° 15' 1", Sec. 19, T. 18 N., R. 7 E., Ramon Vigil Land Grant, Los Alamos County.

Period of Record. May 16, 2007, to September 30, 2017.

Gage. Elevation of gage is 6423 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 1.19 in. on July 19, 2007.

Maximum Daily Total Precipitation for Monsoon Season. 1.16 in. on September 27, 2017.

Equipment. The station is equipped with a Rain Collection II tipping bucket rain gage. Equipment is powered with a solar-panel battery-charging system.

Precipitation Record. The precipitation gage gave a complete and satisfactory record, except for December 1, 2016, to March 21, 2017, when the gage was shut down for winter.



E340 Precipitation gage

E340 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	IA*	IA	IA	IA	0.33	0	0.01	0	0.01	0.08
2	0.07	0	IA	IA	IA	IA	0.15	0	0	0	0.01	0
3	0	0	IA	IA	IA	IA	0.01	0	0	0	0.04	0
4	0	0.48	IA	IA	IA	IA	0.07	0	0	0	0.11	0
5	0	0.46	IA	IA	IA	IA	0	0	0	0	0	0
6	0	0	IA	IA	IA	IA	0	0	0.1	0.01	0.02	0
7	0	0.01	IA	IA	IA	IA	0	0	0.04	0	0.01	0.03
8	0.14	0.01	IA	IA	IA	IA	0	0.01	0	0	0	0
9	0.05	0	IA	IA	IA	IA	0	0.74	0	0	0	0
10	0	0	IA	IA	IA	IA	0	0.02	0	0.03	0	0
11	0	0	IA	IA	IA	IA	0	0	0	0.03	0.21	0
12	0	0	IA	IA	IA	IA	0	0	0	0.18	0.01	0.07
13	0	0.01	IA	IA	IA	IA	0	0	0.01	0.08	0	0
14	0	0	IA	IA	IA	IA	0	0	0	0	0.09	0.06
15	0	0	IA	IA	IA	IA	0	0	0	0	0	0.05
16	0	0	IA	IA	IA	IA	0	0	0	0	0	0
17	0	0	IA	IA	IA	IA	0	0	0	0	0	0
18	0	0	IA	IA	IA	IA	0	0.03	0	0	0	0
19	0	0	IA	IA	IA	IA	0	0.17	0	0	0.01	0.02
20	0	0.03	IA	IA	IA	IA	0	0	0	0	0.15	0
21	0	0.43	IA	IA	IA	IA	0	0	0.17	0	0.01	0
22	0	0	IA	IA	IA	0	0	0	0.03	0	0	0
23	0	0.01	IA	IA	IA	0.06	0	0.02	0	0	0.02	0.25
24	0	0.01	IA	IA	IA	0	0	0	0.03	0.21	0	0
25	0	0	IA	IA	IA	0	0.05	0	0.98	0.08	0	0.01
26	0	0.07	IA	IA	IA	0	0.01	0.01	0.04	0.08	0	0.52
27	0	0	IA	IA	IA	0.01	0	0	0	0.12	0	1.16
28	0	0	IA	IA	IA	0.09	0.24	0	0	0.04	0.26	1.09
29	0	0.01	IA	IA		0.1	0.55	0.01	0	0.06	0.08	0.02
30	0	0	IA	IA		0.02	0	0	0	0	0	0.16
31	0		IA	IA		0.03		0.02		0.02	0	

* IA = Inactive gage during seasonal shutdown.

E340 Monthly Total Precipitation (in.)

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.26	1.53	IA ^a	IA	IA	0.31 ^b	1.41	1.03	1.41	0.94	1.04	3.52
Mean Total for Period of Record (in.)	1.02	0.72	IA	IA	IA	IA	0.80	0.82	0.60	2.56	1.60	1.97
Max Daily Total (in.)	0.14	0.48	IA	IA	IA	0.10	0.55	0.74	0.98	0.21	0.26	1.16
Missing Days	0	0	31	31	28	21	0	0	0	0	0	0


^a IA = Inactive gage during seasonal shutdown.^b Partial month because of inactivity, maintenance, or equipment failure.

Meteorological Tower Data

The meteorological network is a comprehensive system that measures temperature, wind, humidity, pressure, precipitation, insolation, and other meteorological variables required for DOE facilities. The collected data play a critical role in emergency planning in the event of chemical or radiological release, demonstrating regulatory compliance in the areas of air quality, water quality, and waste management as well as supporting monitoring programs in biology, hydrology, and health physics. Each station is named according to its location.

Precipitation gages from LANL's meteorological towers located throughout LANL collect 15-min precipitation data using heated tipping buckets. During snow precipitation events, the data are measured estimates of the amount of liquid precipitation from the total amount of snow. These data are commonly referred to as the snow-water equivalent. Monthly data are compiled from each meteorological tower to show monthly precipitation amounts. LANL meteorologists qualify the meteorological tower precipitation data. The data are either evaluated to be good or are replaced with a numerical code for missing data. Estimates are not made for missing data. Further documentation and precipitation information data can be found at <https://envweb.lanl.gov/weathermachine>.

Figure 10 shows the total monthly precipitation at each of the five meteorological towers from October 2016 to September 2017.



Note: The gages are listed in ascending order by elevation from TA-54 (6553 ft) to TA-06 (7427 ft).

Figure 10 The total monthly precipitation for the meteorological towers for WY 2017.

TA-06 Meteorological Tower

Location. Lat 35° 51' 41", long -106 19' 10.2102", NW ¼, Sec. 21, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. February 1, 1990, to September 30, 2017.

Gage. Elevation of gage is 7423 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.92 in. on September 13, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.59 in. on September 27, 2017.

Equipment. The precipitation gage consists of a heated tipping bucket with wind screen.

Precipitation Record. The precipitation gage gave a complete and satisfactory record for the year.



TA-06 Meteorological tower

TA-06 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0.03	0	0	0.47	0	0.14	0	0	0.31
2	0	0	0.05	0	0	0	0	0	0.01	0	0	0
3	0	0	0	0	0	0	0.01	0	0	0	0.08	0
4	0	0.62	0	0	0	0	0.26	0	0	0	0	0
5	0	0.76	0	0.33	0	0	0	0	0	0	0	0
6	0	0	0	0.05	0	0	0	0	0.56	0	0.11	0
7	0	0	0	0	0	0	0	0	0.01	0.03	0.09	0.04
8	0.25	0	0	0	0	0	0	0.01	0	0.07	0.07	0
9	0.07	0	0	0.04	0	0	0	0.41	0	0	0	0
10	0	0	0	0.01	0	0	0	0.08	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0.48	0
12	0	0	0	0	0.16	0	0	0	0	0.37	0	0.01
13	0	0	0	0	0.18	0	0	0	0	0.01	0	0
14	0	0	0	0.15	0	0	0	0	0	0	0.02	0.05
15	0	0	0	0.67	0	0	0	0	0	0	0	0
16	0	0	0.25	0.45	0	0	0	0	0	0	0	0
17	0	0	0.1	0.01	0	0	0	0	0	0	0	0.02
18	0	0	0	0	0	0	0	0	0	0.24	0	0
19	0	0	0	0	0.01	0	0	0.18	0	0	0.02	0
20	0	0	0	0.07	0	0	0	0	0.01	0	0.03	0
21	0	0.49	0	0.33	0	0	0	0	0	0	0.29	0
22	0	0	0.47	0	0	0	0	0	0.01	0	0	0
23	0	0	0	0.05	0	0.12	0	0	0	0	0.21	0.17
24	0	0	0.2	0.04	0	0	0	0	0.02	0.02	0.06	0
25	0	0	0.16	0	0	0.01	0.07	0	0.69	0.06	0	0
26	0	0	0	0	0	0	0	0	0.46	0.45	0.04	0.62
27	0	0.14	0	0	0.03	0	0	0	0	0.18	0	1.59
28	0	0	0	0	0.18	0.25	0.3	0	0	0.02	0.01	1.01
29	0	0.03	0	0		0.33	0.22	0.04	0	0.48	0.01	0.49
30	0	0	0	0		0	0	0.01	0	0	0	0.26
31	0		0	0		0		0		0.14	0	

TA-06 Monthly Total Precipitation (in.), October 2016–September 2017

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.32	2.04	1.23	2.23	0.56	0.71	1.33	0.73	1.91	2.07	1.52	4.57
Mean Total for Period of Record (in.)	1.54	0.94	0.97	0.86	0.75	0.92	0.94	1.22	1.13	2.88	3.35	2.08
Max Daily Total (in.)	0.25	0.76	0.47	0.67	0.18	0.33	0.47	0.41	0.69	0.48	0.48	1.59
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0

TA-49 Meteorological Tower

Location. Lat 35° 48' 48", long -10617' 57.483", T. 18 N., R. 6 E., Ramon Vigil Land Grant.

Period of Record. June 24, 1987, to September 30, 2017.

Gage. Elevation of gage is 7045 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 3.68 in. on February 27, 1988.

Maximum Daily Total Precipitation for Monsoon Season. 1.42 in. on September 27, 2017.

Equipment. The precipitation gage consists of a heated tipping bucket with wind screen.

Precipitation Record. The precipitation gage gave a complete and satisfactory record for the year.



TA-49 Precipitation gage

TA-49 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0.04	0	0	0.49	0	0.09	0	0	0.03
2	0	0	0.06	0	0	0	0	0	0	0	0	0
3	0.06	0	0	0	0	0	0	0	0	0	0.09	0
4	0	0.54	0	0	0	0	0.17	0	0	0	0.06	0
5	0	0.54	0	0.32	0	0	0	0	0	0	0	0
6	0	0.01	0	0.05	0	0	0	0	0.4	0	0.03	0
7	0	0	0	0	0	0	0	0	0.02	0	0.01	0.02
8	0.14	0	0	0	0	0	0	0	0.01	0.01	0.03	0
9	0.08	0	0	0.01	0	0	0	0.52	0	0	0	0
10	0	0	0	0	0	0	0	0.02	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0.05	0.67	0
12	0	0	0	0	0.22	0	0	0	0	0.25	0	0.06
13	0	0	0	0	0.25	0	0	0	0	0.23	0	0
14	0	0	0	0.2	0	0	0	0	0	0	0.01	0.04
15	0	0	0	0.72	0	0	0	0	0	0	0	0
16	0	0	0.17	0.23	0	0	0	0	0	0	0	0
17	0	0	0.09	0.02	0	0	0	0.01	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0.26	0	0
19	0	0	0	0	0.01	0	0	0.16	0	0	0.09	0
20	0	0	0	0.08	0	0	0	0	0	0	0.04	0
21	0	0.75	0	0.43	0	0	0	0	0.05	0	0.31	0
22	0	0.03	0.54	0	0	0.08	0	0	0.03	0.59	0	0
23	0	0	0.02	0.06	0	0	0	0	0	0	0.07	0.19
24	0	0	0.15	0.02	0	0	0	0	0.02	0.03	0.01	0
25	0	0	0.1	0	0	0	0.07	0	1.08	0.05	0	0
26	0	0	0	0	0	0.01	0	0	0.1	0.26	0.18	0.57
27	0	0.1	0	0	0.03	0.56	0	0	0	0.21	0	1.42
28	0	0	0	0	0.14	0.28	0.23	0	0	0.1	0.01	0.66
29	0	0	0	0		0	0.33	0	0	0.54	0.05	0.59
30	0	0	0	0		0	0	0	0	0.01	0	0.12
31	0		0	0		0.49		0		0.06	0	

TA-49 Monthly Total Precipitation (in.), October 2016–September 2017

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.28	1.97	1.13	2.18	0.65	1.42	1.29	0.71	1.8	2.65	1.66	3.7
Mean Total for Period of Record (in.)	1.46	0.90	0.89	0.91	0.88	0.90	0.86	1.15	0.95	2.62	3.01	2.03
Max Daily Total (in.)	0.14	0.75	0.54	0.72	0.25	0.56	0.49	0.52	1.08	0.59	0.67	1.42
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0

TA-53 Meteorological Tower

Location. Lat 35° 52' 12", long -106° 15' 15", NW ¼, Sec. 24, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. February 8, 1992, to September 30, 2017.

Gage. Elevation of gage is 6992 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.01 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.41 in. on September 27, 2017.

Equipment. The precipitation gage consists of a heated tipping bucket with wind screen.

Precipitation Record. The precipitation gage gave a complete and satisfactory record for the year.



TA-53 Precipitation gage (foreground) and meteorological tower (background)

TA-53 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0.02	0	0	0.32	0	0.18	0	0	0.05
2	0.08	0	0.04	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0.05	0
4	0	0.48	0	0	0	0	0.12	0	0	0	0	0
5	0	0.59	0	0.24	0	0	0	0	0.01	0	0	0
6	0	0	0	0.04	0	0	0	0	0.31	0	0.03	0
7	0	0	0	0	0	0	0	0	0.17	0.08	0.49	0.01
8	0.08	0	0	0	0	0	0	0	0	0.2	0.01	0
9	0.1	0	0	0.02	0	0	0	0.36	0	0.43	0	0
10	0	0	0	0	0	0	0	0.14	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0.02	0.36	0
12	0	0	0	0	0.18	0	0	0	0	0.02	0	0.06
13	0	0	0	0	0.19	0	0	0	0	0.05	0	0
14	0	0	0.19	0.1	0	0	0	0	0	0.02	0.13	0
15	0	0	0	0.7	0	0	0	0	0	0	0	0
16	0	0	0.14	0.21	0	0	0	0	0	0.04	0	0
17	0	0	0.07	0	0	0	0	0	0	0	0	0.02
18	0	0	0	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0.21	0	0	0	0
20	0	0.02	0	0.04	0	0	0	0	0	0	0.04	0
21	0	0.41	0	0.31	0	0	0	0	0	0	0.21	0
22	0	0	0.38	0	0	0	0	0	0.09	0.04	0.01	0
23	0	0	0.01	0.05	0	0.1	0	0	0	0	0.01	0.15
24	0	0	0.14	0.01	0	0	0	0	0	0.01	0.09	0
25	0	0	0.08	0	0	0	0.04	0	0.17	0.01	0	0
26	0	0	0	0	0	0	0	0	0.02	0.48	0.02	0.36
27	0	0	0	0	0.03	0.05	0	0	0	0.65	0	1.41
28	0	0	0	0	0.11	0.17	0.27	0	0	0.01	0.05	0.61
29	0	0	0	0		0.3	0.51	0.05	0	0.15	0.18	0.41
30	0	0	0	0		0	0	0	0	0	0	0.19
31	0		0	0		0.02		0		0.06	0	

TA-53 Monthly Total Precipitation (in.), October 2016–September 2017

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.26	1.5	1.05	1.74	0.51	0.64	1.26	0.76	0.95	2.27	1.68	3.27
Mean Total for Period of Record (in.)	1.36	0.66	0.70	0.74	0.66	0.79	0.82	1.10	0.82	1.99	2.44	1.56
Max Daily Total (in.)	0.1	0.59	0.38	0.7	0.19	0.3	0.51	0.36	0.31	0.65	0.49	1.41
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0

TA-54 White Rock Meteorological Tower

Location. Lat 35° 49' 33", long -106° 13' 24", T. 18 N., R. 7 E., Ramon Vigil Land Grant.

Period of Record. January 29, 1992, to September 30, 2017.


Gage. Elevation of gage is 6553 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 3.28 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.58 in. on September 27, 2017.

Equipment. The precipitation gage consists of a heated tipping bucket with wind screen.

Precipitation Record. The precipitation gage gave a complete and satisfactory record for the year.



TA-54 Meteorological tower

TA-54 Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0.03	0	0	0.32	0	0.09	0	0	0.05
2	0	0	0.03	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0.04	0
4	0.14	0.29	0	0	0	0	0.08	0	0.01	0	0	0
5	0	0.6	0	0.24	0	0	0	0	0	0	0	0
6	0	0	0	0.04	0	0	0	0	0.14	0	0.01	0.01
7	0	0	0	0	0	0	0	0	0.03	0.05	0.14	0
8	0.14	0	0	0	0	0	0	0	0	0	0.06	0
9	0.15	0	0	0	0	0	0	0.43	0	0.06	0.08	0
10	0	0	0	0	0	0	0	0.04	0	0.18	0	0
11	0	0	0	0	0	0	0	0	0	0	0.16	0
12	0	0	0	0	0.11	0	0	0	0	0.01	0	0.08
13	0	0	0	0	0.18	0	0	0	0	0.09	0.23	0
14	0	0	0	0.09	0	0	0	0	0	0	0.21	0.02
15	0	0	0	0.76	0	0	0	0	0	0	0	0
16	0	0	0.12	0.19	0	0	0	0	0	0	0	0
17	0	0	0.07	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0	0.02	0	0
19	0	0	0	0	0	0	0	0.16	0	0	0	0
20	0	0	0	0.06	0	0	0	0	0	0	0.02	0
21	0	0.49	0	0.34	0	0	0	0	0	0	0.08	0
22	0	0	0.39	0	0	0.06	0	0	0.03	0.04	0	0
23	0	0	0	0.01	0	0	0	0.09	0	0	0	0.18
24	0	0	0.05	0	0	0	0	0	0	0.07	0	0
25	0	0	0.07	0	0	0	0.06	0	0.17	0.01	0	0
26	0	0	0	0	0	0.01	0	0	0	0.31	0.01	0.35
27	0	0.05	0	0	0.03	0.54	0	0	0	0.18	0	1.19
28	0	0	0	0	0.06	0.14	0.2	0	0	0.05	0	0.89
29	0	0	0	0		0	0.63	0.01	0	0.05	0.03	0.38
30	0	0	0	0		0.02	0	0	0	0.01	0	0.17
31	0		0	0		0.32		0		0.03	0	

TA-54 Monthly Total Precipitation (in.), October 2016–September 2017

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.43	1.43	0.73	1.76	0.38	1.09	1.29	0.73	0.47	1.16	1.07	3.32
Mean Total for Period of Record (in.)	1.42	0.67	0.67	0.61	0.53	0.75	0.74	0.92	0.92	2.04	2.39	1.60
Max Daily Total (in.)	0.15	0.6	0.39	0.76	0.18	0.54	0.63	0.43	0.17	0.31	0.23	1.19
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0

North Community Meteorological Tower

Location. Lat 35° 54' 3", long -106° 19' 18", NE ¼, Sec. 5, T. 19 N., R. 6 E., Los Alamos County.

Period of Record. January 1, 1986, to September 30, 2017.

Gage. Elevation of gage is 7414 ft using LANL LIDAR DEM with NAD 83.

Maximum Daily Total Precipitation for Period of Record. 2.58 in. on September 12, 2013.

Maximum Daily Total Precipitation for Monsoon Season. 1.54 in. on September 27, 2017.

Equipment. The precipitation gage consists of a heated tipping bucket with wind screen.

Precipitation Record. The precipitation gage gave a complete and satisfactory record for the year.

No image available for the North Community precipitation gage.

North Community Daily Total Precipitation (in.)

Day	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
1	0	0	0	0.01	0	0	0.38	0	0.14	0	0	0.14
2	0	0	0.05	0	0	0	0.03	0	0.01	0	0	0
3	0.13	0	0	0	0	0	0	0	0	0	0	0
4	0	0.62	0	0	0	0	0.27	0	0	0	0.12	0
5	0	0.71	0	0.24	0	0	0	0	0	0	0	0
6	0	0	0	0.07	0	0	0	0	0.08	0	0.25	0
7	0	0	0	0	0	0	0	0	0.01	0	0.08	0
8	0.1	0	0	0	0	0	0	0	0	0.01	0.01	0
9	0.01	0	0	0.05	0	0	0	0.37	0	0	0	0
10	0	0	0	0.01	0	0	0	0.15	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0.56	0
12	0	0	0	0	0.08	0	0	0	0	0.06	0.01	0.12
13	0	0	0	0	0.25	0	0	0	0	0.07	0	0
14	0	0	0	0.14	0	0	0	0	0	0	0.16	0.05
15	0	0	0	0.72	0	0	0	0	0	0	0	0
16	0	0	0.32	0.35	0	0	0	0	0	0	0	0
17	0	0	0.1	0.18	0	0	0	0	0	0	0	0.01
18	0	0	0	0	0	0	0	0	0	0.34	0	0
19	0	0	0	0	0	0	0	0.1	0	0	0.12	0
20	0	0	0	0.04	0	0	0	0	0	0	0.02	0
21	0	0.45	0	0.3	0	0	0	0	0	0	0.25	0
22	0	0	0.32	0	0	0	0	0	0.04	0	0	0
23	0	0	0.09	0.06	0	0.14	0	0	0	0	0.33	0.16
24	0	0	0.16	0.03	0	0.01	0	0	0	0.02	0.14	0
25	0	0	0.14	0	0	0.05	0.08	0	0.23	0.21	0	0
26	0	0	0	0	0	0.01	0	0	0.36	0.18	0.01	0.56
27	0	0.14	0	0	0.05	0	0.01	0	0	0.21	0	1.54
28	0	0	0	0	0.15	0.07	0.38	0	0	0	0.01	0.65
29	0	0	0	0		0.31	0.23	0.1	0	0.56	0.05	0.35
30	0	0	0	0		0	0	0.1	0	0.12	0	0.58
31	0		0	0		0		0		0.07	0	

North Community Monthly Total Precipitation (in.), October 2016–September 2017

	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep
Total (in.)	0.24	1.92	1.18	2.2	0.53	0.59	1.38	0.82	0.87	1.85	2.12	4.16
Mean Total for Period of Record (in.)	1.61	0.98	0.92	0.92	0.87	0.96	1.08	1.32	1.46	2.99	3.57	1.90
Max Daily Total (in.)	0.13	0.71	0.32	0.72	0.25	0.31	0.38	0.37	0.36	0.56	0.56	1.54
Missing Days	0	0	0	0	0	0	0	0	0	0	0	0

REFERENCES

Carter, R.W., and J. Davidian, 1968. Techniques of Water-Resources Investigations of the United States Geological Survey, General Procedure for Gaging Streams. Book 3, Chapter A6, U.S. Geological Survey.

Kilpatrick, F.A., and V.R. Schneider, 1983. Techniques of Water-Resources Investigations of the United States Geological Survey, General Procedure for Gaging Streams. Book 3, Chapter A14, U.S. Geological Survey.

LANL, September 2011. "Investigation Report for Water Canyon/Cañon de Valle," Los Alamos National Laboratory document LA-UR-11-5478.

LANL, 2015 Site Discharge Pollution Prevention Plan, Revision 1, NPDES Permit No. NM0030759, Volumes 1–5.

National Geodetic Vertical Datum of 1929.

North American Datum of 1983.

Rantz, S.E., 1982. Measurement and Computation of Stream Flow Volume 1: Measurement of Stage and Discharge. Geological Survey Water-Supply Paper 2175. U.S. Geological Survey.

Previous LANL reports in this series: "Surface Water Data at Los Alamos National Laboratory" for WY 1995 to 2014 are available in pdf format. The reports can be accessed at the electronic public reading room at <http://epr.lanl.gov>.

ABBREVIATIONS, ACRONYMS, AND GLOSSARY

Acre-foot (acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equivalent to 43,560 cubic feet, 325,851 gallons, or 1233.49 cubic meters.

CMP is corrugated metal pipe.

Construction General Permit is a permit from the U.S. Environmental Protection Agency that allows for storm water discharges from construction activities.

Control designates a feature downstream from the gage that determines the stage-discharge relation at the gage. This feature may be a natural constriction of the channel, an artificial structure, or a uniform cross-section over a long reach of the channel.

Control structure as used in this report is a structure on a stream or canal used to regulate the flow or stage of the stream.

Cubic feet per second (ft³/s) is the rate of discharge representing a volume of 1 cubic foot passing a given point during 1 second; it is equivalent to 7.48 gallons per second, 448.8 gallons per minute, or 0.02832 cubic meters per second.

DOE is the U.S. Department of Energy.

Discharge is the volume of water (or more broadly, the volume of fluid, including suspended sediment) that passes a given point within a given period of time.

Drainage area of a stream at a specified location is that area measured in a horizontal plane and enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above the specified point. Figures of drainage areas provided herein include all closed basins, or noncontributing areas, within the area, unless otherwise noted.

EPA (U.S. Environmental Protection Agency) is the federal agency that enforces regulations to protect the environment and human health.

Extended precipitation network is the LANL precipitation monitoring gage network from which precipitation data are obtained.

Gage height is the water-surface elevation referred to in some arbitrary gage data. GH is often used interchangeably with the more general term “stage,” although GH is more appropriate when used with a reading on a gage.

Gage station is a particular site on a stream, canal, lake, or reservoir in which systematic observations of hydrologic data are obtained.

GPS is global positioning system.

Individual Permit is a National Pollutant Discharge Elimination System individual permit issued by the EPA that authorizes the discharge of storm water associated with industrial activities at Los Alamos National Laboratory.

Instantaneous discharge is the discharge at a particular instance of time.

ISCO is a reference to Teledyne ISCO, Inc., which is an automated sampler manufacturer.

LANL is Los Alamos National Laboratory.

LIDAR DEM is light detection and ranging digital elevation model.

MDA is material disposal area.

Mean discharge (mean) is the arithmetic mean of individual daily mean discharges during a specific period.

Meteorological observation network is a network of towers that provides year-round meteorological data.

Multi-Sector General Permit is a National Pollutant Discharge Elimination System permit issued by the EPA that authorizes the discharge of storm water associated with industrial activities.

National Geodetic Vertical Datum of 1929 (NGVD 29) is the National standard reference datum for elevations.

NEMA is the National Electrical Manufacturers Association.

North American Datum of 1983 (NAD 83) is the official horizontal datum for use in the North and Central American geodetic networks. Based on the Geodetic Reference System 1980 ellipsoid, it was developed using satellite and remote sensing imagery and is the default datum used at LANL and most global positioning system units today.

NPDES is National Pollutant Discharge Elimination System.

Point of zero flow (PZF) is the gage height at which no flow occurs.

Reference point is a permanent gage height reference used to calibrate stage measurements.

Site Discharge Pollution Prevention Plan is a LANL report updated annually that provides information on each of the seven major watersheds of the Pajarito Plateau and related storm water monitoring activities within the watersheds.

SR means “State Road” and is the former designation for NM 4, NM 501, and NM 502. It appears in gage station names.

Stage see **gage height**.

Stage-discharge relationship is the relation between the water-surface elevation, termed “gage height,” and the volume of water flowing in a channel per unit of time.

Stream flow is the discharge that occurs in a natural channel.

TA is technical area.

USGS is U.S. Geological Survey.

Waste Water Treatment Facility (WWTF) is the Los Alamos County Wastewater Treatment Facility located in TA-74 in Pueblo Canyon. It was previously called the Waste Water Treatment Plant.

Water data report is the USGS report that provides the methodology used for data collection.

Water year (WY) in reports dealing with surface water supply is the 12-mo period, October 1 through September 30. The water year is designated by the calendar year in which it ends and that includes 9 of the 12 mo. Thus, the year ending September 30, 1980, is called the “1980 water year” or WY 1980.

